



CIRCUIT DIAGRAM  
C: COMMON PIN  
BOTTOM VIEW



non-shorting

HOLE LAYOUT  $\pm 0.05$



Specifications:

- Contact rating: 0.1A, 12V DC
- Contact resistance: 500mOhm max.
- Insulation resistance: 100MOhm min. at 500V DC for 1 minute
- Dielectric strength: 500V AC (50/60Hz, 2mA) for 1 minute
- Operating temperature: -40°C to +85°C
- Storage temperature: -40°C to +85°C
- Mechanical life: 10 000 cycles
- Soldering conditions: 260 +/-5°C, 5 +/-1sec.
- Material: Spring plate: phosphor bronze, washing  
Contact clip: phosphor bronze, silver plated  
Slider: PA46, black  
Terminal: brass strip, silver plated  
Base: phenolic resin, natural  
Frame: steel, nickel plated



Tolerances: up to 10: ±0.2mm above 10-50: ±0.3mm	Date	Name
	05/12	dr
Temperatures	12/12	dr
Modifications	Date	Name

**MFP 113 D-RA**

**knitter-switch**

**30 26 36**

Page

1/1

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Slide Switches](#) category:*

*Click to view products by [Knitter-Switch](#) manufacturer:*

Other Similar products are found below :

[6-1437581-1](#) [M43R](#) [MHS123K15D](#) [MHSS1104A](#) [MMD](#) [GH49S010001](#) [GH49WW00001](#) [1437576-8](#) [EPS1PC1](#) [1825074-1](#) [1825160-3](#)  
[1825167-2](#) [25139NLDB](#) [25436NLDB](#) [25449NAH](#) [25536NA](#) [L101011ML04B](#) [SLB1240R45](#) [SLSA12004](#) [1825078-1](#) [1825080-4](#) [1825081-1](#)  
[1825269-1](#) [1825270-2](#) [STS141RA04](#) [T2215BEN506](#) [GF-124-0204](#) [GH46P000001](#) [GH46W000001](#) [GH49P010001](#) [25339NA](#) [25436NLDH](#)  
[CST91246FK](#) [TG36P000000](#) [TG36P000050](#) [47227LFE](#) [49331L](#) [MHSS1105A](#) [50208L](#) [HW4S-5LF22N3](#) [L202091MS02Q](#) [4-1437581-7](#)  
[X2225CR-437W](#) [48BFSP3M2QT](#) [49329L](#) [1101M1S3ZB8E2](#) [1-1437581-1](#) [EG1218REDACTUATOR](#) [TG39W000000](#) [1825075-1](#)