



HOLE LAYOUT



P/N	No. of positions	A	B
MFP 1370-R	3	20.0	7.6
MFP 1470-R	4	20.0	9.9
MFP 1570-R	5	22.0	12.2

SCHEMATIC



Specifications:

- Contact rating: 350mA, 30V DC
- Contact resistance: 25mOhm max.
- Insulation resistance: 100MOhm min.
- Dielectric strength: 500V, 50Hz for the duration of 1 minute
- Mechanical life: min. 10 000 cycles
- Soldering conditions: auto-soldering: 260°C, 10sec. max.
- Timing: non-shorting
- Material: Contacts: copper alloy, silver plated over nickel barrier  
Slide color: black



Tolerances:			Date	Name	<h1>MFP 1x70-R</h1>
			10/95	Ey	
Dimension A	11/14	dr	<b>knitter-switch</b>		<h1>21 13 02</h1>
Soldering conditions	09/05	rs			
RoHS compliant	09/05	rs			
Modifications	Date	Name			Page 1/1

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Slide Switches](#) category:*

*Click to view products by [Knitter-Switch](#) manufacturer:*

Other Similar products are found below :

[6-1437581-1](#) [M43R](#) [MHS123K15D](#) [MHSS1104A](#) [MMD](#) [GH49S010001](#) [GH49WW00001](#) [1437576-8](#) [EPS1PC1](#) [1825074-1](#) [1825160-3](#)  
[1825167-2](#) [25139NLDB](#) [25436NLDB](#) [25449NAH](#) [25536NA](#) [L101011ML04B](#) [SLB1240R45](#) [SLSA12004](#) [1825078-1](#) [1825080-4](#) [1825081-1](#)  
[1825269-1](#) [1825270-2](#) [STS141RA04](#) [T2215BEN506](#) [GF-124-0204](#) [GH46P000001](#) [GH46W000001](#) [GH49P010001](#) [25339NA](#) [25436NLDH](#)  
[CST91246FK](#) [TG36P000000](#) [TG36P000050](#) [47227LFE](#) [49331L](#) [MHSS1105A](#) [50208L](#) [HW4S-5LF22N3](#) [L202091MS02Q](#) [4-1437581-7](#)  
[X2225CR-437W](#) [48BFSP3M2QT](#) [49329L](#) [1101M1S3ZB8E2](#) [1-1437581-1](#) [EG1218REDACTUATOR](#) [TG39W000000](#) [1825075-1](#)