



x	L (mm)
none	5
7C	7
8	8

HOLE LAYOUT $\oplus 0.05$



CIRCUIT DIAGRAM

C: COMMON PIN
BOTTOM VIEW



Specifications:

Contact rating: 350mA, 30V DC
 Contact resistance: 20mOhm max.
 Insulation resistance: 100MOhm min. at 500V DC for 1 minute
 Dielectric strength: 500V AC (50/60Hz, 2mA) for 1 minute
 Operating temperature: -20°C to +85°C
 Mechanical life: 10 000 cycles
 Operating force: 150 +/-70gf
 Soldering conditions: 260 +/-5°C, 5 +/-1sec.
 Material: Terminal: brass strip, silver plated
 Base: phenolic resin, natural
 Steel ball: carbon steel, natural
 Frame: steel, zinc plated
 Contact clip: phosphor bronze, silver plated
 Spring: SWC, temper
 Slider: POM, black



Tolerances: up to 10: ±0.2mm above 10-50: ±0.3mm		Date	Name
		07/10	dr
Revised	04/11	dr	
Modifications	Date	Name	

MFP 220-x

30 21 33

Page

1/1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Slide Potentiometers](#) category:

Click to view products by [Knitter-Switch](#) manufacturer:

Other Similar products are found below :

[M22](#) [MHS133K](#) [MSS12A](#) [MSSA22](#) [M42A](#) [MSS42G](#) [SS-4928](#) [RSA0K11A901L](#) [SLB124145](#) [SLB1340R45](#) [RA6020F-10-20D1-B50K](#)
[RA4520F-10-20D1-B50K](#) [TSS11AGPC](#) [X22205CAAF](#) [448XC2103BDN](#) [X22205A-437W](#) [T22205BAAE](#) [SS-22J08-G5](#) [X22205AAAL](#)
[K22208EAAG](#) [PS15-10PC1BR10K](#) [1101M1S3ZQI2](#) [1201M1S1ZBE2](#) [1101M2S4AGE2](#) [1101M2S6ABE2](#) [1201M1S3ZBE2](#) [EVA-](#)
[JQKR15Y14](#) [EVA-NADR15A14](#) [EVA-NADR15D14](#) [EVA-NE4R15A14](#) [EVB-NADR15Y14](#) [ASE1D](#) [ASE1E](#) [ASE2D](#) [MFP113D](#) [MFP130](#)
[MFP1323](#) [MFP1424](#) [MFP161D](#) [MFP2220R](#) [MFP231P](#) [MFP261N](#) [MMP1010DRA1](#) [MMP131](#) [L202021MS02Q](#) [MFP120](#) [MFP 130 R](#)
[MFP1323R](#) [MFP140](#) [MFP140-R](#)