



HOLE LAYOUT $\oplus 0.05$



CIRCUIT DIAGRAM



C: COMMON PIN
BOTTOM VIEW

Material:

- Base: phenolic resin, natural
- Frame: SPCC, tin plated
- Slider: PBT, black
- Terminal: brass strip, silver plated
- Contact plate: brass strip, silver plated
- Spring: SWC, temper
- RoHS compliant

Maßstab		Datum	Name	<h1>MFP 221 N</h1>
Oberfläche		05/07	dr	
		knitter-switch		<h1>30 11 27</h1>
Zust	Änderung	Datum	Name	Blatt 1/3

SPECIFICATION

1. General				
1) Operating temperature range -10 to 60 °C.				
2) Standard test conditions shall be 5 to 35 °C in temperature and 45 to 85 % in humidity.				
2. Rating DC 30V 0.3A				
3. Change over timing Non-shorting				
4. Electrical performance				
Item	Conditions		Specifications	
1 Contact Resistance	a) 1 KHz +/- 200 Hz (20mA) b) DC 5V 1A by voltage drop method.		30 mohm or less.	
2 Insulation Resistance	DC 500 V 1 minute	between terminals	100 Mohm or more.	
		terminal & frame	100 Mohm or more.	
3 Withstand Voltage	AC 500 V 1 min. (50/60Hz 2mA)	between terminals	No dielectric breakdown.	
	AC 500 V 1 min. (50/60Hz 2mA)	terminal & frame		
5. Mechanical performance				
Item	Conditions		Specifications	
1 Terminal Strength	A static load of 500 gf shall be applied to the tip of the terminals for 15 seconds in any direction. 1 cycle shall be made per 1 terminal.		Electrical performance shall be satisfied. Without damage of excessive looseness of terminals.	
2 Actuator Strength	A static load of 3.0 kgf shall be applied for 15 seconds in a direction reverse to cause actuation of the switch.		Clause 5.4 and electrical performance shall be satisfied. Without excessive looseness of bending to the actuator and stopper.	
3 Displacement of actuator	A static load of 100 gf shall be applied at the point 1 mm from the tip of the actuator and than displacement shall be measured.		1.0 mm p-p or less.	
4 Operating force	Measure at the tip of actuator.		250gf ±100gf	
6. Endurance performance				
Item	Conditions		Specifications	
1 Solderability	Solder temperature 230 ± 5 °C Dipping time 3 ± 0.5 second		More than 75 % of the dipping covered by solder.	
2 Soldering heat resistance	Solder bath method Solder temperature: 260 ± 5 °C Dipping time: 5 ± 1.0 second Thickness of PCB: 1.6 mm Immersion depth: Up to the surface of the board		Without deformation of frame or excessive looseness of terminals. Electrical performance shall be satisfied.	
	Solder iron method Bit temperature: 350 ± 10 °C Application time: 3 ± 1.0 second			
3 Heat Test	The switch shall be stored at a temperature of 70 ± 2 °C for 48 hours. Then the switch shall be maintained standard atmospheric condition for 1 hour, after which measurement shall be made within 1 hour.		Contact Resistance	Less than 100 mohm.
			Insulation resistance	4.2 shall be satisfied
			Operating force	5.4 shall be satisfied
			Terminal strength	5.1 shall be satisfied
			Appearance	No deformation or crack in molded part.
4 Cold Test	The switch shall be stored at a temperature of -25 ± 3 °C for 48 hours. Then the switch shall be maintained standard atmospheric condition for 1 hour, after which measurement shall be made within 1 hour.		Contact Resistance	Less than 100 mohm.
			Insulation resistance	4.2 shall be satisfied
			Operating force	5.4 shall be satisfied
			Appearance	No deformation or crack in molded part.

Maßstab		Datum	Name	MFP 221 N
Oberfläche		05/07	dr	
			knitter-switch	30 11 27
Zust	Änderung	Datum	Name	Blatt 2/3

Item	Conditions	Specifications																		
5 Humidity Test	The switch shall be stored at a temperature of 40 ± 2 °C and a humidity of 90 to 95 % for 96 hours. Then the switch shall be maintained standard atmospheric condition for 1 hour, after which measurement shall be made within 1 hour.	Contact Resistance	Less than 100 mohm.																	
		Insulation resistance	More than 10 Mohm after 500 V DC is applied for 1 minute.																	
		Withstand voltage	Withstand AC 250 V for 1 minute.																	
		Appearance	No deformation or crack in molded part or excessive rust or discoloration.																	
6 Change of temperature	The switch shall be subjected to 5 successive change of temperature cycles, each as shown in table below.	Contact Resistance	Less than 100 mohm.																	
		Insulation resistance	4.2 shall be satisfied																	
		Withstand voltage	4.3 shall be satisfied																	
		Operating force	5.4 shall be satisfied																	
		Appearance	No deformation or crack in molded part.																	
		<table border="1"> <thead> <tr> <th></th> <th>Temperature</th> <th>Duration</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>-10 +/- 3°C</td> <td>30 min.</td> </tr> <tr> <td>2</td> <td>Standard atmospheric condition</td> <td>10-15 min.</td> </tr> <tr> <td>3</td> <td>70 +/- 2°C</td> <td>30 min.</td> </tr> <tr> <td>4</td> <td>Standard atmospheric condition</td> <td>10-15 min.</td> </tr> </tbody> </table>			Temperature	Duration	1	-10 +/- 3°C	30 min.	2	Standard atmospheric condition	10-15 min.	3	70 +/- 2°C	30 min.	4	Standard atmospheric condition	10-15 min.		
			Temperature	Duration																
1	-10 +/- 3°C	30 min.																		
2	Standard atmospheric condition	10-15 min.																		
3	70 +/- 2°C	30 min.																		
4	Standard atmospheric condition	10-15 min.																		
7 Vibration	Only endurance conditioning by a frequency sweep shall be made. The entire frequency range, from 10 to 55 Hz and return to 10 Hz be transversed in 1 minute. Amplitude (total excursion): 1.5 mm This motion shall be applied for a period of 2 hours in each of 3 mutually perpendicular axis (a total of 6 hours).	Terminal strength	5.1 shall be satisfied																	
		Actuator strength	5.2 shall be satisfied																	
		Operating force	5.4 shall be satisfied																	
		Electrical performance shall be satisfied.																		
8 Shock	Peak acceleration: 735 m/s^2 Duration of pulse: 6 msec. Three successive shock shall be applied in both directions of mutually perpendicular axis (a total of 18 shocks).	Terminal strength	5.1 shall be satisfied																	
		Actuator strength	5.2 shall be satisfied																	
		Operating force	5.4 shall be satisfied																	
		Electrical performance shall be satisfied.																		
9 Life test	(Endurance without load) A switch shall be subject to 5,000 cycles at a speed of 15 to 20 cycles per min. without load.	Contact resistance	Less than 100 mohm.																	
		Insulation resistance	More than 10 Mohm after 500 V DC is applied for 1 minute.																	
		Withstand voltage	Withstand AC 250 V for 1 minute.																	
		Operating force	Relative to the previously specified value. $\pm 30\%$																	

Maßstab		Datum	Name	MFP 221 N
Oberfläche		05/07	dr	
		knitter-switch		30 11 27
Zust	Änderung	Datum	Name	Blatt 3/3

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Toggle Switches](#) category:

Click to view products by [Knitter-Switch](#) manufacturer:

Other Similar products are found below :

[A19HV](#) [8A1-C-222](#) [60012L](#) [6006L](#) [6663](#) [7101MD9V30GE](#) [7101SPDV30BE](#) [7103SDV30BE](#) [7105D](#) [7108P3YAV2BE](#) [71YY50282](#)
[7201MD9AVBE](#) [7301K38](#) [7306K36](#) [7310K36](#) [7314K36](#) [7506K4](#) [7592K6](#) [7691K14](#) [7700K1](#) [8396K108](#) [8824K14](#) [8828K13](#) [G3VX](#) [PS83-](#)
[121G](#) [A101MD9AB04](#) [A101SD9AB04](#) [A101SDCQ04](#) [A103SD9AQ04](#) [A107TZB04](#) [A123P32YZQ](#) [A123S1YZG](#) [A127S1YCQ](#) [1-1825192-](#)
[0](#) [A131S1YZQ](#) [A201SCWZB04](#) [A207SYCB04](#) [A208J61ZQ0004](#) [A221K12KAG](#) [A221S1YZQ](#) [A221T1TCQ](#) [A232K12KZQ](#) [A232M1YCQ](#)
[A323S1CWZQ](#) [A423S1YZQ](#) [12149A-3V](#) [12156AX408](#) [12147AGKX679](#) [12149AD2G0383VX408](#) [12246X778](#)