



Specifications:

- Contact rating: 0.2A, 30V DC
- Contact resistance: 20mOhm max.
- Insulation resistance: 100MOhm min. at 500V DC for 1 minute
- Dielectric strength: 500V AC for 1 minute (50/60Hz, 2mA)
- Operating temperature: -10°C to +60°C
- Mechanical life: 10 000 cycles min.
- Operating force: a-b c-b: 200gf +/-100gf
b-a b-c: 250gf +/-150gf
- Soldering heat resistance: bath method: 260 +/-5°C; 5 +/-1.0sec.
- Contact timing: shorting
- Switching functio: on - on - on
- RoHS compliant
- Material: Slider: POM, black
Frame: SPCC, nickel plated
Spring: SWC, temper
Steel ball: carbon steel, natural
Contact slip: C5210R-EH, silver plated
Base: phenolic resin, natural
Terminal: brass strip, silver plated

Maßstab		Datum	Name
Oberfläche		07/05	dr
Material	07/07	dr	knitter-switch
Soldering cond.	01/06	dr	
Zust	Änderung	Datum	Name

MFP 223 P

30 06 51

Blatt
1/1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Toggle Switches](#) category:

Click to view products by [Knitter-Switch](#) manufacturer:

Other Similar products are found below :

[A19HV](#) [8A1-C-222](#) [60012L](#) [6006L](#) [6663](#) [7101MD9V30GE](#) [7101SPDV30BE](#) [7103SDV30BE](#) [7105D](#) [7108P3YAV2BE](#) [71YY50282](#)
[7201MD9AVBE](#) [7301K38](#) [7306K36](#) [7310K36](#) [7314K36](#) [7506K4](#) [7592K6](#) [7691K14](#) [7700K1](#) [8396K108](#) [8824K14](#) [8828K13](#) [G3VX](#) [PS83-](#)
[121G](#) [A101MD9AB04](#) [A101SD9AB04](#) [A101SDCQ04](#) [A103SD9AQ04](#) [A107TZB04](#) [A123P32YZQ](#) [A123S1YZG](#) [A127S1YCQ](#) [1-1825192-](#)
[0](#) [A131S1YZQ](#) [A201SCWZB04](#) [A207SYCB04](#) [A208J61ZQ0004](#) [A221K12KAG](#) [A221S1YZQ](#) [A221T1TCQ](#) [A232K12KZQ](#) [A232M1YCQ](#)
[A323S1CWZQ](#) [A423S1YZQ](#) [12149A-3V](#) [12156AX408](#) [12147AGKX679](#) [12149AD2G0383VX408](#) [12246X778](#)