


SCHMATIC



Specifications:

- Contact rating: 0.35A, 30V DC
- Contact resistance: 20mOhm max.
- Insulation resistance: 100MOhm min.
- Dielectric strength: 500V, 50Hz for the duration of 1 minute
- Operating temperature: -10°C to +70°C
- Storage temperature: -30°C to +85°C
- Mechanical life: 10 000 cycles min.
- Soldering conditions: see process limitation below
- Timing: non-shorting
- Material: Contacts: copper alloy, silver plated over nickel
Housing: plastic
- Process limitation: JEDEC J-STD-075 class W4Y
pre-heat max. 100°C / max. 60sec.
time in wave 5sec. max.
terminal peak temperature 260°C
1 pass
no liquid cleaning



Tolerances:	Date	Name
	10/03	tm
Process limitation	05/09	dr
Modifications	Date	Name

MFP 461 N

30 03 94

Page

1/1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Slide Switches](#) category:

Click to view products by [Knitter-Switch](#) manufacturer:

Other Similar products are found below :

[6-1437581-1](#) [M43R](#) [MHS123K15D](#) [MHSS1104A](#) [MMD](#) [GH49S010001](#) [GH49WW00001](#) [1437576-8](#) [EPS1PC1](#) [1825074-1](#) [1825160-3](#)
[1825167-2](#) [25139NLDB](#) [25436NLDB](#) [25449NAH](#) [25536NA](#) [L101011ML04B](#) [SLB1240R45](#) [SLSA12004](#) [1825078-1](#) [1825080-4](#) [1825081-1](#)
[1825269-1](#) [1825270-2](#) [STS141RA04](#) [T2215BEN506](#) [GF-124-0204](#) [GH46P000001](#) [GH46W000001](#) [GH49P010001](#) [25339NA](#) [25436NLDH](#)
[CST91246FK](#) [TG36P000000](#) [TG36P000050](#) [47227LFE](#) [49331L](#) [MHSS1105A](#) [50208L](#) [HW4S-5LF22N3](#) [L202091MS02Q](#) [4-1437581-7](#)
[X2225CR-437W](#) [48BFSP3M2QT](#) [49329L](#) [1101M1S3ZB8E2](#) [1-1437581-1](#) [EG1218REDACTUATOR](#) [TG39W000000](#) [1825075-1](#)