


P.C. LAYOUT



CONTACT ARRANGEMENT:

code for x	function	actuator in position 1	actuator opposite to pos. 1
D	On-On	1-2	2-3

code for x	function	actuator in position 1	actuator in center	actuator opposite to pos. 1
E	On-Off-On	1-2	open	2-3

RATING AND CONTACT/TERMINAL MATERIAL:

y	contacts	terminals	rating
empty	silver plated, copper alloy	silver plated, copper alloy	28 VDC / 3 A 120 VAC / 3 A 250 VAC / 1 A * see remark
B	gold plated over nickel	gold plated over nickel	0.4 VA, 20 V AC/DC

Specifications:

Contact resistance: 50mOhm max.
 Insulation resistance: 1 000MOhm min.
 Dielectric strength: 1 000V RMS
 Operating temperature: -40°C to +85°C
 Mechanical life: 20 000 make-and-break cycles
 Soldering conditions: auto-soldering: 260 +/-5°C, max. 10sec.
 Material: Case: nylon, white
 Actuator / housing: nylon, black
 *Remark: Breaking capacity: 1A, 250V AC wit resistive load
 Min. load: 100mA, 10V DC

Compliance: RohS II (2011/65/EU)

Tolerances:			Date	Name	MSS 3111 xy-R	
			03/06	dr		
Rename	09/15	dr	knitter-switch		30 08 25	Page
Dimensions	11/08	dr				1/1
Specifications	05/08	dr				
Modifications	Date	Name				

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Slide Switches](#) category:

Click to view products by [Knitter-Switch](#) manufacturer:

Other Similar products are found below :

[6-1437581-1](#) [M43R](#) [MHS123K15D](#) [MHS133K](#) [MHSS1104A](#) [MMD](#) [GH49S010001](#) [MSS12A](#) [EPS1PC1](#) [1825160-3](#) [1825167-2](#) [K232CB](#)
[25139NLDB](#) [25449NAH](#) [SLB1240R45](#) [1825078-1](#) [1825080-4](#) [1825269-1](#) [1825270-2](#) [STS141RA04](#) [T2215BEN506](#) [GH46P000001](#)
[GH46W000001](#) [GH49P010001](#) [25339NA](#) [M42A](#) [TG36P000000](#) [TG36P000050](#) [AYZ0202AG](#) [47227LFE](#) [49331L](#) [50208L](#) [L203091MS02Q](#)
[4-1437581-7](#) [X2225CR-437W](#) [49329L](#) [1101M1S3ZB8E2](#) [1-1437581-1](#) [MSS2225G04](#) [TG39W000000](#) [1825075-1](#) [MSS42G](#) [TG36WS80065](#)
[T105S1CWZBE](#) [SLB124145](#) [SLB1280R5](#) [SLB1340R45](#) [25136NLDB](#) [TG39W000050](#) [4021.4621](#)