


P.C. MOUNTING



Specifications:

- Contact rating: 1A, 250V AC; 3A, 120V AC or 28V DC
- Contact resistance: 50mOhm max.
- Insulation resistance: 1 000MOhm min.
- Dielectric strength: 1 000V RMS
- Operating temperature: -40°C to +85°C
- Mechanical life: 20 000 make-and-break cycles
- Breaking capacity: 1A, 250V AC with resistive load
- Min. load: 100mA, 10V DC
- Soldering conditions: auto-soldering: 260 +/-5°C, max. 10sec.
- Switching function: on - on
- Material: Case: nylon, white
Actuator / housing: nylon, black
Terminals / contact: silver plated copper alloy



Tolerances:			Date	Name
			03/06	dr
Specifications	05/08	dr		
Modifications	Date	Name		

MSS 3112 D

knitter-switch

30 08 17

Page

1/1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Slide Switches](#) category:

Click to view products by [Knitter-Switch](#) manufacturer:

Other Similar products are found below :

[6-1437581-1](#) [M43R](#) [MHS123K15D](#) [MHS133K](#) [MHSS1104A](#) [MMD](#) [GH49S010001](#) [MSS12A](#) [EPS1PC1](#) [1825160-3](#) [1825167-2](#) [K232CB](#)
[25139NLDB](#) [25449NAH](#) [SLB1240R45](#) [1825078-1](#) [1825080-4](#) [1825269-1](#) [1825270-2](#) [STS141RA04](#) [T2215BEN506](#) [GH46P000001](#)
[GH46W000001](#) [GH49P010001](#) [25339NA](#) [M42A](#) [TG36P000000](#) [TG36P000050](#) [AYZ0202AG](#) [47227LFE](#) [49331L](#) [50208L](#) [L203091MS02Q](#)
[4-1437581-7](#) [X2225CR-437W](#) [49329L](#) [1101M1S3ZB8E2](#) [1-1437581-1](#) [MSS2225G04](#) [TG39W000000](#) [1825075-1](#) [MSS42G](#) [TG36WS80065](#)
[T105S1CWZBE](#) [SLB124145](#) [SLB1280R5](#) [SLB1340R45](#) [25136NLDB](#) [TG39W000050](#) [4021.4621](#)