





TOGGLE SHOWN IN POS. 2

Contact arrangement

		toggle	toggle	
code for x	function	towards keyway	opposite to keyway	
N	On-On	1-2, 4-5	2-3, 5-6	
R	Mom-On	1-2, 4-5		

code for x	function	toggle towards keyway	toggle in center	toggle opposite to keyway
Р	On-Off-On			
S	Mom-Off-Mom	1-2, 4-5	open	2-3, 5-6
Т	Mom-Off-On			

Specifications:

					P.C.B. LAYOUT		
Contact rating: Contact resistance: Insulation resistance: Dielectric strength: Operating temperature: Mechanical life: Electrical life: Operating force: Material: Compliance: RohS III (20	ontact resistance:20mOhm max. (1.5mA, 200µV AC; 1kHz)sulation resistance:1 000MOhm min. at 500V DCelectric strength:1 000V AC (between terminals)1 500V AC (between terminals and ground) for 1 minuteberating temperature:-20°C to +80°Cechanical life:100 000 cycles min.berating force:2.5 +/-1.2 N (250 +/-120 gf)aterial:Case: diallyl phthalate resin, blackFixed terminal: brass, silver platedCommon terminal: brass, silver platedPlunger: brass, chrome platedBushing: brass, nickel platedFrame: stainless steelPlate: brass, tin platedContact: silver, silver plated						
Tolerances: ±0.15mm		Date Name					
		09/21 dr	00/21 dr				
				STM 206	5 X - VM		
				20 10	05	Page	
		knitter-su	witch	30 46	93	1/1	
Modifications Date	Name					1/1	

P.C.B. LAYOUT

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Toggle Switches category:

Click to view products by Knitter-Switch manufacturer:

Other Similar products are found below :

8928K478 8A1-C-222 020017-13 60012L 6006L CS115W CS120W 6663 7101SPDV30BE 7103SDV30BE 7105D 7108P3YAV2BE 71YY50282 7300K36 7301K38 7306K36 7310K36 7506K4 7592K6 7660K12 7691K14 7700K1 8391K108 8396K108 8812K14 8824K14 8828K13 8835K3 8858K44 PS83-121G 1-1825192-0 A201SCWZB04 A207SYCB04 A208J61ZQ0004 A221T1TCQ A232M1YCQ A323S1CWZQ A423S1CWZG-M8 1201W 12149A-3V 12156AX408 12147AGKX679 12246X778 12TW49-3D 130312 13037L 13001X AE101MD1W4B04 AE208SD1W4B04 MS24659-22D