



Electrical Details

Electrical Configuration	C Filter	
Capacitance Measurement	@ 1000hr Point	
Current Rating	10A	
Insulation Resistance (IR)	10GΩ or 1000ΩF	
Temperature Rating	-55°C to +125°C	
Ferrite Inductance (Typical)	Not Applicable	

Mechanical Details

Head (A/F)	4mm (0.157")
Nut A/F	Not Applicable
Washer diameter	Not Applicable
Mounting Torque	Not Applicable
Mounting Hole Diameter	4-40 UNC Class 2B tapped hole
Max. Panel Thickness	Not Applicable
Weight (Typical)	0.5g (0.017oz)
Finish	Silver plate on copper undercoat

Product Code	Capacitance (±20%) UOS	Dielectric	Rated Voltage (Vdc)	DWV (Vdc)	Typical No-Load Insertion Loss (dB)								
					0.01MHz	0.1MHz	1MHz	10MHz	100MHz	1GHz			
*SFAAC5000100ZC	10pF -20% / +80%	COG/NP0	500#	750	-	-	-	-	-	4			
SFAAC5000150ZC	15pF -20% / +80%				-	-	-	-	-	7			
SFAAC5000220ZC	22pF -20% / +80%				-	-	-	-	-	10			
SFAAC5000330ZC	33pF -20% / +80%				-	-	-	-	-	12			
*SFAAC5000470ZC	47pF -20% / +80%				-	-	-	-	1	15			
*SFAAC5000680MC	68pF				-	-	-	-	2	18			
*SFAAC5000101MC	100pF				-	-	-	-	4	22			
SFAAC5000151MC	150pF				-	-	-	-	7	25			
*SFAAC5000221MC	220pF				-	-	-	-	10	29			
*SFAAC5000331MC	330pF				-	-	-	-	13	33			
*SFAAC5000471MX	470pF	†X7R	500#	750	-	-	-	1	16	35			
SFAAC5000681MX	680pF				-	-	-	2	19	36			
*SFAAC5000102MX	1.0nF	X7R	500#	750	-	-	-	4	23	41			
SFAAC5000152MX	1.5nF				-	-	-	7	26	45			
*SFAAC5000222MX	2.2nF				-	-	-	10	30	50			
SFAAC5000332MX	3.3nF				-	-	-	13	33	52			
*SFAAC5000472MX	4.7nF				-	-	1	16	36	55			
*SFAAC5000682MX	6.8nF				-	-	2	19	39	57			
*SFAAC5000103MX	10nF				-	-	4	22	41	60			
*SFAAC5000153MX	15nF				-	-	7	25	44	62			
*SFAAC5000223MX	22nF				-	-	10	29	46	65			
SFAAC5000333MX	33nF				-	-	13	33	48	68			
*SFAAC2000473MX	47nF				-	200	500	-	1	16	35	50	70
SFAAC2000683MX	68nF				-	200	500	-	2	19	39	54	>70
*SFAAC1000104MX	100nF				-	100	250	-	4	22	41	57	>70
*SFAAC0500154MX	150nF				-	50	125	-	7	25	45	60	>70

Also rated for operation at 115Vac 400Hz. Self heating will occur - evaluation in situ recommended. * Recommended values. † Also available in COG/NP0.

Ordering Information - SFAAC range

SF	A	A	C	500	0333	M	X	O
Type	Case style	Thread	Electrical configuration	Voltage (dc)	Capacitance in picofarads (pF)	Tolerance	Dielectric	Hardware
Syfer Filter	4.0mm Hex Head	4-40 UNC	C = C Filter	050 = 50V 100 = 100V 200 = 200V 500 = 500V	First digit is 0. Second and third digits are significant figures of capacitance code. The fourth digit is number of zeros following Example: 0101 = 100pF 0332 = 3300pF	M = ±20% Z = -20+80%	C = COG/NP0 X = X7R	0 = Without

Note: The addition of a 4-digit numerical suffix code can be used to denote changes to the standard part. Options include for example: change of finish / alternative voltage rating / non-standard intermediate capacitance values / test requirements. Please refer specific requests to the factory.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [EMI Feedthrough Filters](#) category:

Click to view products by [Knowles](#) manufacturer:

Other Similar products are found below :

[FN7511-32-M4](#) [FN7660-100-M8](#) [FN7660-200-M10](#) [2443-007-X5S0-102MLF](#) [2463-001-X5S0-471MLF](#) [SCI-9925-303](#) [1609992-3](#) [1609993-1](#) [FN7510-100-M8](#) [FN7511-200-M10](#) [FN7562-100-M8](#) [FN7562-200-M10](#) [FN7563-100-M8](#) [FN7611-10-M3](#) [2450-000-X5U0-102PLF](#) [2499-003-X5S0-152MLF](#) [4202-025](#) [4251-001LF](#) [4253-002LF](#) [4300-523LF](#) [4305-001LF](#) [4306-019LF](#) [4403-010LF](#) [4600-072LF](#) [4403-060](#) [4600-067](#) [100AFC6-G](#) [10AFC6-B](#) [1-1609990-7](#) [1-1609990-1](#) [FN7510-16-M4](#) [FN7514-32-M4](#) [2461-010-X7V0-102AA](#) [FN7611-32-M4](#) [FN7660-10-M3](#) [SXD1A3-251](#) [2499-003-X5S0-102M](#) [4206-502](#) [M15733/62-0002](#) [4305-006LF](#) [4306-011LF](#) [4300-314-2](#) [4251-002LF](#) [4305-005LF](#) [2461-002-X7V0-102MLF](#) [4403-005](#) [CK70AW152M](#) [4311-001LF](#) [4101-500](#) [32DFC6-N](#)