

SHW SERIES

(High Reliability,Super Small,Super Low ESR) (高可靠性,超小型,低阻抗)






SPECIFICATIONS 技术参数

Table-1 (表-1)

Items (项目)	Conditions (条件) Characteristics (特征)				
Category temperature range(温度范围)	=	– 55°C to +105 °C			
Tolerance on reted capacitance (额定容量公差)	120Hz	M:±20%			
Tangent of less angle (测试频率)	120Hz	Less than or equal to the value of Table-4 小于或等于表-4的值			
Leakage Current (漏电流)	After 2 minites	Less than or equal to the value of Table-4 小于或等于表-4的值			
ESR (阻抗值)		Less than c	or equal to the value of Ta	able-4 小于或等于表-4的值	
Characteristics of impedance ratio at high temp. and low temp. (高低温特性的阻抗比)	Based the value at 100KHz,-25°C/+25°C	− 55°C	Z/Z20°C	5.0max	
	105℃ Rated voltage applied 10000H(105℃ 额定电压下:10000H)	Δ C/C	Within ± 20% ± 20%内		
		Tan-δ	2 times or less than an initial standerd(初始值的2倍)		
Endurance (使用寿命)		ESR	2 times or less than an initial standerd(初始值的2倍)		
		Leakage Current(漏电流)	Below an initial standerd (after voltage processing) (小于初始值		

DIMENSIONS



Ta	h	۱۵-	7

Table-2				Unit:(mm)
Size code	D ± 0.5	L± 1.0	F ± 0.5	d ± 0.05
5L	5.0	11	2.0	0.5
6.3L	6.3	11	2.5	0.5
8L	8.0	8, 11.5, 15, 16,	3.5	0.5
10L	10.0	8, 12.5, 16, 20	5.0	0.60
13L	13.0	15	5.0	0.60
16L	16.0	15	7.5	0.80
18L	18.0	15	7.5	0.80

- Φ5mm/6.3mm/8mm: d=0.50mm Φ10mm/13mm: d=0.60mm Φ16mm/18mm: d=0.80mm

FREQUENCY CONFFICENT FOR RIPPLECURRENT 频率纹波电流系数

Table -3

Frequency(频率)	120Hz≦ f<1KHz	1KHz ≤ f < 10KHz	10KHz ≤ f < 100KHz	100KHz ≤ f < 200KHz
Confficient(系数)	0.65	0.90	0.95	1.00



SHW SERIES

SHW SERISE CHARACTERISTICS LIST (SHW 的系列特性)

	Rated	Rated	ESR(阻抗值)	Rated ripple current		2
Case Size	voltage (V)	Capacitance	100KHz to 300KHz/20℃	100KHz/105°C(mA.rms)	Tangent of loss angle	Leakage current(µA
(尺寸)	额定电压	(μF)容量	$(m \Omega max)$	纹波电流	(max)损失角	(max)*1 漏电流
5× 9		330	155	650	0.35	21
5× 9		390	137	720	0.32	25
5× 11		470	137	900	0.30	30
6.3× 9]	680	100	1100	0.30	43
6.3× 11]	820	100	1400	0.30	52
6.3× 11	1	1000	75	2000	0.28	63
8× 8	1	1000	40	2200	0.28	63
8× 8	1	1200	40	2350	0.28	76
8× 8		1500	35	2400	0.26	95
8× 11.5	6.3	1500	35	2500	0.26	95
10× 8		1500	30	2550	0.26	95
8× 15		2200	25	2600	0.26	139
10× 12.5	1	2200	25	2650	0.26	139
8× 16		2700	25	2690	0.26	170
10× 12.5	-	2700	25	2800	0.28	170
10× 12.5	-	3300	25	2900	0.28	208
10× 16	-	3900	20	3470	0.28	246
10× 16	-	4700	20	3690	0.30	296
8× 8		4700		960	0.35	
100 1.70	-	- NO. 1001	50	1031 (5130)	0.30	47
6.3× 11		680	50	980	0.30	68
8× 8		820	45	1150	0.28	82
8× 8		1000	45	1200	500000000	100
8×11.5		1000	40	1350	0.26	100
8×11.5	10	1200	40	1550	0.24	120
8× 16		1800	35	1980	0.22	180
10× 8		1800	35	2270	0.22	180
10×12.5		2200	35	2450	0.22	220
10×16		2700	35	2690	0.22	270
10× 16		3300	35	3550	0.20	330
5× 11		220	130	720	0.22	35
6.3× 11		330	120	800	0.22	53
6.3× 11		470	100	960	0.20	75
8×8		470	45	1025	0.20	75
8× 8		680 1000	45	1126	0.20	109 160
8× 11.5 10× 8		1000	40 40	1660 1700	0.20 0.20	160
8× 16	-	1200	40	2180	0.20	192
10x12.5	16	1200	38	2210	0.20	192
10x12.5		1500	38	2240	0.20	240
10× 16		1800	35	2670	0.20	288
10× 16		2200	30	2200	0.20	352
10x20		3300	30	3390	0.20	528
13x15		3300	25	3470	0.20	528
16× 15		4700	20	3820	0.20	752
18× 15		5600	20	4450	0.20	896

SHW SERIES

Case Size (尺寸)	Rated voltage (V) 额定电压	Rated Capacitance (µ F)容量	ESR(阻抗值) 100KHz to 300KHz/20℃ (mΩ max)	Rated ripple current 100KHz/105℃(mA.rms) 纹波电流	Tangent of loss angle (max) 损失角	Leakage current (µ A) (max)*1漏电流
62 11		10 0100000	` ,		0.00	
6.3× 11		220	137	800	0.20	55
6.3× 11		330	100	960	0.20	83
8 × 8		390	65	1000	0.18	98
8× 8		470	40	1070	0.18	118
8× 11.5]	560	40	1350	0.18	140
8× 16		820	35	1550	0.18	205
10× 8		680	35	1720	0.18	170
10× 12.5	25	680	35	1790	0.18	170
10× 12.5		1000	30	2200	0.18	250
10× 12.5		1200	30	2390	0.18	300
10× 16		1500	25	3300	0.18	375
10× 20		2200	25	3450	0.16	550
13× 15		2200	25	3550	0.16	550
16× 15		3300	25	3670	0.16	825
18× 15		4700	20	3850	0.16	1175
6.3× 11		180	100	920	0.18	63
8×8		330	75	962	0.18	116
8× 11.5		390	60	1126	0.18	137
10× 12.5		470	40	1660	0.18	165
10× 12.5		560	35	1720	0.16	196
10× 16	25	680	35	2050	0.16	238
10× 16	35	820	35	2180	0.16	287
10× 20		1000	35	2360	0.16	350
10× 20		1200	30	2540	0.16	770
13× 20		1500	30	3694	0.16	525
16× 15		1500	25	3730	0.16	525
18× 15		2200	25	3880	0.16	770
6.3× 11		100	110	550	0.16	50
8× 11.5		180	60	800	0.16	90
10× 12.5		220	45	1000	0.16	110
10× 12.5		330	40	1200	0.16	165
10× 16		470	35	1350	0.14	235
13× 15	50	470	30	1460	0.14	235
10× 20		560	28	1660	0.14	280
13× 15		560	26	1850	0.14	280
13× 20		820	24	2050	0.14	410
16× 15		820	24	2180	0.14	410
18× 15		1000	22	2550	0.12	500
8× 9		100	105	650	0.16	63
10× 12.5		220	40	1200	0.16	139
10×17		330	40	1400	0.16	208
10× 25		470	35	1550	0.14	296
13× 16		470	30	1650	0.14	296
10× 25	63	560	28	1760	0.14	353
16× 16		560	26	1900	0.14	353
13× 25		820	24	2200	0.14	517
18× 16		820	24	2350	0.14	517
16× 25		1000	22	2600	0.14	630
18× 32		2200	22	2600	0.12	1360
10×16		100	105	1100	0.16	100
10 × 10 10 × 20		220		1450	0.16	220
10 × 20 13 × 25			40	1700	0.16	330
13 × 25 16 × 25	100	330	40		0.16	<u> </u>
16 × 25	100	470	35	2200	DOM: 2	470
		560	28	2600	0.14	560
18 × 32		820	24	3000	0.14	820

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Aluminium Electrolytic Capacitors - Radial Leaded category:

Click to view products by KNSCHA manufacturer:

Other Similar products are found below:

NRELS102M35V16X16C.140LLF ESRG160ETC100MD07D 227RZS050M 335CKR250M 476CKH100MSA 477CKR100M 107CKR010M 107CKH063MSA RJH-25V222MI9# RJH-35V221MG5# B43827A1106M8 RJH-50V221MH6# EKYA500ELL470MF11D B41022A5686M6 ESRG250ELL101MH09D EKMA160EC3101MF07D RJB-10V471MG3# ESMG160ETD221MF11D EKZH160ETD152MJ20S RJH-35V122MJ6# EGXF630ELL621ML20S RBD-25V100KE3#N EKMA350ELL100ME07D ESMG160ETD101ME11D ELXY100ETD102MJ20S EGXF500ELL561ML15S EKMG350ETD471MJ16S 35YXA330MEFC10X12.5 RXW471M1ESA-0815 ELXZ630ELL221MJ25S ERR1HM1R0D11OT LPE681M30060FVA LPL471M22030FVA HFE221M25030FVA LKMD1401H221MF B41888G6108M000 EKMA160ETD470MF07D UHW1J102MHD6 EKMG500ETD221MJC5S LKMK2502W101MF LKMD1401H181MF LKMI2502G820MF LKMJ2001J122MF LKML2501C472MF LKMJ4002C681MF 450MXH330MEFCSN25X45 450MXK330MA2RFC22X50 63ZLH560MEFCG412.5X30 ELH2DM331O25KT ELH2DM471P30KT