

MDA Series
SMD Low Profile High Current Molded Inductor
Size 1040




FEATURES

- Shielded construction
- Capable of corresponding high frequency .
- Low loss realized with low DCR.
- High performance (Isat) realized by metal dust core.
- Ultra low buzz noise, due to composite construction.
- 100% Lead(Pb)-Free and RoHS compliant.
- High reliability -Reliability test complied to AEC-Q200
- Operating temperature: -55 to +155 °C (including self-temperature rise)
- Quantity: 500PCS


APPLICATION

- Headlamps, tail lamps and interior lighting
- HVAC
- Doors, window lift and seat control
- Audio subsystem
- Digital instrument cluster
- In-Vehicle Infotainment and navigation


Dimensions: [mm] 0.15μH-1.50μH




Land Pattern: [mm]



Dimensions: [mm] 1.8μH-47μH



Land Pattern: [mm]




Electrical Properties:













Part No	Inductance @ 100KHz/1V (μH)	Tolerance	Temperature Rise Current Typ. (A)	Saturation Current Typ. (A)	DC Resistance Typ. (mΩ)	DC Resistance Max. (mΩ)	E
MDA1040-R15N	0.15	±30%	44.0	82.0	0.50	0.60	3.0±0.3
MDA1040-R22M	0.22	±20%	36.0	70.0	0.72	0.83	3.0±0.3
MDA1040-R36M	0.36	±20%	33.0	51.0	1.05	1.18	3.0±0.3



Part No	Inductance @ 100KHz/1V (μH)	Tolerance	Temperature Rise Current Typ. (A)	Saturation Current Typ. (A)	DC Resistance Typ. (mΩ)	DC Resistance Max. (mΩ)	E
MDA1040-R47M	0.47	±20%	32.0	46.0	1.30	1.50	3.0±0.3
MDA1040-R56M	0.56	±20%	25.0	34.0	1.60	1.80	2.5±0.3
MDA1040-R68M	0.68	±20%	23.0	31.0	1.90	2.20	2.5±0.3
MDA1040-1R0M	1.00	±20%	20.0	29.0	2.90	3.25	2.5±0.3
MDA1040-1R5M	1.50	±20%	17.5	26.0	3.70	4.20	2.5±0.3
MDA1040-1R8M	1.80	±20%	16.5	23.0	5.10	5.70	3.0±0.3
MDA1040-2R2M	2.20	±20%	15.0	20.0	5.80	6.70	3.0±0.3
MDA1040-3R3M	3.30	±20%	11.0	17.5	10.5	11.8	3.0±0.3
MDA1040-4R7M	4.70	±20%	8.80	15.2	15.8	19.0	3.0±0.3
MDA1040-5R6M	5.60	±20%	8.00	14.1	19.0	22.8	3.0±0.3
MDA1040-6R8M	6.80	±20%	7.80	12.2	22.0	24.5	3.0±0.3
MDA1040-8R2M	8.20	±20%	7.60	9.50	25.0	28.0	3.0±0.3
MDA1040-100M	10.0	±20%	7.50	8.60	27.0	30.0	3.0±0.3
MDA1040-150M	15.0	±20%	6.25	7.00	41.0	45.0	3.0±0.3
MDA1040-220M	22.0	±20%	5.00	6.20	58.0	66.0	3.0±0.3
MDA1040-330M	33.0	±20%	4.40	5.50	84.0	91.0	3.0±0.3
MDA1040-470M	47.0	±20%	3.50	4.00	125	143	3.0±0.3

Saturation Current will cause L to drop approximately 30%
 Temperature Rise Current: The actual value of DC current when the temperature rise is $\Delta T=40^{\circ}\text{C}$

Typical Electrical Characteristics:







X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fixed Inductors](#) category:

Click to view products by [KOHER](#) manufacturer:

Other Similar products are found below :

[CR32NP-100KC](#) [70F224AI](#) [MHQ1005P10NJ](#) [MHQ1005P1N0S](#) [MHQ1005P2N4S](#) [MHQ1005P3N6S](#) [MHQ1005P5N1S](#) [MHQ1005P8N2J](#)
[PE-53601NL](#) [PE-53602NL](#) [PG0936.113NLT](#) [9220-20](#) [9310-16](#) [PM06-2N7](#) [PM06-39NJ](#) [A01TK](#) [1206CS-471XJ](#) [HC2-R47-R](#) [HC8-1R2-R](#)
[HCF1305-3R3-R](#) [1206CS-151XG](#) [RCH664NP-4R7M](#) [RCP1317NP-391L](#) [DH2280-4R7M](#) [DS1608C-106](#) [B10TJ](#) [B82498B3101J000](#) [ELJ-](#)
[RE27NJF2](#) [1812CS-153XJ](#) [1812CS-183XJ](#) [1812CS-223XJ](#) [1812LS-104XJ](#) [1812LS-105XJ](#) [1812LS-124XJ](#) [1812LS-154XJ](#) [1812LS-223XJ](#)
[1812LS-224XJ](#) [1812LS-563XJ](#) [1812LS-683XJ](#) [1812LS-824XJ](#) [NIN-FB101JTR110F](#) [NIN-FB471JTR62F](#) [NIN-FC1R5JTR220F](#) [NIN-](#)
[HCR15JTRF](#) [NIN-HCR33JTRF](#) [NIN-HDR22JTRF](#) [NIN-HDR82JTRF](#) [NIN-HK2N7STRF](#) [NIN-PA150KTR370F](#) [NIN-PB100KTR550F](#)