

MDE Series
Molding Power Inductors
Size 1250




FEATUERS

- High rated current
- Frequency up to 3 MHz
- 125 °C maximum total temperature operation
- Low core loss
- Ultra low buzz noise due to molding construction
- Halogen Free & ROHS compliant
- Quantity: 500pcs


APPLICATION

- Laptops and PCs
- Switch and servers
- Base stations
- DC/DC converters
- Battery powered devices
- SSD modules

Dimensions: [mm]



Land Pattern: [mm]



Electrical Properties:


Part No.	L@100KHz /1V (µH)	Tolerance	R _{DC} Max. (mΩ)	I _{sat} Typ. (A)	I _R Typ. (A)
MDE1250-R22M	0.22	±20%	0.7	75	50
MDE1250-R36M	0.36	±20%	0.85	50	42
MDE1250-R50M	0.50	±20%	1.15	48	38
MDE1250-R68M	0.68	±20%	1.55	46	33
MDE1250-R82M	0.82	±20%	1.67	39	30
MDE1250-1R0M	1.0	±20%	2.2	35	26
MDE1250-1R5M	1.5	±20%	3.2	33	23
MDE1250-2R2M	2.2	±20%	5.0	24	15
MDE1250-3R3M	3.3	±20%	7	22	14
MDE1250-4R7M	4.7	±20%	9	20	13
MDE1250-6R8M	6.8	±20%	18	16	12

Part No.	L@100KHz /1V (μH)	Tolerance	R _{DC} Max. (mΩ)	I _{sat} Typ. (A)	I _R Typ. (A)
MDE1250-100M	10	±20%	22	12	9
MDE1250-150M	15	±20%	30	10	8
MDE1250-220M	22	±20%	58	6.5	4.5
MDE1250-330M	33	±20%	84	6.0	3.5
MDE1250-470M	47	±20%	130	5.0	3.0


Operating temperature range - 55 °C to + 125 °C
 I_R will cause the coil temperature approximate ΔT40 °C
 I_{sat} will cause to drop approximately 30 %

Typical Electrical Characteristics:

Inductance vs DC Current Characteristics:



Temperature Rise vs DC Current Characteristics:



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fixed Inductors](#) category:

Click to view products by [KOHER](#) manufacturer:

Other Similar products are found below :

[CR32NP-100KC](#) [CR54NP-470LC](#) [70F224AI](#) [MGDQ4-00004-P](#) [MHQ1005P10NJ](#) [MHQ1005P1N0S](#) [MHQ1005P2N4S](#) [MHQ1005P3N6S](#)
[MHQ1005P5N1S](#) [MHQ1005P8N2J](#) [PE-53601NL](#) [PE-53602NL](#) [PG0936.113NLT](#) [9220-20](#) [9310-16](#) [PM06-2N7](#) [PM06-39NJ](#) [A01TK](#)
[1206CS-471XJ](#) [HC2-R47-R](#) [HC8-1R2-R](#) [HCF1305-3R3-R](#) [1206CS-151XG](#) [RCH664NP-140L](#) [RCH664NP-4R7M](#) [RCP1317NP-391L](#)
[RCR110DNP-331L](#) [DH2280-4R7M](#) [DS1608C-106](#) [B10TJ](#) [B82498B3101J000](#) [ELJ-RE27NJF2](#) [1812CS-153XJ](#) [1812CS-183XJ](#) [1812CS-](#)
[223XJ](#) [1812LS-104XJ](#) [1812LS-105XJ](#) [1812LS-124XJ](#) [1812LS-154XJ](#) [1812LS-223XJ](#) [1812LS-224XJ](#) [1812LS-563XJ](#) [1812LS-683XJ](#)
[1812LS-824XJ](#) [NIN-FB101JTR110F](#) [NIN-FB471JTR62F](#) [NIN-FC1R5JTR220F](#) [NIN-HCR15JTRF](#) [NIN-HCR33JTRF](#) [NIN-HDR22JTRF](#)