

NRSC Series

SMD Shielded Tiny Power Inductor Size 5040




Features:

- Magnetic-resin shielded construction reduces buzz noise to ultra-low levels
- Metallization on ferrite core results in excellent shock resistance and damage-free durability
- Closed magnetic circuit design reduces leakage flux and Electro Magnetic Interference (EMI)
- 30% higher current rating than conventional inductors of equal size
- Takes up less PCB real estate and save more power
- Quantity: 2000 pcs


Application:

- LED Lighting
- Next-generation mobile devices with multifunction such as mobile TV and digital movie cameras
- Flat-screen TVs, blue-ray disc recorders, set top box
- Notebooks, desktop computers, servers, graphic cards
- Portable gaming devices, personal navigation systems, personal multimedia devices
- Automotive systems
- Telecomm base stations

Dimensions: [mm]



Land Pattern: [mm]



Electrical Properties:

Part No	Inductance (μ H)	Tolerance	Saturation current (A)	Temperature Rise Current (A)	DCR $\pm 20\%$ (Ω)	S.R.F Min. (MHz)
NRSC5040-1R0N	1.0	$\pm 30\%$	7.35	4.90	0.012	117
NRSC5040-1R5N	1.5	$\pm 30\%$	6.30	4.30	0.015	86
NRSC5040-2R2N	2.2	$\pm 30\%$	4.90	3.80	0.019	50
NRSC5040-2R7N	2.7	$\pm 30\%$	4.30	3.60	0.022	37
NRSC5040-3R3N	3.3	$\pm 30\%$	3.95	3.40	0.024	32
NRSC5040-3R9N	3.9	$\pm 30\%$	3.55	3.20	0.027	29
NRSC5040-4R7N	4.7	$\pm 30\%$	3.50	3.00	0.030	28
NRSC5040-6R8M	6.8	$\pm 20\%$	2.90	2.50	0.043	21
NRSC5040-100M	10	$\pm 20\%$	2.35	2.10	0.064	18
NRSC5040-150M	15	$\pm 20\%$	2.00	2.00	0.086	13
NRSC5040-220M	22	$\pm 20\%$	1.60	1.50	0.129	11
NRSC5040-330M	33	$\pm 20\%$	1.30	1.20	0.188	9.1
NRSC5040-470M	47	$\pm 20\%$	1.10	1.00	0.272	6.7

Part No	Inductance (μ H)	Tolerance	Saturation current (A)	Temperature Rise Current (A)	DCR $\pm 20\%$ (Ω)	S.R.F Min. (MHz)
NRSC5040-680M	68	$\pm 20\%$	0.90	0.80	0.400	5.7
NRSC5040-101M	100	$\pm 20\%$	0.75	0.70	0.560	4.7

Inductance tested at 100kHz, 1Vrms.


Operating temperature : -40°C ~ +125°C

Temperature rise current: the actual value of DC current when the temperature rise is $\Delta T_{40}^{\circ}\text{C}$


Saturation Current that will cause initial inductance to drop approximately 30%

Typical Electrical Characteristics:

Inductance VS. DC.Current Characteristics:



Temperture Rise VS. DC.Current Characteristics:



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fixed Inductors](#) category:

Click to view products by [KOHER](#) manufacturer:

Other Similar products are found below :

[CR32NP-151KC](#) [CR32NP-180KC](#) [CR32NP-181KC](#) [CR32NP-1R5MC](#) [CR32NP-390KC](#) [CR32NP-3R9MC](#) [CR32NP-680KC](#) [CR32NP-820KC](#) [CR32NP-8R2MC](#) [CR43NP-390KC](#) [CR43NP-560KC](#) [CR43NP-680KC](#) [CR54NP-181KC](#) [CR54NP-470LC](#) [CR54NP-820KC](#) [CR54NP-8R5MC](#) [70F224AI](#) [MGDQ4-00004-P](#) [MHL1ECTTP18NJ](#) [MHQ1005P10NJ](#) [MHQ1005P1N0S](#) [MHQ1005P2N4S](#) [MHQ1005P3N6S](#) [MHQ1005P5N1S](#) [MHQ1005P8N2J](#) [PE-51506NL](#) [PE-53601NL](#) [PE-53602NL](#) [PE-53630NL](#) [PE-53824SNLT](#) [PE-92100NL](#) [PG0434.801NLT](#) [PG0936.113NLT](#) [9220-20](#) [9310-16](#) [PM06-2N7](#) [PM06-39NJ](#) [A01TK](#) [1206CS-471XJ](#) [HC2LP-R47-R](#) [HC2-R47-R](#) [HC3-2R2-R](#) [HCF1305-3R3-R](#) [1206CS-151XG](#) [RCH664NP-140L](#) [RCH664NP-4R7M](#) [RCH8011NP-221L](#) [RCP1317NP-332L](#) [RCP1317NP-391L](#) [RCR1010NP-470M](#)