


NYLON-INSULATED DOUBLE CRIMP FEMALE DISCONNECTORS



MAXIMUM ELECTRIC CURRENT:

A.W.G.	22	20	18	16	14	12	10
AMP.	3	4	7	10	15	20	24

MAXIMUM ELECTRICAL RATING: 105°C 600 VOLTS MAX.

INSULATION MATERIAL: NYLON TERMINAL MATERIAL: BRASS

INSULATION COLOR:

22-16 A.W.G.: RED 16-14 A.W.G.: BLUE 12-10 A.W.G.: YELLOW

DOUBLE CRIMP: WITH COPPER SLEEVE ON BARREL

TERMINAL BARREL I.D.:

22-16 A.W.G.: C=1.7mm 16-14 A.W.G.: C=2.3mm 12-10 A.W.G.: C=3.4mm

WIRE RANGE A.W.G. mm ²	ITEM NO.	NEMA TAB	DIMENSION ^{inch} / _{mm}						CRIMPING TOOL	Q'TY BOX					
			W	F	L	B	D	T							
22-16 A.W.G. 0.5-1.5 mm ²	FDNYD1-110(5)	.020×.110 (0.5×2.8)	.126 3.2	.256 6.5	.772 19.6	.433 11.0	.157 4.0	.012 0.3	IZUMI MODEL 34 WITH DIE INDEX COLOR:RED OR K.S. MODEL KST2000A WITH DIE INDEX COLOR:RED	1000					
	FDNYD1-110(8)	.032×.110 (0.8×2.8)										1000			
	FDNYD1-187(5)	.020×.187 (0.5×4.75)	.197 5.0	.252 6.4	.787 20.0							1000			
	FDNYD1-187(8)	.032×.187 (0.8×4.75)										1000			
	FDNYD1-205(5)	.020×.205 (0.5×5.2)	.224 5.7	.228 5.8	.768 19.5							1000			
	FDNYD1-205(8)	.032×.205 (0.8×5.2)										1000			
	FDNYD1-250	.032×.250 (0.8×6.35)	.260 6.6	.295 7.5	.846 21.5							1000			
FDNYD1-312	.032×.315 (0.8×8.0)	.323 8.2	.394 10.0	.992 25.2			.016 0.4	1000							
16-14 A.W.G. 1.5-2.5 mm ²	FDNYD2-110(5)	.020×.110 (0.5×2.8)	.126 3.2	.256 6.5	.772 19.6	.433 11.0	.197 5.0	.012 0.3	IZUMI MODEL 34 WITH DIE INDEX COLOR:BLUE OR K.S. MODEL KST2000A WITH DIE INDEX COLOR:BLUE	1000					
	FDNYD2-110(8)	.032×.110 (0.8×2.8)										1000			
	FDNYD2-187(5)	.020×.187 (0.5×4.75)	.197 5.0	.252 6.4	.787 20.0							1000			
	FDNYD2-187(8)	.032×.187 (0.8×4.75)										1000			
	FDNYD2-205(5)	.020×.205 (0.5×5.2)	.224 5.7	.228 5.8	.768 19.5							1000			
	FDNYD2-205(8)	.032×.205 (0.8×5.2)										1000			
	FDNYD2-250	.032×.250 (0.8×6.35)	.260 6.6	.295 7.5	.846 21.5							1000			
	FDNYD2-312	.032×.315 (0.8×8.0)	.323 8.2	.394 10.0	.992 25.2							.016 0.4	1000		
FDNYD2-375	.047×.370 (1.2×9.4)	.394 10.0	.472 12.0	1.043 26.5			.020 0.5	1000							
12-10 A.W.G. 4-6 mm ²	FDNYD5-110(5)	.020×.110 (0.5×2.8)	.126 3.2	.256 6.5	.866 22.0	.512 13.0	.256 6.5	.014 0.35	IZUMI MODEL 5 WITH DIE INDEX COLOR:YELLOW OR K.S. MODEL KST2000A WITH DIE INDEX COLOR:YELLOW	500					
	FDNYD5-110(8)	.032×.110 (0.8×2.8)											500		
	FDNYD5-187(5)	.020×.187 (0.5×4.75)	.197 5.0										500		
	FDNYD5-187(8)	.032×.187 (0.8×4.75)											500		
	FDNYD5-250	.032×.250 (0.8×6.35)	.260 6.6							.295 7.5	.925 23.5			.016 0.4	500
	FDNYD5-375	.047×.370 (1.2×9.4)	.394 10.0							.472 12.0	1.122 28.5			.020 0.5	500

UL cUL ALL LISTED
⊙: NOT UL AND C-UL LISTED

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Terminals](#) category:

Click to view products by [K.S Terminals](#) manufacturer:

Other Similar products are found below :

[00-054007-01074-6](#) [00-054007-70206-1](#) [00-054007-70210-8](#) [00-054007-70217-7](#) [00-054007-70228-3](#) [00-054007-70256-6](#) [00-054007-70316-7](#) [00-054007-49560-4](#) [00-054007-70209-2](#) [00-054007-70231-3](#) [00-054007-70241-2](#) [00-054007-70242-9](#) [00-054007-70246-7](#) [00-054007-70263-4](#) [00-054007-70288-7](#) [00-054007-70290-0](#) [00-054007-70300-6](#) [00-054007-70304-4](#) [01-2900-1-04412](#) [0190160084](#) [0190350008](#) [600TS-10](#) [605601-1](#) [60617-1-C](#) [61314-6-C](#) [626-0194](#) [63-S](#) [M55155/079C01](#) [M55155/099B03](#) [M55155/109H01](#) [M55155/12XH05](#) [M55155/29XJ08](#) [M55155/30-6S](#) [M55155/30-9S](#) [M55155/30XI09](#) [M6-14RSX](#) [M86700006](#) [D18-110B-C](#) [D18-110B-M](#) [701-1936](#) [701-1955](#) [701-2003](#) [701-2007](#) [701-2013](#) [701-2018](#) [701-2069](#) [701-2077-60](#) [701-2315](#) [701-2430](#) [701-2480](#)