

| 2D Drawing            | IGES                | STEP                 | 3D PDF           |
|-----------------------|---------------------|----------------------|------------------|
| Solder Profile        | CofC RoHS Compliant | CofC REACH Compliant | UL Plastic File  |
| Certificate of Origin | Check Stock         | Request a Sample     | Send Us An Email |
|                       |                     |                      |                  |


#### Generated Part Number


# D-SUBMINIATURE CONNECTORS:

K22X Series Right Angle PCB Mount 0.318" Footprint

### **K22X Series Dimensions**

Dimensions in mm





| Shell<br>Size<br>In<br>mm | A<br>±.010<br>±0.25 | A1<br>±.010<br>±0.25 | B<br>±.005<br>±0.13 | C<br>±.015<br>±0.38 |
|---------------------------|---------------------|----------------------|---------------------|---------------------|
| 9                         | .643                | .666                 | .984                | 1.213               |
| (E)                       | 16.33               | 16.92                | 24.99               | 30.81               |
| 15                        | .971                | .994                 | 1.312               | 1.541               |
| (A)                       | 24.66               | 25.25                | 33.32               | 39.14               |
| 25                        | 1.511               | 1.534                | 1.852               | 2.088               |
| (B)                       | 38.38               | 38.96                | 47.04               | 53.04               |
| 37                        | 2.159               | 2.182                | 2.500               | 2.729               |
| (C)                       | 54.84               | 55.42                | 63.50               | 69.32               |

A = Exterior of Female Shell (S)

A1 = Interior of Male Shell (P)



#### Series

< KYCON

K22X - D-Subminiature Connector, Right Angle

#### Shell Size-Contact Option

- E 9 Contacts
- A 15 Contacts
- B 25 Contacts
- C 37 Contacts

#### Contact Type

- P Pin Contact (Plug)
- S Socket Contact (Receptacle)

#### **Mounting Option**

N - With Boardlocks and #4-40 UNC Threaded Inserts NJ - With Boardlocks and # 4-40 Jackscrews Installed

#### **Plating Option**

Blank - Gold Flash 30 - 30µ" Gold

Contact Kycon for Other Options

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Standard Connectors category:

Click to view products by Kycon manufacturer:

Other Similar products are found below :

 56F706-005-LI
 56F711-015
 012-9507-004
 LV242999-142T12
 015-0341-000
 015-0372-005
 015-0372-008
 015-8755-001
 020419-0104

 012-0467-000
 012-9507-034
 012-9507-114
 020745-0008
 609-25P
 CT2-14S-2PCA34
 CT2-18-11PCAU
 CT6-10SL-3SC
 CT6-10SL-4SC

 CT6-14S-2SC
 CT6E14SA7SC
 CT6N10SL-4SSA34
 M83513/01-FC
 M83723/76W24619
 L/C
 M85049/48-3-2F
 6STD09PCM99B70X

 6STD09SCM99B30X
 6STD09SCT99S40X
 6STD15PCT99S40X
 6STD15SCT99S40X
 6STF09PCM05B70X
 7-135760-9
 MC11E-10-6SN

 747552-3
 MD1-21PS
 MDM-15SCBRM7-F222
 MDM96517-699
 MDM96521-744
 MDVB1-21SL1
 MIK0-1-7SH003
 MIKQ6-7SH076

 MIKQ7-7PH077
 MIKQ7-7PH11
 MIKQ7-7PH32
 MJSV-28SL61
 MKJ4A1F14-55S
 8-135760-3
 8STD09PCM99B30X
 PG-KV/PV-16 

 GROM-SEALING
 GDA15P
 GDAY15PB
 MISV-28SL61
 MKJ4A1F14-55S
 8-135760-3
 8STD09PCM99B30X
 PG-KV/PV-16