


Recommended PCB Layout
(Top View)



Part Number	Center Post Diameter
KLDX-0201-AHT-1	Ø1.0±0.05
KLDX-0201-BHT-1	Ø1.3±0.05

Material and Finish

Housing: High Temperature Thermoplastic, UL 94V-0 Rated, Black Color
 Contact Materials:
 Center Pin: Copper Alloy, Nickel Plated
 Contact #1: Brass, Matte Tin Plated
 Contact #2: Brass, Matte Tin Plated
 Contact #3: Phosphor Bronze, Matte Tin Plated

Electrical Characteristics

Rated Current: 2.5A
 Rated Voltage: 24V DC
 Insulation Resistance: 100 Megohms Min. at 500V DC
 Contact Resistance:
 Initial:
 Center Contact: 30 milliohms Max.
 Barrel Contact: 50 milliohms Max.
 After Durability Test:
 Center Contact: 60 milliohms Max.
 Barrel Contact: 100 milliohms Max.

Mechanical Characteristics

Insertion Force: 0.3kg - 3kg
 Withdrawal Force: 0.3kg - 3kg
 Durability: 5000 Mating Cycles Min.
 Operating Temperature: -25°C to +85°C



Tolerances
X.X ± 0.3
X.XX ± 0.15
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A0	08/25/15	New Drawing	W. Cook	H. MA		
A1	09/17/15	Pin Outs, Spec Details	C. Kelleher	C. Furumasu	W. Cook	08/20/15
A2	12/18/15	Release Drawing	C. Kelleher	N/A		

KLDX-0201-xHT-1

Mini DC Power Jack, Matte Tin Leads

High Temp, RoHS Compliant



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [DC Power Connectors](#) category:

Click to view products by [Kycon](#) manufacturer:

Other Similar products are found below :

[RAPC3FG](#) [B04P-VL-VN-1.8](#) [1600206-1](#) [163-0302](#) [163-0310-EX](#) [163-4024](#) [163-4117-EX](#) [163-5005-E](#) [163-7421](#) [171-0721-EX](#) [171-3118-EX](#) [173-23507-ST-EX](#) [KLDVX-SMT-02-ATR](#) [KLDX-SMT-0202-BP](#) [KLDX-SMT-0202-BPTR](#) [163-0179-EX](#) [163-0307-E](#) [163-4119-E](#) [171-0722-E](#) [171-3218-EX](#) [171-7391](#) [173-3413-ST-EX](#) [RAPCBRK](#) [K596](#) [KLD-0201-BC](#) [KPPX-D](#) [TPCF-140-01-L-Q-4-RA](#) [RAPC3MHG](#) [RASM752TRX](#) [163-4800-E](#) [4C6831AX](#) [TS3PNJ](#) [DC-025LM-5A-2.5](#) [CL14218R](#) [AS250F RED](#) [DC-105-4A-1.6](#) [09441](#) [AS120-F](#) [09442](#) [AS120-M](#) [CP30240](#) [TAMIYA-M](#) [TAMIYA-MT1](#) [TAMIYA-MT2](#) [4840.1200](#) [4840.2202](#) [C5080HI-04P-18 + C5080HI-C](#) [JC-135](#) [JC-138](#) [JPO-25 \(FC6814\)](#) [JYO-26 \(FC6811\)](#) [KLBR 4](#)