



DC POWER CONNECTORS: KLDX-SMT3 Series

Surface Mount DC Power Jack

Product Features

2.0mm and 2.5mm

Built-In DC On/Off Switch

Laptop and Palm Computers, Portable Modems, Radar

Detectors, and Other Portable Device Applications

Surface Mount

UL File No. E140125

Performance Specifications

Materials and Finish

Housing: High Temperature Thermoplastic,

UL 94V-0 Rated, Black Color

Center Pin: Copper Alloy, Nickel Plated

Contact #1: Brass, Silver Plated

Contact #2: Phosphor Bronze, Silver Plated

Contact #3: Brass, Silver Plated

Electrical Characteristics

Rated Current: 3.5A Rated Voltage: 24V DC

Insulation Resistance: 50 Megohms Min. at 500V DC

Contact Resistance: 30 milliohms Max.

Mechanical Characteristics

Insertion Force: 0.3kg - 2.0kg Withdrawl Force: 0.3kg - 2.0kg Durability: 5000 Mating Cycles Min. Operating Temperature: -25°C to +85°C

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

Generated Part Number



Series

KLDX-SMT3-0202 - Surface Mount DC Power Jack

Diameter

A - 2.0mm Center Pin Diameter B - 2.5mm Center Pin Diameter


Packaging Option

TR - Tape and Reel

Contact Kycon for Other Options

KLDX-SMT3 Series

Dimensions in mm







X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DC Power Connectors category:

Click to view products by Kycon manufacturer:

Other Similar products are found below:

RAPC3FG B04P-VL-VN-1.8 1600206-1 163-0302 163-0310-EX 163-4024 163-4117-EX 163-5005-E 163-7421 171-0721-EX 171-3118-EX 173-23507-ST-EX KLDVX-SMT-02-ATR KLDX-SMT-0202-BP KLDX-SMT-0202-BPTR 163-0179-EX 163-0307-E 163-4119-E 171-0722-E 171-3218-EX 171-7391 173-3413-ST-EX RAPCBRK K596 KLD-0201-BC KLDVX-SMT-02-BTR KPPX-D TPCF-140-01-L-Q-4-RA RAPC3MHG RASM752TRX 163-4800-E 4C6831AX TS3PNJ DC-025LM-5A-2.5 CL14218R AS250F RED DC-105-4A-1.6 09441 AS120-F 09442 AS120-M CP30240 TAMIYA-M TAMIYA-MT1 TAMIYA-MT2 4840.1200 4840.2202 C5080HI-04P-18 + C5080HI-C JC-135 JC-138 JPO-25 (FC6814) JYO-26 (FC6811)