





## Material And Finish

Body: PBT Thermoplastic

Color: Pantone 2715C, Purple (meets PC99 spec)

Contacts: Copper Alloy, Gold Flash on Contact Area

Matte Tin Plated on Termination End

Shield: SPCC, Tin Plated

## Electrical Characteristics

Contact Resistance:

Before Test:

Plug to Terminals: 30 milliohm max.

After Test:

Plug to Terminals: 60 milliohm max.

Insulation Resistance: 500 Megohms min.

Dielectric Withstanding Voltage: 500V AC RMS for 1 minute

Current Rating: 2 Amp at 12V DC

## Mechanical Characteristics

Durability Test: 1000 Cycles

Insertion Force: 3.0kg max.

Extraction Force: 0.3kg - 3.0kg

Locked Retention Strength: 5lbs. Min. (When used with Kycon KMDLA Snap & Lock Plugs)

Operating Temperature: -25°C to +80°C

Designed to work with Kycon KMDLAX Series Snap & Lock plugs.







Tolerances

X.X ± 0.3

X.XX ± 0.15

Unless Stated
Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A2	03/04/05	Release Drawing	H. MA	N/A	R. Aguirre	09/01/04
A3	12/01/05	ECO #05-065	R. Aguirre	H. MA	I IV. Aguille	09/01/04
A4	07/30/13	ECO #13-039	D. Gih	P. DalCanto	+ 1	UNITS
A5	06/16/14	ECO #14-021	D. Gih	H. MA	(⊕) €	UNITS
B6	12/18/14	ECO #14-052	W. Cook	H. MA		mm
B7	03/28/18	ECO #18-013	J. Elbanna	H. MA		111111

KMDGX-6S-BS2715C

6 pos. Mini-DIN,Lead-Free, PC99

Center Board Lock, Gold Flash on Contacts



## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular DIN Connectors category:

Click to view products by Kycon manufacturer:

Other Similar products are found below:

60KD4M CTVP00RW-19-32S(506) M83723/76W22326 M83723/78R22327 D38999/26FE99SN L/C 75-069228-21J 7547401103P 75-474014-07L 88-559975-75P 8R3006A18M0033 PT02E1283P GTC00G-24-7S PT05A-14-5SX PT05A1832SW PT05E2255PW PT05SE1832SWLC PT05SE1832SYLC GTC030-20-27PW-LC GTC030A-20-33S PT06SE1811SXLC 1211290078 1211810025 1210120122 ACC06AF-20-23P(003) 1210503216 1211290084 1211500027 ACS06AF-16-10P(003) D38999/40FB35AN D38999/40WB35BN D38999/40WD35PN D38999/40WJ29SN-L/C D38999/40WJ4BN D38999/42FB35BN D38999/42WB35AB D38999/42WB35AB D38999/42WJ19AN D38999/42WJ29SN-L/C D38999/44WB35AN D38999/44WH21AN D38999/44WH35AN D38999/44WJ29BA D38999/44WJ35PN D38999/44WJ61BA D38999/46FB35AC D38999/46FB35BN D38999/46FB35SA-L/C D38999/46FB99BA D38999/46FB99BN