



Recommended PCB Layout
(Top View)

Material and Finish

Insulator: UL94V-0 rated thermoplastic, glass fiber filled, black color
 Shield: cold roll steel (front), brass (rear)
 Plating - 120u" nickel over 50u" min. copper
 Contacts: phosphor bronze
 Plating - 30u" gold on contact area, 120u" min. tin on solder tails, all over 50u" min. nickel underplating

Mechanical Specifications

Mating Force:
2 kg max.
 Withdrawal Force:
0.5~4.0 kg

Electrical Specifications

Dielectric Withstanding Voltage:
100VAC at sea level
 Contact Resistance:
30 milliohms max.
 Insulation Resistance:
100 Megohms min.

Part Number	Packaging Options
KMFSX-SMT-310B30	Tubes (standard)
KMFSX-SMT-310B30TR	Tape and Reel (TR option)



Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	10/11/05	New Drawing	R. Aguirre	H. MA	R. Aguirre	8/03/05

KMFSX-SMT-310B30

Mini IEEE 1394 Receptacle, 4 Position, RoHS Compliant
 Low-Profile Mount, SMT-type with 30u" Gold Plating



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [IEEE 1394 Connectors](#) category:

Click to view products by [Kycon](#) manufacturer:

Other Similar products are found below :

[EHFF2](#) [PX0485/BK](#) [EHFF2B](#) [EHFWX2BX](#) [3E106-2230KV](#) [53460-0619](#) [3E106-0220KV](#) [1734290-2](#) [53460-0629](#) [53462-0629](#) [NA1394-6-W](#) [5788516-1](#) [3E306-3200-008](#) [FWF21NSCC](#) [FWFODE](#) [FWFTV22G](#) [FWFTVC2G](#) [FWFTVC2N](#) [JE14](#) [JE18](#) [PX0480/BK](#) [928](#) [929](#) [930](#)
[NA1394-6-W-B](#) [EHFW800X2](#) [5787956-1](#) [PX0419](#) [PX0847](#) [693-006-699-003](#) [45740-0001](#) [53460-0639](#) [53462-0001](#) [53984-0681](#)
[EHFW800X2B](#) [EHFW800X2PKG](#) [1734290-1](#)