KYCON





Generated Part Number



HDMI_(TM):KMMDMIX Series Type D (Micro) HDMI_(TM)

Product Features

Smaller than the Mini HDMI(TM) Offering Significant Space Savings Equivalent Mechanical Strength and Electrical Characteristics as the Standard HDMI(TM) 19 Position Receptacle, Surface Mount


Performance Specifications

Materials and Finish Insulator UL94V-0 High Temperature Thermoplastic, Color Black Contacts Copper Alloy Plating Gold Flash over Nickel Underplate on Entire Contact Shell Stainless Steel, Matte Tin Plated

Electrical Characteristics

Rated Current 0.5A Rated Voltage 40V AC

Dielectric Withstanding Voltage Unmated 250V RMS Mated 150V RMS Insulation Resistance 100 Megohms Min. (Unmated) 10 Megohms Min. (Mated) Operating Temperature -20°C to + 85°C



Series KMMDMIX - Type D Micro HDMI(TM)

Shield Option NS3 - Surface Mount, Through Hole Shield Tabs


Spring Option WS - With Top Spring

Packaging Option BTRT - Tape and Reel With Mylar Tape


Contact Kycon for Other Options

KMMDMIX-NS3-WS-BTRT


Dimensions in mm







Dust Cap Comes Installed



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for HDMI, Displayport & DVI Connectors category:

Click to view products by Kycon manufacturer:

Other Similar products are found below :

<u>1775247-3</u> 2-1932649-5 30-1231 30-528 2069485-1 30-504 30-519 30-542 47648-2000 2002-400 769-103/021-000 1932649-1 233-368NFG6-17NH PJ-210A PJ-35825 3VD51203-3D6A-7H DV11201-H5R6-4F RPI-16337 CC-MDPM-VGAM-6 RPI-16338 CCB-HDMIL-1.5M CCB-HDMIL-1M CCB-HDMIL-2M CCB-HDMIL-3M CCB-HDMIL-5M CCB-HDMIL-7.5M CCBP-HDMI-10M CCBP-HDMI-1M CCBP-HDMI-2M CCBP-HDMI-3M CCBP-HDMI-7.5M CCBP-HDMI8K-1M CCBP-HDMI8K-2M CCBP-HDMI8K-3M AK-AV-02 AK-AV-03 AK-AV-05 AK-AV-11 AK-AV-13 AK-AV-15 CCP-MDP2-6 CCP-MDPMDP2-6 AK-HD-05A AK-HD-100A AK-HD-100P AK-HD-15A AK-HD-15P AK-HD-30A AK-HD-30P 49959