
KYCON



c PL'us

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

Generated Part Number



Series

KMMX - Micro Universal Serial Bus

Туре В - В Туре

Mounting Option

SMT35S - Surface Mount With Long Through Hole Shield Tabs

Insulator Color Option

B - Black

Plating Option Blank - Gold Flash 30 - 30µ" Gold

Packaging


TR - Tape and Reel


Contact Kycon for more options

KMMX

Dimensions in mm

Phone: +1.408.494.0330 | Fax: +1.408.494.0325 | WWW.KYCON.COM | 0319





Mechanical Characteristics Durability

10,000 Mating Cycles Min. Operating Temperature -30°C to +80°C

Micro Universal Serial Bus

UNIVERSAL SERIAL BUS: KMMX Series

Type B Long Through Hole Shield Tabs

Product Features

More Compact Footprint than Mini-USB Stainless Steel Shell, Which Yields 10,000 Insertion Cycles Long Through Hole Shield Tabs for Better Board Stability Used in Portable Devices Such as Mobile Phones, PDAs, and Digital Cameras US Certified File No. LR78160 UL File No. E134345

Performance Specifications

Materials and Finish Insulator High Temperature Thermoplastic, UL 94V-0 Rated, Black Color

Shell Steel, Tin Plated Contact Material Brass Contact Plating Options Flash Option: Gold Flash on Contact Area,Gold Flash on Solder Tails, All over Nickel Underplate 30 Option: 30μ" Gold Plated on Contact Area, Gold Flash on Solder Tails, All over Nickel Underplate

Electrical Characteristics

Rated Current: 1A Rated Voltage: 30V AC/DC Contact Resistance: 30 milliohms Max. Dielectric Withstanding Voltage: 100V AC for 1 Minute

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for USB Connectors category:

Click to view products by Kycon manufacturer:

Other Similar products are found below :

65-647-8-BK-BU 950 952 E8144-B01021-L A-USB A-LP-SMT-C MUSBA511N5 MUSBD11135 217450-1 CA 6 W LD KMBVX-TH-5S-B30 896-30-004-00-00000 KUSBVX-BS1N-W30 KUSBX-AP-KIT-SCBLK KUSBX-AS2N-W KUSBX-SMT2AP1S-W KUSBX-SMT2AP1S-W30 935 957 30-498-6 17-210051 1734082-1 30-1574 30-470 30-489 30-541 30-572-3 MAB 8 SN V A-USB A-2P-C MIKROE-1451 USBFTV2PEM2G USBFTVC6ZN KUSBX-AS2N-W30 KUSBX-SLAS1N-W KUSBX-SMT-AS1N-W30 4689-1 1-1734084-2 E8110-001-01 MUSBA81130 33UBARS1-04SW11 33UBAR-04SW11 USBF21ZNSCC USBBFTV6ZC MUSBB151341 10135326-001LF M9177/3-1 USB-A-S-F-B-VT 925 4198 690-024-633-031 KUSBEX-BSFS1N-W