## KYCON





# AUDIO JACKS: STX-25442 Series Mid-Mount 2.5mm Audio Jack

#### **Product Features**

Offered in a 4-Pole Version Used in Devices Such as Audio Equipment, Cell Phones, or Digital Still Camera Complies with EIA Standards CSA/NRTL Certified File No. LR78160

## Performance Specifications

# Materials and Finish

#### Housing

High Temperature Thermoplastic, Black Color, UL 94V-0 Rated

#### Terminals

Copper Alloy, Gold Plated

#### **Electrical Characteristics**

**Contact Resistance** 

50 milliohms Max.

**Insulation Resistance** 

100 Megohms at 250V DC

**Dielectric Withstanding Voltage** 

250V AC RMS for 1 Minute

### **Mechanical Characteristics**

Insertion Force

0.4kg - 3.0kg

Withdrawal Force

0.4kg - 3.0kg

Durability


5000 Mating Cycles Min.

**Operating Temperature** 

-25°C to + 85°C

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

#### **Generated Part Number**



# **Series**

STX-25442 - Mid-Mount 2.5mm Audio Jack

#### **Number of Pins**

5 - Pins

#### **Threading Option**

N - Non-Threaded Barrel


#### **Packaging**


TR - Tape and Reel

Contact Kycon for other options


#### STX-25442


Dimensions in mm













# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Phone Connectors category:

Click to view products by Kycon manufacturer:

Other Similar products are found below:

M444B 6J1041A R4F E12BPKG ECP4PKG 161-3502L-E MT333X 171-0350-EX 171-101A-EX 171-3325-EX 176S NC3MG-V NYS228G P10834 P2380 P2381X P2411X P2412 P2724 JM2PB-AU BULK 9144 S2674 280L 163-156N-2-E 163-158N-2-E 171-3308-EX 171-3500-E 2501FT CMT335 M10662 330Q RJ5VI-S 40116 TM1R-AU TM2PBMJ-AU TM2PJ-AU TM2PJ-AU BULK 4803.1351 49201 49205 TS3PBJ-AU TS3PBMJ-AU TT32BX 54B 40112 40205 XMT332B 52170017-331 570 NM3