KYCON





AUDIO JACKS: STX-3081 Series PCB Mount 3.5mm Low Profile Audio Jack

Product Features

Audio Applications for Computers and Multimedia Low Profile CSA/NRTL Certified File No. LR78160

Performance Specifications

Materials and Finish

Housing

PBT Thermoplastic, 15% Glass Filled, Black Color UL94V-0 Rated

Terminals

Copper Alloy, Matte Tin Plating

Barrel

Brass, Nickel Plating

Mechanical Characteristics

Insertion Force

0.4kg - 3.0kg

Extraction Force

0.3kg - 3.0kg

Electrical Characteristics

Contact Resistance

Before Durability Test

50 milliohms Max.

After Durability Test

100 milliohms Max.

Insulation Resistance

More than 100 Megohms Min. at 500V DC

Dielectric Withstanding Voltage


500V AC RMS for 1 Minute

Operating Temperature

-25°C to + 85°C

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

Generated Part Number



Series

STX-3081 - Low Profile Audio Jack

Number of Pins

3 - Pins

5 - Pins

Threading Option

C - Threaded Barred


N - Non-Threaded Barred

Contact Kycon for other options

STX-3081 Series


Dimensions in mm

STX-3081-3N





STX-3081-5C One Single Throw, Double Pole Switch





X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Phone Connectors category:

Click to view products by Kycon manufacturer:

Other Similar products are found below:

M444B 6J1041A R4F E12BPKG ECP4PKG 161-3502L-E MT333X 171-0350-EX 171-101A-EX 171-3325-EX 176S NC3MG-V NYS228G P10834 P2380 P2381X P2411X P2412 P2724 JM2PB-AU BULK 9144 S2674 280L 163-156N-2-E 163-158N-2-E 171-3308-EX 171-3500-E 2501FT CMT335 M10662 330Q RJ5VI-S 40116 TM1R-AU TM2PBMJ-AU TM2PJ-AU TM2PJ-AU BULK 4803.1351 49201 49205 TS3PBJ-AU TS3PBMJ-AU TT32BX 54B 40112 40205 XMT332B 52170017-331 570 NM3