KYCON





AUDIO JACKS: STX-3150 Series

3.5mm Jack Slim Design with Switch PCB Mount

Product Features

Audio Applications for Computers and Multimedia
Can Be Used To Activate Speakers, an Equalizer or to
Configure the Audio Signal
Up to One Double-Pole Single-Throw Switch
Spring Loaded Contacts for High Contact Reliability
Narrow Body Uses Minimal Board Space
CSA/NRTL Certified File No. LR78160

Performance Specifications

Materials and Finish

Housing

PBT Thermoplastic, UL94V-0 Rated, Black Color

Bushing

Brass. Nickel Plated

Terminals and Contacts

Phosphor Bronze, Silver Plated

Coil Springs

Spring Steel

Mechanical Characteristics

Insertion Force

0.3kg - 3.0kg

Extraction Force

0.3kg - 3.0kg

Durability

5000 Mating Cycles

Electrical Characteristics

Insulation Resistance

100 Megohms Min. at 500V DC

Contact Resistance

30 milliohms Max.

Dielectric Withstanding Voltage


500V AC RMS for 1 Minute

Operating Temperature

-25°C to + 80°C

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

Generated Part Number



Series

STX-3150 - 3.5mm Jack Slim Design with Switch PCB Mount

Number of Pins

3 - Pin

5 - Pin

Threading Option

C - Threaded Barrel


N - Non-Threaded Barrel

Contact Kycon for other Options


STX-3150 Series

Dimensions in mm





STX-3150-5N



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Phone Connectors category:

Click to view products by Kycon manufacturer:

Other Similar products are found below:

M444B 6J1041A R4F E12BPKG ECP4PKG 161-3502L-E MT333X 171-0350-EX 171-101A-EX 171-3325-EX 176S NC3MG-V NYS228G P10834 P2380 P2381X P2411X P2412 P2724 JM2PB-AU BULK 9144 S2674 280L 163-156N-2-E 163-158N-2-E 171-3308-EX 171-3500-E 2501FT CMT335 M10662 330Q RJ5VI-S 40116 TM1R-AU TM2PBMJ-AU TM2PJ-AU TM2PJ-AU BULK 4803.1351 49201 49205 TS3PBJ-AU TS3PBMJ-AU TT32BX 54B 40112 40205 XMT332B 52170017-331 570 NM3