KYCON





AUDIO JACKS:STX-3200 Series PCB Mount 3.5mm Audio Jack

Product Features

Audio Applications for Computers and Multimedia Available with Threaded or Non-Threaded Metal Bushing CSA/NRTL Certified File No. LR78160

Performance Specifications

Materials and Finish Housing

PBT Thermoplastic,15% Glass Filled, Black Color, UL94V-0 Rated

Terminals

Pin # 2R, 5T: Phosphor Bronze, Matte Tin Plated

Pin # 1S: Copper Alloy, Nickel Plated Pin # 3N, 4N: Brass, Matte Tin Plated

Mechanical Characteristics

Insertion Force

0.4kg - 3.0kg

Extraction Force

0.3kg - 3.0kg

Durability

5000 Mating Cycles

Electrical Characteristics

Contact Resistance

50 milliohms Max.

Insulation Resistance

100 Megohms Min. at 500V DC

Dielectric Withstanding Voltage


500V AC RMS for 1 Minute

Operating Temperature

-25°C to + 100°C

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

Generated Part Number



Series

STX-3200 - PCB Mount 3.5 Audio Jack

Number of Pins

3 - Pins

5 - Pins

Threading and Back Plate Option

CB - Threaded Barrel with Back Plate

NB - Non-Threaded Barrel with Back Plate


N - Non-Threaded Barrel

Contact Kycon for other options

STX-3200 Series


Dimensions in mm

STX-3200-3CB





STX-3200-5N





X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Phone Connectors category:

Click to view products by Kycon manufacturer:

Other Similar products are found below:

M444B 6J1041A R4F E12BPKG ECP4PKG 161-3502L-E MT333X 171-0350-EX 171-101A-EX 171-3325-EX 176S NC3MG-V NYS228G P10834 P2380 P2381X P2411X P2412 P2724 JM2PB-AU BULK 9144 S2674 280L 163-156N-2-E 163-158N-2-E 171-3308-EX 171-3500-E 2501FT CMT335 M10662 330Q RJ5VI-S 40116 TM1R-AU TM2PBMJ-AU TM2PJ-AU TM2PJ-AU BULK 4803.1351 49201 49205 TS3PBJ-AU TS3PBMJ-AU TT32BX 54B 40112 40205 XMT332B 52170017-331 570 NM3