## KYCON



**AUDIO JACKS: STX-3542 Series** 3.5mm, Audio Jack, SMT, 5 Pole

## **Product Features**

5-Pole contact, TRRRS Provides enough contacts for: Active Noise Canceling, Balanced Audio and Biaural Recordings Complies with EIA Standards

## Performance Specifications

Materials and Finish

Housing

High Temperature Thermoplastic, UL 94V-0 Rated

Color: Black
Contact Material

Phosphor Bronze, Gold Plated

## **Electrical Characteristics**

Insulation Resistance 100 Megohms at 500V DC Contact Resistance 30 milliohms Max. Dielectric Withstanding Voltage 500V AC RMS for 1 Minute

## **Mechanical Characteristics**

Insertion Force: 0.4kg - 3.0kg Withdrawal Force: 0.3kg - 3.0kg Durability: 5,000 Mating Cycles Operating Temperature


Mating Connectors

STX-P-5POLE

-25°C to + 70°C

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

#### **Generated Part Number**



#### **Series**

STX-3542- 3.5mm Audio Jack

#### **Number of Pins**

5 - 5 Pins, 5 Pole

## **Threading Option**

N - Non-Threaded Barrel

### **Plating**

G - Gold plated


#### **Packaging**

TR - Tape and Reel

Contact Kycon for other options

## STX-3542-5N-G-TR

Dimensions in mm



# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Phone Connectors category:

Click to view products by Kycon manufacturer:

Other Similar products are found below:

M444B 6J1041A R4F E12BPKG ECP4PKG 161-3502L-E MT333X 171-0350-EX 171-101A-EX 171-3325-EX 176S NC3MG-V NYS228G P10834 P2380 P2381X P2411X P2412 P2724 JM2PB-AU BULK 9144 S2674 280L 163-156N-2-E 163-158N-2-E 171-3308-EX 171-3500-E 2501FT CMT335 M10662 330Q RJ5VI-S 40116 TM1R-AU TM2PBMJ-AU TM2PJ-AU TM2PJ-AU BULK 4803.1351 49201 49205 TS3PBJ-AU TS3PBMJ-AU TT32BX 54B 40112 40205 XMT332B 52170017-331 570 NM3