

**Materials and Finish**

Housing: Nylon thermoplastic, UL94V-0 rated

Contacts: phosphor bronze, Whole Terminal Nickel Plated, With Gold Flash Plated In Contact Area

**Specifications**

Current Rating: 3A max.

Contact Resistance: 30 milliohms max.

Dielectric Withstanding Voltage: 650V AC rms for 1 minute

Insulation Resistance: 1000 megohm min. at 500V DC

Durability Rating: 120 mating cycles min.

Insertion Force: 6 oz. max. per contact

Extraction Force: 0.7 oz. min. per contact

Operating Temperature: -40°C to +80°C

**RoHS COMPLIANT**


Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	03/12/07	New Drawing	R. Aguirre	H. MA	R. Aguirre	03/12/07
A2	09/23/10	ECO #10-065	S. Vien	H. MA		
A3	08/13/18	Update Address	D. Shehan	N/A		
A4	02/01/19	ECO # 19-012	C. Kelleher	D. Shehan		

**SX1100-H-BLK**

2.54mm Pitch Mini Shunt, RoHS Compliant

with handle, black housing



UNITS  
mm

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Kycon](#) manufacturer:*

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)  
[609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-010LF](#)  
[65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5020](#) [707-](#)  
[5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#) [FCN-360C032-B](#) [FCN-](#)  
[367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)