



Part No. 1002857

EtherHelix™ Mission Critical GPS Antenna

1.575 GHz Circularly Polarized

Supports: Aviation, GPS Navigation Systems, Fire & Rescue, Asset Tracking, Automotive, Security, Home Network application



EtherHelix GPS Antenna Quadhelix design

1.575 GHz

KEY BENEFITS

Smallest Effective Size

Ethertronics' antennas require a smaller keep-out area for surrounding components, leading to a smaller effective size.

High Performance

Ethertronics' high efficiency and simple design rules lower development risk and speed time-to-market without sacrificing performance. Plus, high RF selectivity eliminates the cost and space for band-pass circuitry.

Reliability

Products are the latest RoHS version compliant.

APPLICATIONS

- GPS enabled phones
 GPS pavigation
- GPS navigation systems
- Mobile devicesTracking
- Wireless Monitoring •
- Medical/Healthcare applications
- Mission Critical ApplicationsCommercial/
- Communication Radar
- Industrial Automotive
- First Responders

EtherHelix™ series of GPS Quad Helix Isolated Magnetic Dipole™ (IMD) antennas deliver on the key needs of device designers for higher functionality and performance in the worlds smallest Stand alone Circular polarized external and internal designs. These innovative antennas provide compelling advantages for GPS enabled cell phones, navigation equipment, and other mobile devices.

Real-World Performance and Implementation

Antennas may look alike on the outside, but the important difference is inside. Other antennas may contain simple PIFA or monopole patch designs that inter-act with their surroundings, complicating component layout or changing performance with use position. Ethertronics' antennas utilize patented IMD technology to deliver a unique size and performance combination.

Electrical Specifications

Measured in Free space

Frequency	GPS - 1.575 GHz		
Polarization	Right Hand CP (RHCP)		
Peak Gain (dBi)	-3.0 [-5 dB at Zenith]		
Beam-width	120 degrees (Axial Ratio < 3dB)		
Axial Ratio (dB)	< 1.5 at zenith		
Average Efficiency (%)	27		
VSWR Match	2.0:1 max		
Feed Point Impedance	50 ohms unbalanced		
Power Handling	0.5 Watt CW		

Mechanical Specifications & Ordering Part Number


Ordering Part Number	1002857	
Size (mm)	34.93 height 15.0 diameter	
Connector	SMA Male	
Weight (grams)	11.8	
Mechanical Rating	IP 68 UV Protected	
Connector	SMA Male	
Operative Temperature (°C)	-40 to +85	
Humidity(°C)	95% RH @ 54	
Packaging	Trays: 60 per tray - 300 per master carton	





Ethertronics' EtherHelix GPS Antenna Specifications. Ethertronics produces a wide variety of standard and custom antennas to meet user needs.

Efficiency, Axial Ratio, RHCP / LHCP Plots

Typical performance, measured in free space








Antenna Radiation Patterns

Typical performance, measured in free space @ 1575 GHz






Ethertronics' EtherHelix GPS Antenna Specifications. Ethertronics produces a wide variety of standard and custom antennas to meet user needs.


Mechanical Dimensions

Typical antenna dimensions (mm)


Part Number	A (mm)	B (mm)	C (mm)
1002857	34.93 ± 0.5	15.0 ± 0.5	1.5 ± 0.3








Connector View



Front View



Diameter View

0

Bottom View

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antennas category:

Click to view products by Kyocera AVX manufacturer:

Other Similar products are found below:

GAN30084EU 930-033-R GW17.07.0250E 1513563-1 EXE902SM APAMPG-117 MAF94383 W3908B0100 W6102B0100 YE572113-30RSMM 108-00014-50 66089-2406 SPDA17RP918 A09-F8NF-M A09-F5NF-M RGFRA1903041A1T W3593B0100 W3921B0100 SIMNA-868 SIMNA-915 SIMNA-433 W1044 W1049B090 A75-001 WTL2449CQ1-FRSMM CPL9C EXB148BN 0600-00060 TRA9020S3PBN-001 Y4503 GD5W-28P-NF MA9-7N GD53-25 GD5W-21P-NF C37 MAF94051 MA9-5N EXD420PL B1322NR QWFTB120 MAF94271 MAF94300 GPSMB301 FG4403 AO-AGSM-OM54 5200232 MIKROE-2349 WCM.01.0111 MIKROE-2393 MIKROE-2352