



TBC SERIES

T4C HRC4000 Implantable Non Life Support and Non Implantable Life Support



The AVX T4C microchip medical series is designed for use in Implantable - Non-Life support or Non-Implantable - Life support medical applications with space limits. These components are screened using our newly designed Q-Process to effectively remove components that may experience parametric shifts through customer processing or display instability through life testing.

FEATURES

- Dedicated to medical applications
- HRC4000 - Implantable, Non-Life support
- Non-Implantable, Life support
- -55 to +125°C operation temperature
- Basic reliability better than 0.1%/1000hours
- Custom DCL / ESR options on selected parts



For RoHS compliant products, please select correct termination style.

T4C Standard - Standard option DCL and ESR limits including Q-Process screening.


T4C Custom – A custom option where specific DCL and ESR parameter limits can be agreed based Q-Process statistical screening. DCL down to 0.005CV on selected codes

APPLICATIONS

- Medical, Implantable - Non-Life support and Non-Implantable - Life support
- For additional information on Q-process please consult the AVX technical publication "Reaching the Highest Reliability for Tantalum Capacitors" (see the link: <http://www.avx.com/docs/techinfo/Qprocess.pdf>)

MARKING

K, L, R CASE



CASE DIMENSIONS: millimeters (inches)

| Code | EIA Code | EIA Metric | L+0.20 (0.008) -0.00 (0.000) | W+0.15 (0.006) -0.00 (0.000) | H+0.15 (0.006) -0.00 (0.000) | Termination Spacing(S) | Minimum Termination Length (Lt) |
|------|----------|------------|---------------------------------|---------------------------------|---------------------------------|------------------------|---------------------------------|
| K | 0402 | 1005-07 | 1.00 (0.039) | 0.50 +0.20 -0.00 | 0.50 +0.20 -0.00 | 0.40 (0.016) min | 0.10 (0.004) |
| | | | | (0.020) +0.008 -0.000 | (0.020) +0.008 -0.000 | | |
| L | 0603 | 1608-10 | 1.60 (0.063) | 0.85 (0.033) | 0.85 (0.033) | 0.55 (0.022) min | 0.15 (0.006) |
| R | 0805 | 2012-15 | 2.00 (0.079) | 1.35 (0.053) | 1.35 (0.053) | 0.70 (0.028) min | 0.15 (0.006) |

CAPACITANCE AND RATED VOLTAGE RANGE (LETTER DENOTES CASE SIZE)

| Capacitance | | Rated Voltage DC (V _R) to 85°C (Voltage Code) | | | |
|-------------|------|---|----------|---------------------|---------|
| µF | Code | 4V (G) | 6.3V (J) | 10V (A) | 16V (C) |
| 0.33 | 334 | | | | |
| 0.47 | 474 | | | K | |
| 1.0 | 105 | K | K | L | L |
| 2.2 | 225 | | | L | |
| 3.3 | 335 | | | | |
| 4.7 | 475 | K | | | |
| 10 | 106 | | | L ^(M) ,R | |
| 15 | 156 | | | | |
| 22 | 226 | | R | | |

Available Ratings (M tolerance only)

Please contact the factory for codes not listed in the table.

Note: Voltage ratings are minimum values. AVX reserves the right to supply higher ratings in the same case size, to the same reliability standards with customer written approval.



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at www.avx.com/disclaimer/ by reference and should be reviewed in full before placing any order.

TBC SERIES

T4C HRC4000 Implantable Non Life Support and Non Implantable Life Support



HOW TO ORDER

| | | | | | | | | | | | |
|------------|-----------|---|-----------------------|--|---------------------------|--|--------------------|-------------------------|---------------------|---|------------------------------|
| T4C | R | 105 | * | 006 | C | □ | L | Q | 4 | ^ | 00 |
| Type | Case Size | Capacitance Code | Capacitance Tolerance | Voltage Code | Standard or Low ESR Range | Packaging | Inspection Level | Reliability Grade | Qualification Level | Termination Finish | Suffix |
| | | pF code: 1st two digits represent significant figures 3rd digit represents multiplier (number of zeros to follow) | M = ±20% K = ±10% | 004 = 4Vdc 006 = 6.3Vdc 010 = 10Vdc 016 = 16Vdc | C = Std ESR | R, P = 7" Reel X, Q = 4 1/4" Reel B = Bulk | L = Lab Inspection | Q = Q-Process Screening | 4 = HRC4000 | 7 = 100% Tin 9 = Gold Plated H = SnPb Non RoHS H, 9 = (Contact Manufacturer) | 00 = Standard XX = Custom |

TECHNICAL SPECIFICATIONS

| | | | | | |
|------------------------------------|--|-----|-----|-----|----|
| Technical Data: | All technical data relate to an ambient temperature of +25°C | | | | |
| Capacitance Range: | 0.47 µF to 22 µF (for extended range contact manufacturer) | | | | |
| Capacitance Tolerance: | ±10%; ±20% | | | | |
| Leakage Current DCL: | 0.01CV or 0.3µA whichever is the greater | | | | |
| Rated Voltage (V _R) | ≤ +85°C: | 4 | 6.3 | 10 | 16 |
| Category Voltage (V _C) | ≤ +125°C: | 2.7 | 4 | 6.7 | 10 |
| Surge Voltage (V _S) | ≤ +85°C: | 5.2 | 8 | 13 | 20 |
| Surge Voltage (V _S) | ≤ +125°C: | 3.2 | 5 | 8 | 13 |
| Temperature Range: | -55°C to +125°C | | | | |
| Reliability: | 0.1% per 1000 hours at 25°C, V _R with 0.1Ω/V series impedance, 90% confidence level | | | | |

RATINGS & PART NUMBER REFERENCE

| AVX Part No. | Case Size | Capacitance (µF) | Rated Voltage (V) | Rated Temperature (°C) | Category Voltage (V) | Category Temperature (°C) | DCL Max. (µA) | DF Max. (%) | ESR Max. @ 100kHz (Ω) | MSL | 100kHz RMS Current (mA) | | |
|------------------------|-----------|------------------|-------------------|------------------------|----------------------|---------------------------|---------------|-------------|-----------------------|-----|-------------------------|------|-------|
| | | | | | | | | | | | 25°C | 85°C | 125°C |
| 4 Volt @ 85°C | | | | | | | | | | | | | |
| T4CK105*004C□LQ4*00 | K | 1 | 4 | 85 | 2.7 | 125 | 0.3 | 6 | 15 | 3 | 32 | 28 | 13 |
| T4CK475*004C□LQ4*00 | K | 4.7 | 4 | 85 | 2.7 | 125 | 0.3 | 20 | 15 | 3 | 32 | 28 | 13 |
| 6.3 Volt @ 85°C | | | | | | | | | | | | | |
| T4CK105*006C□LQ4*00 | K | 1 | 6.3 | 85 | 4 | 125 | 0.3 | 6 | 15 | 3 | 32 | 28 | 13 |
| T4CR226*006C□LQ4*00 | R | 22 | 6.3 | 85 | 4 | 125 | 1.4 | 10 | 5 | 3 | 95 | 85 | 38 |
| 10 Volt @ 85°C | | | | | | | | | | | | | |
| T4CK474*010C□LQ4*00 | K | 0.47 | 10 | 85 | 6.7 | 125 | 0.3 | 6 | 15 | 3 | 32 | 28 | 13 |
| T4CL105*010C□LQ4*00 | L | 1 | 10 | 85 | 6.7 | 125 | 0.3 | 6 | 7.5 | 3 | 58 | 52 | 23 |
| T4CL225*010C□LQ4*00 | L | 2.2 | 10 | 85 | 6.7 | 125 | 0.3 | 6 | 7.5 | 3 | 58 | 52 | 23 |
| T4CL106M010C□LQ4*00 | L | 10 | 10 | 85 | 6.7 | 125 | 1 | 20 | 7.5 | 3 | 58 | 52 | 23 |
| T4CR106*010C□LQ4*00 | R | 10 | 10 | 85 | 6.7 | 125 | 1 | 8 | 5 | 3 | 95 | 85 | 38 |
| 16 Volt @ 85°C | | | | | | | | | | | | | |
| T4CL105*016C□LQ4*00 | L | 1 | 16 | 85 | 10 | 125 | 0.3 | 6 | 7.5 | 3 | 58 | 52 | 23 |

Moisture Sensitivity Level (MSL) is defined according to J-STD-020.

All technical data relates to an ambient temperature of +25°C. Capacitance and DF are measured at 120Hz, 0.5V RMS with a maximum DC bias of 2.2 volts.

DCL is measured at rated voltage after 5 minutes.

The EIA & CECC standards for low ESR Solid Tantalum Capacitors allow an ESR movement to 1.25 times catalogue limit post mounting.

TBC SERIES

T4C HRC4000 Implantable Non Life Support and Non Implantable Life Support



QUALIFICATION TABLE

| TEST | T4C HRC4000 (Temperature range -55°C to +125°C) | | | | | | | | | | |
|-----------------------|--|---------------|----------------|--------------------|------------------------------|-----------|------------|------------|------------|------------|--|
| | Condition | | | Characteristics | | | | | | | |
| Endurance | Determine after application of rated voltage for 2000 +48/-0 hours at 85±2°C and then leaving 1-2 hours at room temperature. Also determine of 125°C temperature, category voltage for 2000 +48/-0 hours and then leaving 1-2 hours at room temperature. Power supply impedance to be ≤0.1Ω/V. | | | Visual examination | no visible damage | | | | | | |
| | | | | DCL | 1.25 x initial limit | | | | | | |
| | | | | ΔC/C | within ±10% of initial value | | | | | | |
| | | | | DF | initial limit | | | | | | |
| | | | | ESR | 1.25 x initial limit | | | | | | |
| Storage Life | 125°C, 0V, 2000h | | | Visual examination | no visible damage | | | | | | |
| | | | | DCL | 1.25 x initial limit | | | | | | |
| | | | | ΔC/C | within ±10% of initial value | | | | | | |
| | | | | DF | initial limit | | | | | | |
| | | | | ESR | 1.25 x initial limit | | | | | | |
| Temperature Stability | Step | Temperature°C | Duration (min) | | +20°C | -55°C | +20°C | +85°C | +125°C | +20°C | |
| | 1 | +20±2 | 15 | DCL | IL* | n/a | IL* | 10 x IL* | 12.5 x IL* | IL* | |
| | 2 | -55+0/-3 | 15 | ΔC/C | n/a | +0/-10% | ±5% | +10/-0% | +12/-0% | ±5% | |
| | 3 | +20±2 | 15 | DF | IL* | 1.5 x IL* | IL* | 1.5 x IL* | 2 x IL* | IL* | |
| | 4 | +85+3/-0 | 15 | ESR | 1.25 x IL* | 2.5 x IL* | 1.25 x IL* | 1.25 x IL* | 1.25 x IL* | 1.25 x IL* | |
| | 5 | +125+3/-0 | 15 | | | | | | | | |
| 6 | +20±2 | 15 | | | | | | | | | |
| Surge Voltage | Test temperature: 85°C+3/0°C Test voltage: Rated voltage at 85°C Surge voltage: 1.3x rated voltage at 85°C Series protection resistance 1000±100Ω Discharge resistance: 1000Ω Number of cycles: 1000x Cycle duration: 6min; 30 sec charge, 5min 30 sec discharge | | | Visual examination | no visible damage | | | | | | |
| | | | | DCL | initial limit | | | | | | |
| | | | | ΔC/C | within ±5% of initial value | | | | | | |
| | | | | DF | initial limit | | | | | | |
| | | | | ESR | 1.25 x initial limit | | | | | | |

*Initial Limit

LOT ACCEPTANCE TESTING

| TEST | T4C HRC4000 (Temperature range -55°C to +125°C) | | |
|---------------------|---|--------------------|-----------------------------|
| | Condition | Characteristics | |
| Lot Acceptance Test | 25 Pieces from each lot • Read and Record Initial Electricals • Bake Out @ 125°C for 2 Hours • Mount using AVX recommended profile • Read and Record Post Mounting Electricals • Life Test: 6 hours, 2/3 R.V., 125°C • Read and Record Post Electricals | DCL | initial limit |
| | | ΔC/C | within ±5% of initial value |
| | | DF | initial limit |
| | | ESR | 1.25 x initial limit |
| | | 0 Failures Allowed | |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Tantalum Capacitors - Solid SMD category:](#)

Click to view products by [Kyocera AVX manufacturer:](#)

Other Similar products are found below :

[CWR06HC106KB](#) [B45197-A2157-M509](#) [B45197A5226M409](#) [NTC-T476K10TRDF](#) [CWR06KC106KP](#) [CWR09KB106KCA](#)
[TCSCS1A336KBAR](#) [TCTP0J336M8R](#) [B45196-H5106-K309](#) [B45196-H6226-K509](#) [CWR09JC225JBB](#) [T83D475K050RCCL](#)
[TCSCS1A476KBAR](#) [T83E107K016RCCL](#) [T83D685K035RCCL](#) [595D107X0004B2T](#) [CWR11HH105KB](#) [293D155X9020A2DE3](#)
[CWR09NC224KB](#) [CWR11MC685KCB](#) [CWR29FC685KCEC](#) [CWR09NC684KM](#) [CWR19MH106KCHB](#) [CWR29HH155KCBB](#)
[CWR29FC336KDGC](#) [CWR09NC225KDB](#) [CWR29FC475KDDC](#) [CWR29HC225KCAC](#) [CWR11KC106KBB](#) [CWR09JH105KC](#)
[293D476X9035E2TE3](#) [CWR29JC335KDDC](#) [CWR29KC226JCGC](#) [CWR29FC105KDAC](#) [CWR29DC337KCHC](#) [NTC-T686K6.3TRBF](#)
[595D686X9010B2T](#) [594D686X9016C2T](#) [595D106X0025C8T](#) [TAZH685K035LBSB0824](#) [TAZG107K010LBSB0800](#)
[TAZH475K050LBSB0H23](#) [TAJD107K016KNJ](#) [TAZH227K010LBSB0024](#) [TAZH156K025CBSZ0824](#) [TAZH227J010LBSZ0800](#)
[TPSE687M006H0045](#) [TBJD156K025CBSZ0824](#) [TMCSA1V154MTRF](#) [TMCSA0G335MTRF](#)