

Innovative **Technology** for a **Connected** World

S4908WB Omni Antenna



The wide band S4908WB is one in a series of omni antennas that have been optimized for direct chassis mount to outdoor radios or NEMA enclosures. These antennas come standard with an integrated N male or female connector directly mounted to the base of the antenna.

The rugged directly mounted connector is perfect for outdoor MESH applications that often require the antenna to be directly mounted to the radio or enclosure. The antenna is enclosed in a UV stable, water resistant housing and the antenna will provide years of trouble free service.

The antenna series includes antennas of various gains all with integrated N male or female connectors. There is a mast mount hardware kit available for applications that require the antenna to be remotely mounted from the radio enclosure.





- Vertically polarized omnidirectional
- Rugged, lightweight and water resistant
- Full 802.11a wide band performance
- Direct to radio mounting
- 5 GHz broad band WLAN

MARKETS

- College campuses
- Airports
- Hospitals
- Transportation centers
- WiMAX

| PARAMETER | SPECIFICATION |
|-----------------------------|--|
| Antenna Part Number | S4908WB |
| Frequency Range (MHz) | 4900 - 5875 |
| Gain (dBi) | 10 |
| Maximum VSWR | 2.0:1 |
| 3 dB Beamwidth - Elevation | 8° |
| 3 dB Beamwidth - Azimuth | Omnidirectional |
| Polarization | Vertical linear |
| Maximum input power (watts) | 10 |
| Input Impedance (Ohms) | 50 |
| Mechanical size | 19.6 x 1.0 in |
| Weight (lbs.) | 0.4 |
| Wind survival rating (mph) | Operational 100 / Survival 136 |
| Antenna connection | Type N male or female |
| Radome | White UV Polycarbonate |
| Mount style | Direct mount (upright or inverted) |
| Temperature (°C) | Operational -30° to +65° Storage -40° to +80° |





H Plane 5.5 Ghz

global solutions: local support ™

Americas: +1.847 839.6907 IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12 IAS-EUSales@lairdtech.com Asia: +1.65.6.243.8022 IAS-AsiaSales@lairdtech.com

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies materials or unsequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2011 Laird Technologies, Log, and other marks are traders or registered trade marks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antennas category:

Click to view products by Laird Connectivity manufacturer:

Other Similar products are found below:

CCT FM1 ABFT AD-NM-SMAF 001-0021 CTC110 MAF94149 EXE902SF MMCX-SMA-100 PDQ24496-91NF GAN30084EU 930-033-R A08-HABUF-P5I AAF95035 DG-ANT-20DP-BG-B APAMPGJ-141 1513563-1 OF86315-FNF OP24516DS-91NM A09-HASM-7 EXE902MD EXE902SM SPDA17806/2170LAR APAMPG-117 GPS1575SP26-004 GPS15MGSMA CMD69273P-30NF CMQ69273-30NF RD2458-5-OTDR-NM RD2458-5-RSMA TRAB24/49003 W4120ER5000 W6102B0100 YE572113-30RSMM 108-00014-50 SPDA17RP918 OP24516SX-91NM OP24516SX-91RSMM CMQ69273P-30NF CMS69273-30NF CMS69273P-30NF TRAB24003N TRAB24003NP TRAB8213NP TRAB8903 A09-Y8NF A09-Y11NF A09-HSM-7 A09-F8NF-M A09-F5NF-M