
* UNCONTROLLED DOCUMENT * FOR REFERENCE ONLY



CORE DIMENSIONS							
UNCOATED	CORE			35T0375-100			
	MM	INCHES		MM	INCHES		
OD	9.53	(.375)	±	.25	(.010)		
ID	4.75	(.187)	±	.25	(.010)		
TH	3.18	(.125)	±	.13	(.005)		
EPOXY COATING				35T0	375-10H		
OD	10.55	(.415)	±	max			
ID	3.73	(.147)	±	min			
TH	4.07	(.160)	±	max			

WEIGHT/K 0.9072 KGS 2.0000 LBS INITIAL PERMEABILITY 5000

ELECTRICAL SPECIFICATIONS								
	MIN		NOM	MAX	MAX	FREQ.	VOLT.	
	(μH)	MIN TOL.	(μH)	(μH)	TOL.	(kHz)	(V)	TURNS
L1	1.772	(-20%)	2.214	2.657	+20%	100	≤.0032	1
L2	177.2	(-20%)	221.4	265.7	+20%	100	≤.0324	10
Q	10	-	-	-	-	100	≤.0032	1

		COAT	INC SPECIFICA	TIONS				
COATING SPECIFICATIONS								
			Max.					
			Coating					
			Thickness	Min. DLB	Min. DLB	TEST FORCE		
		TYPE	(mm)	VAC	VDC	(LB)		
35T	0375-100	UNCOATED	-	-	-	-		
35T	0375-10H	EPOXY	0.76	1000	1333	.83		

NOTES

Steward

THIS DOCUMENT CONTAINS INFORMATION WHICH IS PROPRIETARY TO STEWARD. NO PRODUCTION OR PUBLICATION OF THIS DOCUMENT IN WHOLE OR IN PART SHALL BE MADE WITHOUT WRITTEN AUTHORIZATION FROM STEWARD.

Date:	01/05/2006	DWG #:	35T0375-10H-C	Title:	REV:
Drawn By:	JRK			35Т0375-10Н	C

REV	Description	ECN#	Date	INT
С	CHANGE COATING DESCRIPTION FROM		01/05/2006	JRK
	POLYURETHANE ADD KGS TO WEIGHT			

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for laird connectivity manufacturer:

Other Similar products are found below:

29D3800-000 63202-501 8860-0062-324-72 A10237-21 A14564-01 A15344-01 DA-033-12-02-00-00 DVK-PRM120 ODH24-9-WB
9360002-301 A10093-37 A10874-01 A11809-02 A15796-26 A16367-04 CMQ69273-30NF 430701-501 430744-513 430848-509 4106-.25
430140-502 430745-505 DVK-RM191-SM-01 0650-00005 56460-501 POE-24IR DVK-BL600-SC TPCM FSF-52 CRX150 CRX150B
DVK-BT900-SA-03 B3003 PA24-19 POE-HP-24i PLC1666 A17690-10 Y4065 387000840 A17653-12 YS1505 387000866 OD9-8
A17775-05 CW42S A17690-09 Y4066 HDDA3W-29-DP R2T9-12 PT400100NSMA DVK-MSD50NBT