

SECURE, POWERFUL WIRELESS ENGINE FOR YOUR IOT DESIGN



Building on Laird's expertise with Nordic from the BL600 and BL652 series comes the most powerful yet - the BL654 series! It provides OEMs with the maximum design flexibility and performance. A complete multi-protocol embedded wireless offering with exceptional processing capability, all at a micro power budget.

Powered by Nordic's nRF52840 silicon, the small form factor BL654 module with integrated antenna (part # 451-00001) is embedded inside the robust, **packaged USB Adapter**. The BL654 USB Adapter uses a simple, intuitive **AT Command Set**, as well as Laird's own **smartBASIC** environment.

Leverage the BL654 USB Adapter to enable any BLE device or sensor to communicate to any PC, laptop, or mobile computer without any complicated installation or software support requirements.

- **Bluetooth v5** Bluetooth Low Energy (BLE)
- Industrial Temp Rating (-40° to +85° C)
- **Robust footprint** (18.39 mm x 50.74 mm x 11mm)
- BLE Peripheral/Central roles with DTM embedded
- **2Mbps & LE Long Range**: Support for 2Mbps, 1Mbps, & 125Kbps coded
- **Capable of Hostless operation** – Internal MCU reduces BOM
- **Powerful Core** Cortex-M4F (1MB Flash, 256KB RAM)
- Built on years of experience with Nordic (BL600 & BL652 Series)
- **Application Design Choice**: Leverage Laird's *smartBASIC* or simple AT Command Set (source available)

Note: Nordic SDK is not supported on the BL654 USB dongle, part #451-00003. For Nordic SDK / Zephyr options, contact Laird Connectivity sales.

FEATURES AT A GLANCE



TRULY HOSTLESS OPERATION FOR AUTOMATED USE CASES

Combination of on-module MCU and preloading a *smartBASIC* application enables simultaneous central/peripheral role support for powerful hostless sensor applications.



SPEED TO MARKET

Easily write event-driven, automated applications, no toolchain required with *smartBASIC*.



EXTREMELY EFFICIENT POWER MANAGEMENT

Customize to balance throughput with power usage, enabled by ultra-low power sleep mode.



GLOBAL APPROVALS – MAKE YOURSELF AT HOME

Carries several modular FCC, IC, CE, RCM, MIC and Bluetooth SIG approvals.



PERSONAL SUPPORT FROM DESIGN TO MANUFACTURE

Laird's industry-renowned support is passionate about helping you speed your design to market.

APPLICATION AREAS



IoT Devices and Sensors



Beacons and Proximity Applications



Secure Medical Peripherals



Industrial Monitoring

KEY SPECIFICATIONS

CATEGORY	FEATURE	SPECIFICATION	
Wireless Specification	Bluetooth®	v5 – Single-Mode (Peripheral and Central Roles)	
	Frequency	2.402 - 2.480 GHz	
	Transmit Power	+ 8 dBm (maximum). Configurable down to -40 dBm	
	Receive Sensitivity		-95 dBm (typical @ BLE 1 Mbps)
			-92 dBm (typical @ BLE 2 Mbps)
			-103 dBm (typical @ BLE 125 Kbps)
	Link Budget	103 dB (@ BLE 1 Mbps), 111 db (@ BLE 125Kbps)	
Antenna Options	PCB Trace antenna		
Host Interface and Peripherals	USB - UART Interface	TX, RX, CTS, RTS. Default: 115200, N, 8, 1. Configurable from 1200 bps to 1 Mbps	
	USB Connector	FTDI based – Virtual COM port	
	Other	Configurable LED	
Key BLE Features	Bluetooth Low Energy	<ul style="list-style-type: none"> ▪ GATT Client & GATT Server – Any Adopted / Custom Services ▪ Central / Peripheral Roles. ▪ Up to 8 BLE connections ▪ BLE Mesh ▪ CODED PHY ▪ 2M PHY 	
		<ul style="list-style-type: none"> ▪ LE Advertising Extensions ▪ LE Secure Connections ▪ Data Packet Length Extensions ▪ LE Privacy v1.2 ▪ LE Ping ▪ vSP – Virtual Serial Port 	
Programmability Options	smartBASIC	On-board BASIC programming language	
	AT Command Set	Simple AT 'Hayes style' command protocol Note: AT Command Protocol enabled via a smartBASIC application (available for modification)	
	Firmware Upgrade	Via UART	
Support (as Virtual COM port)	Operating Systems	Windows 7 - 10 and server editions 2008 - 2019	
		Windows Embedded Mac OSX Linux & Android	
Power	Consumption - Current	Max Peak Radio Current (@ +8dBm TX) – 14.1mA (DCDC at 3V)	
		Max Peak Radio Current (@ 0dBm TX) – 4.9mA (DCDC at 3V)	
		Standby Doze – ~3.1µA Deep Sleep – ~0.4µA (external signal wake up) Note: In USB suspend mode, power consumption is slightly increased, due to FTDI chip	
	Supply Voltage	5.0V +/- 10% Powered by standard USB port	
Physical	Dimensions	18.39 mm x 50.74 mm x 11mm	
Environmental	Temp Range	-40°C to +85°C	
Miscellaneous	Lead Free	Lead-free and RoHS compliant	
Development Tools	Utilities	UwTerminalX (Multi-platform)	
		Android and iOS applications	
		UART firmware upgrade	
Qualifications	Bluetooth®	Complete Declaration ID	
Regulatory	Approvals	FCC / IC / CE / MIC / RCM	

For full specifications on BL654 module on which the BL654 USB Adapter is based, please see the BL654 datasheet.

PART #	DESCRIPTION
451-00003	Intelligent USB Bluetooth v5 Adapter

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Bluetooth Modules - 802.15.1 category](#):

Click to view products by [Laird Connectivity manufacturer](#):

Other Similar products are found below :

[A2541R24A10GM](#) [CYBLE-212023-10](#) [BM78SPP05MC2-0002AA](#) [CYW20732S](#) [968EMB0019](#) [E73-2G4M08S1CX](#) [TB-03F](#) [TB-03F-AT_Mesh](#) [TB-04](#) [TB-04--AT_Mesh](#) [BT3L\(jibu\)](#) [BT5S\(xoft\)](#) [BT5S\(4k43\)](#) [BT5S\(jcyv\)](#) [ENW89857A1KF](#) [ENW49D01A1KF](#) [SPB228-D-188980124](#) [DG100 IOT EDGE GATEWAY](#) [1327](#) [RN42HID-I/RM](#) [ENW-89829C3KF](#) [BLE113-A-V1](#) [BM70BLE01FC2-0B03AA](#) [ACN52832](#) [A2541E24A10GM](#) [RN42-I/RM630](#) [450-0168R](#) [MOTG-BLUETOOTH](#) [ABBTM-2.4GHz-52-T](#) [ABBTM-2.4GHz-T](#) [ABBTM-2.4GHz-T2](#) [ACN52840](#) [4076](#) [4077](#) [AFERO-BL24-01](#) [BLED112](#) [BM62SPKS1MC2-0001AA](#) [BM78SPPS5MC2-0002AA](#) [PX0880/1](#) [DAT12](#) [BT680F](#) [PBA31309V1.00 S LK64](#) [ATSAMB11-MR510CA](#) [BM20SPKA1NBC-0001AA](#) [BM20SPKS1NBC-0001AA](#) [BM23SPKS1NB9-0B02AA](#) [BM70BLE01FC2-0B04AA](#) [BM77SPP03MC2-0007AA](#) [BM77SPP03MC2-0008AA](#)