# Tpcm<sup>™</sup> FSF-52



## Innovative **Technology** for a **Connected** World



## Tpcm™ FSF-52

Tpcm<sup>™</sup> FSF-52 is a free standing film. It contains no substrate. At temperatures greater than 52°C, Tpcm<sup>™</sup> FSF-52 changes into a molten state and, under low closure force, wets the heat sink and component surfaces to create a very thin, low thermal resistance interface. Tpcm<sup>™</sup> FSF-52 is thixotropic and won't flow from the interface.

Tpcm<sup>™</sup> FSF-52 has superior thermal performance comparable to the highest performing grease and phase change products available. Since it is a free standing film, it is easy to handle and is a great replacement for messy grease.

Tpcm<sup>™</sup> FSF-52 is available as individual die cut parts, kiss cut parts on rolls or sheets, and uncut rolls. Tpcm<sup>™</sup> FSF-52 is 0.005″ (0.125mm) thick.

#### FEATURES AND BENEFITS **VROHS**

- Superior thermal resistance after phase change at 52°C
- Thixotropic won't bleed or flow out of the interface
- Easy to handle and is a great messy grease replacement
- Free standing film

#### **APPLICATIONS**

- Microprocessors
- Chipsets
- Graphic processing chips
- Custom ASICS

PROPERTIES	TPCM FSF-52	TEST METHOD
Construction & Composition	Ceramic filled wax based free standing film	
Color	White	Visual
Thickness	0.005" (0.125mm)	
Thickness Tolerance	+/-0.001" (0.025mm)	
Density	2.0 g/cc	Helium Pycnometer
UL Flammability Rating	94 V0	
Phase Change Temperature	52°C	
Thermal Conductivity	0.9W/mK	ASTM D5470
Thermal Resistance @ 10 psi @ 50 psi	0.042 C-in <sup>2</sup> /W (0.27 C-cm <sup>2</sup> /W) 0.030 C-in <sup>2</sup> /W (0.19 C-cm <sup>2</sup> /W)	ASTM D5470 (modified)
Dielectric constant:@ 1KHz / 1MH	3.8 / 3.4	ASTM D150
Volume resistivity	7.9 x 10 <sup>13</sup>	ASTM D257

Standard sheet sizes: 18"x18" & 9"x0". Sheets are supplied with white release paper as top and bottom liner. Individual die cut shapes can also be supplied.

Rolls: 18" x 250 ft on 3" core, 18" x 250 ft on 10" core. Rolled on one white liner for 3" cores.

Rolled between two white liners for 10" cores and optional red liner can replace on white liner on 10" cores.

# global solutions: local support...

Americas: +1.800.843.4556 Europe: +49.8031.2460.0 Asia: +86.755.2714.1166

CLV-customerservice@lairdtech.com www.lairdtech.com/thermal

#### THR-DS-Tpcm-FSF-52-0210

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end use, since Laird Technologies and its agents cannot be evanere of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies fracts and the Laird Technologies, and with the end of any kind. All Laird Technologies, no. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trade marks or registered trade marks of Laird Technologies or any third Parthonic Technologies or any third party intellectual property rights.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Thermal Interface Products category:

Click to view products by Laird Connectivity manufacturer:

Other Similar products are found below :

 7721-9PPS
 FGN80-2
 PFM-172-60
 A-40
 174-9-230P
 9601-7
 5300AC 1.500G
 08133
 V6622C
 TVQF-1225-07S
 TP0001
 4860
 SC80-W2

 V6516C
 A17713-06
 A17713-05
 A17690-06
 A17775-03
 A17690-05
 A17690-03
 A17653-02
 A17689-02
 A17690-04
 A17775-05
 A17775 

 06
 A17690-08
 A17690-02
 A17689-06
 A17653-06
 A17690-12
 A17653-03
 A17536-02
 A17689-03
 A17536-10
 A17752-13
 A17752-04

 A17752-07
 A17634-12
 19-36565-0001-1
 A17752-09
 22000-001A
 A17752-20
 A17752-16
 A17752-12
 A17653-04
 A17634-10
 A17634-09

 A17634-07
 A17633-20
 A17633-07
 A17633-07
 A17633-07
 A17633-07