

Smart Technology. Delivered.

Mobile Load Coil Antenna

Standard B7603

PREMIUM MOBILE LOAD COIL ANTENNAS ARE INDUSTRY STANDARD

Laird's ongoing commitment to refinement in mechanical and electrical design has resulted in the most technically advanced mobile load coil antennas on the market. Exclusive features such as stainless steel whips, housings constructed with ABS material injected molded around a solid brass insert, and gold plated push pin contacts make Laird the obvious choice for quality and long lasting value for demanding mobile radio communications.


FEATURES ✓ RoHS

- %" wave design for true 4 dBi performance
- High performance mobile antenna operates on a 6" diameter (min.) ground plane
- Straight stainless steel
- Easy installation with optional NMO Mounts
- 100% tested on a network

MARKETS

- Public safety
- Transportation
- Utility
- Military mobile

ANTENNA PATTERNS



Elevation Polar Radiation Pattern 764 MHz

SPECIFICATIONS

ELECTRICAL	
Frequency Range	760-870 MHz
VSWR	≤ 2.2:1
Nominal Gain	4 dBi
Maximum Power	200 W
Nominal Impedance	50 Ω
Polarization	Vertical
Pattern	Omnidirectional
Half-PowerBeamwidth (Elevation° x Azimuth°)	70° x 360°
Coaxial Cable Length & Type (For Vertical Polarization)	None
Terminations	NMO style

MECHANICAL			
Color	Black chrome or chrome		
Height	6.5 in (16.5 cm)		
Diameter	1.43 in (3.63 mm)		
Weight	0.38 lbs (172.37 g)		
Material	ABS		
Mounting Information (Sold	Optional p/n: NMO Mountable MB8, MAB8		
Separately)	BlackHawk NS1535		
Noise Suppressor	1-35 Volts, 15 amps Noise suppessor (Sold Separately)		

MODEL AND ORDERING INFORMATION

MO	DEL	DESCRIPTION	OVERALL HEIGHT	TUNING
B76	03	760-870 MHz, Base Loaded 5/8 Wave, Chrome Finish	6.5 in	Fixed tune @817 MHz
BB7	603	760-870 MHz, Base Loaded 5/8 Wave, Black Finish	6.5 in	Fixed tune @817 MHz

ANT-DS-B7603 0516

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies hall not be laible for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies' Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2016 Laird Technologies, Inc. an an affiliate company thereof. Laird, Laird Technologies, the Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.

Americas: +1.847 839.6925 IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941 IAS-EUSales@lairdtech.com

Asia:

IAS-AsiaSales@lairdtech.com

Middle East and Africa: +44.1628.858941 IAS-MEASales@lairdtech.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antennas category:

Click to view products by Laird Connectivity manufacturer:

Other Similar products are found below:

GAN30084EU 930-033-R GW17.07.0250E 1513563-1 EXE902SM APAMPG-117 MAF94383 W3908B0100 W6102B0100 YE572113-30RSMM 108-00014-50 66089-2406 SPDA17RP918 A09-F8NF-M A09-F5NF-M RGFRA1903041A1T W3593B0100 W3921B0100 SIMNA-868 SIMNA-915 SIMNA-433 W1044 W1049B090 A75-001 WTL2449CQ1-FRSMM CPL9C EXB148BN 0600-00060 TRA9020S3PBN-001 Y4503 GD5W-28P-NF MA9-7N GD53-25 GD5W-21P-NF C37 MAF94051 MA9-5N EXD420PL B1322NR QWFTB120 MAF94271 MAF94300 GPSMB301 FG4403 AO-AGSM-OM54 5200232 MIKROE-2349 WCM.01.0111 MIKROE-2393 MIKROE-2352