

RF Cable Assembly CA178 700 MHz to 5.82 GHz



The CA178 cable assemblies offered by Laird are engineered for peak performance up to 6 GHz. They are tested 100% and certified to meet performance specifications. Equipment manufacturers require certified cable assemblies to minimize system losses to within known parameters and these cable assemblies meet those requirements. The manufacturing processes and raw materials are well controlled in order to provide very consistent performance from lot to lot.


FEATURES **✓** RoHS


- Consistent low loss design construction
- 100% tested and certified to meet specifications
- · Various connector options available
- Flexible high temperature kink resistant cable jacket

MARKETS

- High performance wireless systems
- OEM equipment
- WiMAX

INSERTION LOSS BY FREQUENCY





PARAMETER	CA178-NFB-UFL-8	CA178-NFB-UFL-12	
Insertion loss (700-5825 MHz)	-1.5 dB max	-2.5 dB max	
Length	8 in (203 mm)	12 in (305 mm)	
Weight	1.4 oz (40 gm)	1.5 oz (43 gm)	
Connector types	N female bulkhead - UFL	N female bulkhead - UFL	
N connector seal	O-ring	O-ring	
Contact plating	Gold	Gold	
Operating temperature	-40 to +125°C	-40 to +125°C	

SYSTEM ORDERING

CA178-NFB-UFL-8 N Female Bulkhead to U.FL 8 in CA178-NFB-UFL-12 N Female Bulkhead to U.FL CA178-NM-UFL-8 12 in N Male to U.FL 8 in N Male to U.FL 12 in

Americas: +1.847 839.6907 IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941 IAS-EUSales@lairdtech.com Asia: +86.21.5855.0827.127 IAS-AsiaSales@lairdtech.com

www.lairdtech.com



RF Cable Assembly CA178 700 MHz to 5.82 GHz

PART NUMBER	CONNECTOR 1	CONNECTOR 2	CABLE LENGTH (INCHES)	CABLE TYPE	MAX INSERTION LOSS (DB)
CA100-NFB-MC-12	N female bulkhead	MC-card	12	LMR100 (equivalent)	1.5
CA100-NFB-MMCX-12	N female bulkhead	MMCX	12	LMR100 (equivalent)	1.5
CA100-NFB-RASMAM-12	N female bulkhead	Right angle SMA male	12	LMR100 (equivalent)	1
CA100-NFB-RMMCX-12	N female bulkhead	Reverse polarity MMCX	12	LMR100 (equivalent)	1.5
CA100-NFB-RSMAM-12	N female bulkhead	Reverse polarity SMA male	12	LMR100 (equivalent)	1
CA100-NFB-RTNCM-12	N female bulkhead	Reverse polarity TNC male	12	LMR100 (equivalent)	1
CA100-NFB-SMAM-8	N female bulkhead	SMA male	8	LMR100 (equivalent)	0.8
CA100-NM-MC-12	N male	MC-card	12	LMR100 (equivalent)	1
CA100-NM-MMCX-12	N male	MMCX	12	LMR100 (equivalent)	1
CA100-NM-RASMAM-12	N male	Right angle SMA male	12	LMR100 (equivalent)	1
CA100-NM-RSMAM-12	N male	Reverse polarity SMA male	12	LMR100 (equivalent)	1
CA100-NM-RTNCM-12	N male	Reverse polarity TNC male	12	LMR100 (equivalent)	1
CA100-RPSMAM-RASMAM-12	Reverse polarity SMA male	Right angle SMA male	12	LMR100 (equivalent)	1
CA100-RPTNCF-NC-6	Reverse polarity TNC female bulkhe	ad No connector	6	LMR100 (equivalent)	0.5
CA100-RPTNCM-RASMAM-12	Reverse polarity TNC male	Right angle SMA male	12	LMR100 (equivalent)	1
CA100-TNCF-NC-6	TNC female bulkhead	No connector	6	LMR100 (equivalent)	0.5
CA178-NFB-UFL-12	N female bulkhead	U.FL	12	RG178 hi freq	2
CA178-NFB-UFL-8	N female bulkhead	U.FL	8	RG178 hi freq	1.5
CA178-NM-UFL-12	N male	U.FL	12	RG178 hi freq	2
CA178-NM-UFL-8	N male	U.FL	8	RG178 hi freq	1.5
CA178-RTNCB-MMCX-4	Reverse polarity TNC bulkhead	(black)	4	RG178 hi freq	0.8
CA178-RTNCB-MMCX-6 MMCX Reverse polarity TNC bulkhead		ulkhead	6	RG178 hi freq	1
CA178-RTNCB-UFL-6	(black) MMCX Reverse polarity TNC		6	RG178 hi freq	1
CA400-NM-NM-48	N male bulkhead (black) U.FL	N male	48	LMR400 (equivalent)	0.8
CA58-NM-MCX-197	N male	MCX	197	RG58/u (white)	5
CA58-SMA-MCX-96	Right angle SMA male	MCX	96	RG58/u (white)	2.5
CA58-SMA-NF-96	Right angle SMA male	N female bulkhead	96	RG58/u (white)	2.5
CA58-SMA-RSMA-96	Right angle SMA male	Reverse polarity SMA male	96	RG58/u (white)	2.5
CA58-SMA-RTNC-96	Right angle SMA male	Reverse polarity TNC male	96	RG58/u (white)	2.5
CA58-SMA-SMAF-96	Right angle SMA male	SMA female bulkhead	96	RG58/u (white)	2.5

Americas: +1.847 839.6907

IAS-Americas East Sales@laird tech.com

Europe: +44.1628.858941 IAS-EUSales@lairdtech.com Asia: +86.21.5855.0827.127 IAS-AsiaSales@lairdtech.com

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for intential or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. @ Copyright 2015 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird, Logo, and other marks are trademarks or registered trademarks of Laird Inc. and filialet company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Cable Assemblies category:

Click to view products by Laird Connectivity manufacturer:

Other Similar products are found below:

573/2 73-6311-6 73-6353-3 73-6364-6 MDB1-9SH001 MDM-15PH003L-K139 MDM-21PH003L-K139 MIKQ6-7SH076 R288940005
RF174-01RP1-03RP1-0110 RMTB1-6PHY0102 145111-05-12.00 1661-C-24 2192 CA-628485-A43 24P104C24J1-012 24P104C24P1-006
24P104C24P1-018 24P203C24P2-006 24P204C24J1-003 172-2150-EX 1800920920914PJ FCB-3030-ALT 21117-046 21117-050 PCX-24-50 24P103C24P2-003 25P203C25P2-003 R284008001 R285426000 R288940003 R288940008 RF174-03RP1-01BR1-0200 RF179-74BJ3-77RP1-0305 RMTB1-15PHY0102 RMTB1-8PHY0102 4814-BB-24 500-181-R-ACC MIKQ6-7SH023 5260-72 314-120 JR4N1-CL1-6F
JR4R3-CL1-4F JT2N1-CL1-1F JT2T1-CL1-6F 4814-K-48 RN-UFL-SMA6 100E151JW3600X CCNTN2-MM-LL335-26 73-6310-50