

## Smart Technology. Delivered.



## **Two-Way Radio Antenna**



Laird's in-building wireless antennas are particularly applicable in environments where aesthetics and wide angle coverage are necessary for successful wireless deployment. Their surprisingly small size allow the antennas to be hidden almost anywhere, providing an invisible solution for most applications.

External antennas are weather resistant and waterproof high-gain anntenas that provide an excellent choice

for outdoor and indoor installation, and can be mounted on the outside of a housing.

Our antennas products are designed for maximum efficiency and are customizable and scalable to meet your frequency and application requirements. Contact Laird today for your complete application solutions!

## **FEATURES**

- Injection molded ¼ wave helical antenna
- · High durability, high efficiency
- · Textured finish with strain-relief base
- Available in various standard connectors

PARAMETER	SPECIFICATION
Frequency Range	UHF
Nominal Impedance	50 ohms
VSWR	1.5:1 max at resonance
Polarization	Vertical
Temperature Range	-40°C to +85°C
Drop Test	1M

FREQUENCIES AND CONNECTORS			
PART#	FREQUENCY BAND	CONNECTORS	AVERAGE LENGTH
EXD400	400-420 MHz	BN, BNX, KR, MD, MX, MXI, SF, SFU, SM, SMI, SMV, TN & TNX	3.4" - 3.8"
EXD410		SMV	
EXD420	420-450 MHz	BN, BNX, KR, MD, MX, SF, SFU, SM, SMV, TN & TNX	3.3" – 3.59"
EXD450	450-470 MHz	BN, BNX, KR, MD, MX, MXI, SF, SM, SMI, SMV, TN & TNX	2.95" – 3.88"
EXD470	470-512 MHz	BN, BNX, KR, MD, MX, MXI, SF, SFU, SM, SMI, SMV, TN & TNX	2.8" – 3.6"

The EXD model antenna is available in the above frequencies and connectors. Order by antenna model, frequency and

For example: EXD450MX. Length of each antenna will vary according to the connector chosen. Specifications subject to change without notice.

Americas: +1.847 839.6925 IAS-AmericasSales@lairdtech.com

Europe: +44.1628.858941 IAS-EUSales@lairdtech.com

Asia:

IAS-AsiaSales@lairdtech.com

Middle East & Affrica: +44.1628.858941

IAS-MEASales@lairdtech.com

www.lairdtech.com

ANT-DS-EXD 1216

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies hakes no warranties as to the fitness, merchantability or any Laird Technologies products are sold pursuant to the Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies. Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2016 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trade marks or registered trade marks of Laird Technologies. Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antennas category:

Click to view products by Laird Connectivity manufacturer:

Other Similar products are found below:

GAN30084EU 930-033-R GW17.07.0250E 1513563-1 EXE902SM APAMPG-117 MAF94383 W3908B0100 W6102B0100 YE572113-30RSMM 108-00014-50 66089-2406 SPDA17RP918 A09-F8NF-M A09-F5NF-M RGFRA1903041A1T W3593B0100 W3921B0100 SIMNA-868 SIMNA-915 SIMNA-433 W1044 W1049B090 A75-001 WTL2449CQ1-FRSMM CPL9C EXB148BN 0600-00060 TRA9020S3PBN-001 Y4503 GD5W-28P-NF MA9-7N GD53-25 GD5W-21P-NF C37 MAF94051 MA9-5N EXD420PL B1322NR QWFTB120 MAF94271 MAF94300 GPSMB301 FG4403 AO-AGSM-OM54 5200232 MIKROE-2349 WCM.01.0111 MIKROE-2393 MIKROE-2352