



Laird's tri-band RD2458-5 series offers high-gain (3dBi/2.4 GHz & 5 dBi/5GHz) omnidirectional performance. These antennas are designed for indoor use and are both rugged and reliable. The heavy duty knuckle designed into the antenna gives the flexibility for angular adjustments at 0°, 45°, and 90°.

The antenna features a 360° horizontal transmission pattern and a 90° vertical transmission pattern. These antennas offer a choice of connector options for maximum design flexibility (SMA, RPSMA, and RPTNC).

## FEATURES AND BENEFITS

- Tri-band operation 2.4 GHz, 5.3 GHz, and 5.8 GHz
- Knuckle detents 0°, 45°, and 90° (N-male not applicable)
- Extends the range of wireless access points and wireless bridges
- SMA, RPSMA, RPTNC, and N-male connector versions available

ELECTRICAL SPECIFICATIONS				
Part Number		RD2458-5		
Operating Frequency (MHz)	2400	5150	5400	5725
Gain (dBi)	3	5	5	5
VSWR	1.5:1			
Nominal Impedance (Ohms)	50			
Max Power - Ambient 25°C (W)	10			
Operating Temperature – °C (°F)		-10 to +70 (+14 to +158)		

MECHANICAL SPECIFICATIONS			
Dimensions (Height x Diameter) – mm (in.)	155 x 12.7 (6.1 x 0.5)		
Weight – g (oz.)	22.7 (0.8)		


### CONFIGURATION

PART NUMBER	CONNECTOR	
RD2458-5-SMA	SMA male connector	
RD2458-5-RSMA	RPSMA male connector	
RD2458-5-RTNC	RPTNC male connector	




## **RADIATION PATTERNS**


#### 2450 MHz



## 5150 MHz



## 5750 MHz



Americas: +1.847 839.6925 IAS-Americas Sales@laird tech.com**Europe:** +44.1628.858941 IAS-EUSales@lairdtech.com Asia: IAS-AsiaSales@lairdtech.com Middle East and Africa: +44.1628.858941

IAS-MEAUSales@lairdtech.com www.lairdtech.com

✓ RoHS

Laird warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations Laird will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the Laird product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.



Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request.

© Copyright 2018 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trademarks or registered trademarks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antennas category:

Click to view products by Laird Connectivity manufacturer:

Other Similar products are found below:

GAN30084EU 930-033-R GW17.07.0250E 1513563-1 EXE902SM APAMPG-117 MAF94383 W3908B0100 W6102B0100 YE572113-30RSMM 108-00014-50 66089-2406 SPDA17RP918 A09-F8NF-M A09-F5NF-M RGFRA1903041A1T W3593B0100 W3921B0100 SIMNA-868 SIMNA-915 SIMNA-433 W1044 W1049B090 A75-001 WTL2449CQ1-FRSMM CPL9C EXB148BN 0600-00060 TRA9020S3PBN-001 Y4503 GD5W-28P-NF MA9-7N GD53-25 GD5W-21P-NF C37 MAF94051 MA9-5N EXD420PL B1322NR QWFTB120 MAF94271 MAF94300 GPSMB301 FG4403 AO-AGSM-OM54 5200232 MIKROE-2349 WCM.01.0111 MIKROE-2393 MIKROE-2352