

S2403BP

Omnidirectional Antenna





SPECIAL PURPOSE OMNIDIRECTIONAL ANTENNAS

Laird Technologies' ISM band data transmission omni-directional antenna, the S2403BP antenna provides for transmission and reception of linearly polarized signals in the 2400 - 2500 MHz frequency band. The antenna consists of a series fed, two element dipole array providing a nominal 3 dBd gain with a nominal 360 by 30 degrees half power beamwidth.


The antenna is an excellent choice for superior RF coverage in warehouses, auditoriums, shopping malls, industrial complexes and more. Standard models of the antennas are white in color. Installation options include a pole mount or suspended ceiling mount.

FEATURES

- Polycarbonate enclosures
- Available with ceiling mounts
- Plated copper laninated radiator
- Weatherproof designs with UltraLink® pigtail
- Broad band performance
- DC grounded

MARKETS

WiMAX



PARAMETER	SPECIFICATIONS				
Antenna Part Number	S5703BP5SMF	S5703BH7SMF	S2400BH12NF	S2403BP12NF	S2403BH12NF
Frequency Range (MHz)	5725 - 5875	5725 - 5875	2400 - 2500	2400 - 2500	2400 - 2500
Gain (dBi)	5	5	2	5.15	5.15
3 dB Beamwidth E-Plane	38°	38°	38°	38°	75°
Height In (cm)	7 (17.8)	7 (17.8)	11.5 (29.2)	11.5 (29.2)	9 (22.9)
Weight lb (kg)	0.3 (0.14)	0.2 (0.1)	0.31 (0.14)	0.41 (0.18)	0.29 (0.13)
W/sur area ft² (m²)	.06 (006)	0.006 (0.006)	0.08 (0.007)	0.08 (0.007)	0.122 (0.0011)
W/survival mph (kph)	125 (200)	125 (200)	125 (200)	125 (200)	125 (200)
Enclosure	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate
Power (watts)	20	20	50	50	50
Mount Style	Tube end	Ceiling	Ceiling	Tube end	Ceiling
Mast Diameter in (cm)	2 (5.1)	N/A	N/A	2 (5.1)	N/A

global solutions: local support ™

Americas: +1.847 839.6907 IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12 IAS-EUSales@lairdtech.com Asia: +1.65.6.243.8022 IAS-AsiaSales@lairdtech.com

ANT-DS-S2403BP 0212

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end use; since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies and products are sold pursuant to the Laird Technologies Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2012 Laird Technologies, Inc. and other marks are trade marks or registered trade marks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antennas category:

Click to view products by Laird Connectivity manufacturer:

Other Similar products are found below:

GAN30084EU 930-033-R GW17.07.0250E 1513563-1 EXE902SM APAMPG-117 MAF94383 W3908B0100 W6102B0100 YE572113-30RSMM 108-00014-50 66089-2406 SPDA17RP918 A09-F8NF-M A09-F5NF-M RGFRA1903041A1T W3593B0100 W3921B0100 SIMNA-868 SIMNA-915 SIMNA-433 W1044 W1049B090 A75-001 WTL2449CQ1-FRSMM CPL9C EXB148BN 0600-00060 TRA9020S3PBN-001 Y4503 GD5W-28P-NF MA9-7N GD53-25 GD5W-21P-NF C37 MAF94051 MA9-5N EXD420PL B1322NR QWFTB120 MAF94271 MAF94300 GPSMB301 FG4403 AO-AGSM-OM54 5200232 MIKROE-2349 WCM.01.0111 MIKROE-2393 MIKROE-2352