

Broadband Wireless Antenna S3307BPNF

Innovative **Technology** for a **Connected** World



3.3-3.8 GHz VERTICAL POLARIZATION 9 dBi OMNI-DIRECTIONAL ANTENNA

The Laird Technologies S3307BPNF provides omni-directional pattern coverage over the entire 3.3-3.8 GHz frequency. At only 28.2 inches long by 1.75 inches in diameter and weighing in at 1.15 lbs, the antenna can be conveniently mounted to any available mounting platform without causing concern about excessive wind loading or axial torque. The antenna comes complete with mast mounting hardware. The antenna is enclosed in a UV stable radome enclosure that will provide years of use without degradation to either its mechanical properties or aesthetics.

The antenna comes with a heavy-duty, fixed N female connector at the base allowing for the most convenient site integration and weather sealing options. The S3307BPNF is a perfect choice for broadband wireless access providers initially installing omnidirectional sites as they begin the process of building out their systems. Because of the antennas wide bandwidth characteristics, it can be inventoried for eventual use by any carrier using any portion of the 3.3-3.8 GHz frequency band.


FEATURES FROHS

ANT-DS-S3307BPNF 0611

- 9.0 dBi gain
- 3.3-3.8 GHz full band coverage
- Weather proof UV stabile radome
- Mast mounting hardware included
- Slim diminutive profile 28.2 in x 1.75 in

- Broadband wireless access service provider
- Campus, healthcare or transportation terminals
- Stadium, industrial plants, and processing stations
- Low to medium density, tower mounted rural locations

| PARAMETER | SPECIFICATIONS |
|----------------------------|--|
| Frequency range | 3.3 - 3.8 GHz |
| Gain @ 2.5 GHz | 9 dBi |
| Maximum VSWR | 2.0:1 |
| 3 dB beamwidth - Elevation | 8° |
| Beamwidth - Azimuth | Omni-directional |
| Polarization | Linear vertical |
| Lightning protection | DC-grounded |
| Maximum input power | 10 W |
| Mechanical size | 28.2 in x 1.7 in |
| Antenna Weight | 1.15 lbs |
| Wind survival rating | Operational 100 mph / survival 136 mph |
| Antenna connection | Type N female |
| Radome | UV polycarbonate |
| Mount style | Mast mount |
| Mounting hardware | Included |
| Temperature | -40°C to +70°C |



E-plane

global solutions: local support ™

Americas: +1.847 839.6907 IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12 IAS-EUSales@lairdtech.com Asia: +1.65.6.243.8022 IAS-AsiaSales@lairdtech.com

www.lairdtech.com

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies makes no reproducts for any specific or general uses. Laird Echnologies, the lair be lair before any lair and Endonologies. Temps and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2011 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies, the Laird Technologies, and there marks are trade marks or Tecistered marks or Te

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antennas category:

Click to view products by Laird Connectivity manufacturer:

Other Similar products are found below:

GAN30084EU 930-033-R GW17.07.0250E 1513563-1 EXE902SM APAMPG-117 MAF94383 W3908B0100 W6102B0100 YE572113-30RSMM 108-00014-50 66089-2406 SPDA17RP918 A09-F8NF-M A09-F5NF-M RGFRA1903041A1T W3593B0100 W3921B0100 SIMNA-868 SIMNA-915 SIMNA-433 W1044 W1049B090 A75-001 WTL2449CQ1-FRSMM CPL9C EXB148BN 0600-00060 TRA9020S3PBN-001 Y4503 GD5W-28P-NF MA9-7N GD53-25 GD5W-21P-NF C37 MAF94051 MA9-5N EXD420PL B1322NR QWFTB120 MAF94271 MAF94300 GPSMB301 FG4403 AO-AGSM-OM54 5200232 MIKROE-2349 WCM.01.0111 MIKROE-2393 MIKROE-2352