

Smart Technology. Delivered.

VERTICALLY POLARIZED SECTOR ANTENNAS

S4901xx

4900-5850 MHZ VERTICALLY POLARIZED SECTOR ANTENNA

The vertically polarized ultra wide-band 5GHz sector antenna systems offered by Laird Technologies are constructed of UV stable ASA plastic radomes and galvanized steel brackets with stainless steel hardware for long service life in the most demanding conditions. The ultra wide-band operation allows a single antenna to cover a wide frequency range thereby allowing the operator maximum flexibility in his network. The antennas are DC Grounded for lightning/ESD protection. The heavy duty bracket system adjusts for up to 15° of downtilt.


FEATURES ✓ RoHS

- High-gain 16 and 17dBi in a small form factor
- Low wind loading: 160MPH survivability
- Vertically polarized, ultra wide-band operation
- Type N female integrated connector
- Galvanized steel tilt bracket for up to 3.5" dia pole


MARKETS

- 5.8GHz U-NII band applications
- Point-to-multi-point systems
- Base station antennas
- 802.11a applications
- · Pubic safety

PARAMETER	S4901790PNF	S49016120PNF	
Frequency range	4900 - 5850 MHz	4900 - 5850 MHz	
VSWR	1.8:1	1.8:1	
Impedance	50 ohm	50 ohm	
Input power	10W	10W	
Pole diameter (OD)	1.5"- 3.5" (38-89mm)	1.5"- 3.5" (38-89mm)	
Operating temperature	-40 - +70°C	-40 - +70°C	
Gain	17 dBi	16 dBi	
Horizontal beamwidth	90°	120°	
Vertical beamwidth	6°	6°	
Polarization	Vertical	Vertical	
Front-to-back	>25 dB	>25 dB	
Cross polarization	>15 dB	>15 dB	
Mechanical downtilt	15°	15°	
Weight	2 lbs (1.3 kg)	2 lbs (1.3 kg)	
Dimensions (L x W x H))	24.6" x 2.7" x 1.7" (625 x 69 x 43 mm)	24.6" x 2.7" x 1.7" (625 x 69 x 43 mm)	











S4901790PNF 5470MHz

S49016120PNF 5470MHz

WIND LOADING

MODEL	SQ. IN	100 MPH	125 MPH
S4901xx	66.4	16.6 lb	24.9 lb





SYSTEM ORDERING

F

S4901790PNF 4900-5850MHz 90deg 17dBi VPOL sector antenna S49016120PN 4900-5850MHz 120deg 16dBi VPOL sector antenna

S4901790PNF 5850MHz

S49016120PNF 5850MHz





ANT-DS-S4901 1115

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2009 Laird Technologies, inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trade marks of trade marks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antennas category:

Click to view products by Laird Connectivity manufacturer:

Other Similar products are found below:

GAN30084EU 930-033-R GW17.07.0250E 1513563-1 EXE902SM APAMPG-117 MAF94383 W3908B0100 W6102B0100 YE572113-30RSMM 108-00014-50 66089-2406 SPDA17RP918 A09-F8NF-M A09-F5NF-M RGFRA1903041A1T W3593B0100 W3921B0100 SIMNA-868 SIMNA-915 SIMNA-433 W1044 W1049B090 A75-001 WTL2449CQ1-FRSMM CPL9C EXB148BN 0600-00060 TRA9020S3PBN-001 Y4503 GD5W-28P-NF MA9-7N GD53-25 GD5W-21P-NF C37 MAF94051 MA9-5N EXD420PL B1322NR QWFTB120 MAF94271 MAF94300 GPSMB301 FG4403 AO-AGSM-OM54 5200232 MIKROE-2349 WCM.01.0111 MIKROE-2393 MIKROE-2352