

# **Vertically Polarized Sector Antennas**

Smart Technology. Delivered.™



#### 2300-2700 MHZ VERTICALLY POLARIZED BASE STATION SECTOR ANTENNA

The 60deg, 90deg and 120deg vertically polarized base station sector antenna systems offered by Laird Technologies are constructed of UV stable fiber glass radomes. The 45deg sector has a UV Stable ASA plastic radome. The radome construction gives long service life under the most demanding conditions. The antennas are constructed using corrosion resistant metal elements and a unique air dielectric system which are more stable than PCB based antenna systems because they don't absorb moisture, which can degrade the performance of PCB based antenna systems. The sectors come with a stainless steel scissor bracket mounting system for ease of installation and alignment.

### FEATURES RoHS

- · Vertically polarized wide band performance
- 45, 60, 90, and 120 deg models with gains from 16dBi to 20dBi
- Type N female integrated connector
- Extremely rugged for long service life in extreme environments
- Weatherproof

#### **MARKETS**

- WiMAX applications
- · Base station antennas
- 802.11b and 802.11g wireless systems
- Point to multi-point systems
- Broadband wireless access
- MMDS applications


PARAMETER	SA24-45-20-WB	SA24-60-17-WB	SA24-90-17-WB	SA24-120-16-WB
Frequency range	2300 - 2700 MHz	2300 - 2700 MHz	2300 - 2700 MHz	2300 - 2700 MHz
VSWR	1.5:1	1.5:1	1.5:1	1.5:1
Impedance	50 ohm	50 ohm	50 ohm	50 ohm
Input power	50W	50W	50W	50W
Pole diameter (OD)	1"- 2" (25-50mm)	1"- 2" (25-50mm)	1"- 2" (25-50mm)	1"- 2" (25-50mm)
Temperature	-40°C to +70°C	-40°C to +70°C	-40°C to +70°C	-40°C to +70°C
Gain	20 dBi	17 dBi	17 dBi	16 dBi
Horizontal beamwidth	45°	60°	90°	120°
Vertical beamwidth	7°	8°	7°	9°
Front-to-back	25 dB	25 dB	20 dB	21 dB
Mechanical downtilt	30°	30°	30°	30°
Weight	8.4 lbs (3.8 kg)	6.6 lbs (3 kg)	6.6 lbs (3 kg)	6.6 lbs (3 kg)
Dimensions (L x W x H)	34" x 7" x 3.5" (864 x 178 x 89mm)	33.5" x 6.5" x 2.5" (851 x 165 x 64mm)	33.5" x 6.5" x 2.5" (851 x 165 x 64mm)	33.5" x 6.5" x 2.5" (851 x 165 x 64mm)

#### WIND LOADING

MODEL	SQ. IN	100 MPH	125 MPH	100 MPH 1/2" RADIAL ICE
SA24 WB	247	61.8 lb	96.5 lb	62 lb

#### SYSTEM ORDERING

SA24-45-20-WB	45deg	20dBi	2300-2700MHz	VPOL	sector	antenna
SA24-60-17-WB	60deg	17dBi	2300-2700MHz	VPOL	sector	antenna
SA24-90-17-WB	90deg	17dBi	2300-2700MHz	VPOL	sector	antenna
SA24-120-16-WB	120deg 16dBi 2300-2700MHz VPOL sector antenna					



Typical azimuth and elevation pattern SA24-90-17-WB



Americas: +1.847 839.6925 IAS-AmericasSales@lairdtech.com Europe: +44.1628.858941 IAS-EUSales@lairdtech.com

Asia:IAS-AsiaSales@lairdtech.com Middle East & Affrica: +44.1628.858941 IAS-MEASales@lairdtech.com

www.lairdtech.com

#### ANT-DS-SA24WB 0716

Any information furnished by Laird and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general user. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Technologies' Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2016 Laird. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies, and other marks are trade marks or registered trade marks of Laird or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antennas category:

Click to view products by Laird Connectivity manufacturer:

Other Similar products are found below:

GAN30084EU 930-033-R GW17.07.0250E 1513563-1 EXE902SM APAMPG-117 MAF94383 W3908B0100 W6102B0100 YE572113-30RSMM 108-00014-50 66089-2406 SPDA17RP918 A09-F8NF-M A09-F5NF-M RGFRA1903041A1T W3593B0100 W3921B0100 SIMNA-868 SIMNA-915 SIMNA-433 W1044 W1049B090 A75-001 WTL2449CQ1-FRSMM CPL9C EXB148BN 0600-00060 TRA9020S3PBN-001 Y4503 GD5W-28P-NF MA9-7N GD53-25 GD5W-21P-NF C37 MAF94051 MA9-5N EXD420PL B1322NR QWFTB120 MAF94271 MAF94300 GPSMB301 FG4403 AO-AGSM-OM54 5200232 MIKROE-2349 WCM.01.0111 MIKROE-2393 MIKROE-2352