



Laird Technologies' unique patented Phantom[®] is a tough low-profile antenna for outdoor or indoor applications. Measuring only 2.3 inches exposed tall, the Phantom covers 4.9 GHz - 6.0 GHz. The antenna model's revolutionary design features field diversity. The industry standard NMO mounting socket mates with all Laird Technologies' magnetic, trunk lid, and hole mounts. A threaded permanent stud Type N connector mount model is also available for vandal-resistant mounting on brackets, panels, ceilings, or any other kind of housing.

The Phantom[®] patented technology is beneficial when high performance, extreme ruggedness, and low profile are required.

FEATURES AND BENEFITS

- Mechanically robust for both Indoor/Outdoor applications
- Phantom® outperforms a 3-dB whip in many applications
- U.S. Patent numbers 5,977,931 6,292,156 and 7,209,096

ELECTRICAL SPECIFICATIONS	
VSWR – Avg	1.25:1
Gain – Typ (dBi)	5.0
Gain Horizon 30° - Max (dBi)	5.6
Nominal Impedance (Ohms)	50
Maximum Peak Power - Ambient 25°C (W)	100
Polarization	Vertical
Pattern	Omnidirectional
Half-power Beamwidth (elevation° x azimuth °)	30 x 360

MECHANICAL SPECIFICATIONS

Dimensions – diameter x height – mm (inches)	NMO: 36.53 (1.438') x 58.4 (2.3) Permanent Mount: 36.53 (1.438) x 80.3 (3.16) , Exposed: 36.53 (1.438')x 58.4 (2.3)
Weight – g (lbs.)	0.078 (0.173)
Radome Material	Lexan
Color	Black or white
Mounting Information	NMO socket (NMO mount is sold separately) or
	Type N Female – Permanent Mount (hardware included)
	Note: P-Mount requires a 5/8" hole for mounting.
Noise Suppressor	BlackHawk NS 1535 1-35 volt, 15 amp

CONFIGURATION


PART NUMBER	DESCRIPTION
TRA58003	4.9 – 6.0 GHz, 5 dBi, White, NMO
TRAB58003	4.9 – 6.0 GHz, 5 dBi, Black, NMO
TRA58003P	4.9 – 6.0 GHz, 5 dBi, White, N Female
TRAB58003P	4.9 – 6.0 GHz, 5 dBi, Black, N Female


Add B to the model number for black radome (example: TRAB58003)


Add P to the model number for the permanent mount option (example: TRA58003P)

Customized models without the logo are also available.

RADIATION PATTERNS









sales@lairdconnect.com support@lairdconnect.com www.lairdconnect.com Laird warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations Laird will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the Laird product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability or suitability or any Laird materials products for any specific or general uses. Laird hall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request.

© Copyright 2019 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trademarks or registered trademarks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antennas category:

Click to view products by Laird Connectivity manufacturer:

Other Similar products are found below :

 GAN30084EU
 930-033-R
 GW17.07.0250E
 1513563-1
 EXE902SM
 APAMPG-117
 MAF94383
 W3908B0100
 W6102B0100
 YE572113

 30RSMM
 108-00014-50
 66089-2406
 SPDA17RP918
 A09-F8NF-M
 A09-F5NF-M
 RGFRA1903041A1T
 W3593B0100
 W3921B0100

 SIMNA-868
 SIMNA-915
 SIMNA-433
 W1044
 W1049B090
 A75-001
 WTL2449CQ1-FRSMM
 CPL9C
 EXB148BN
 0600-00060

 TRA9020S3PBN-001
 Y4503
 GD5W-28P-NF
 MA9-7N
 GD53-25
 GD5W-21P-NF
 C37
 MAF94051
 MA9-5N
 EXD420PL
 B1322NR

 QWFTB120
 MAF94271
 MAF94300
 GPSMB301
 FG4403
 A0-AGSM-OM54
 5200232
 MIKROE-2349
 WCM.01.0111
 MIKROE-2393

 MIKROE-2352
 MIKROE-2352
 MIKROE-2352
 MIKROE-2352
 MIKROE-2352
 MIKROE-2352
 MIKROE-2352