

Smart Technology. Delivered.



800 MHz-5.8GHz Antennas



PHANTOM® ANTENNA IS IDEAL FOR CELL, GSM, PCE, WIFI, 802.11 AND BLUETOOTH WIRELESS APPLICATIONS

Laird's unique patented Phantom® is a tough low-profile antenna for outdoor or indoor applications. Measuring only 2.7" tall, the Phantom 800 MHz to 5.8 GHz antenna models' revolutionary design features field diversity with both vertical and horizontal polarization components. This gives the antenna diversity, frequency agility, low visibility, wide bandwidth and a low angle radiation pattern that is superior to traditional gain antennas in most applications. The industry standard NMO mounting socket mates with all Laird Technolgies' magnetic, trunk lid, and hole mounts. A threaded permanent stud mount model is also available for vandal resistant mounting on brackets, panels, ceilings or any other kind of housing.

The Phantom® patented technology is beneficial when high performance is desired and extreme ruggedness and low profile is required.


FEATURES **✓** RoHS

- True Field Diversity design ensures uninterrupted transmissions in urban canyons and rural drop off areas
- Phantom® outperforms a 3dB whip in many applications
- U.S. Patent Nos. 5,977,931 6,292,156 and 7,209,096

MARKETS

- Cell
- GSM and PCS
- WiFi
- 802.11
- Bluetooth wireless applications

ANTENNA PATTERNS



Americas: +1.847 839.6925 IAS-AmericasSales@lairdtech.com Europe: +44.1628.858941 IAS-EUSales@lairdtech.com

Asia: IAS-AsiaSales@lairdtech.com Middle East & Affrica: +44.1628.858941 IAS-MEASales@lairdtech.com www.lairdtech.com



Smart Technology. Delivered.



800 MHz-5.8GHz Antennas

SPECIFICATIONS

ELECTRICAL	
VSWR	<2.1
Nominal Gain	3 dB- M.E.G.
Maximum Power	100 W
Nominal Impedance	50 Ω
Polarization	Vertical & Horizontal
Pattern	Omnidirectional
Half-Power Beamwidth (Elevation° x Azimuth°)	130° x 360
Coaxial Cable Length & Type	None
Terminations	NMO Socket or, type N-Female

MECHANICAL	
Color	Black or White
Height (initially)	2 ¾"
Diameter	1.438"
Weight	0.173 lbs
Material	ABS
Mounting Information	NMO (PN: MB8, MAB8) Sold Separately
Noise Surpressor	BlackHawk NS1535 1-35 VOLT, 15 Amp Noise Suppessor (Sold Separately)

Permanent Mounting Option:

Please order by antenna model and insert letter "P" to indicate permanent mounting option (TRA8063P).

MODEL AND ORDERING INFORMATION

MODEL	DESCRIPTION
TRA8063	806-870 MHz 3 dB-MEG Phantom® ¾ NMO, White Radome
TRA8213	821-896 MHz 3 dB-MEG Phantom® ¾ NMO, White Radome
TRA8903	890-960 MHz 3 dB-MEG Phantom® ¾ NMO, White Radome
TRA9023	902-928 MHz 3 dB-MEG Phantom® ¾ NMO, White Radome
TRA18503	1.85 - 1.99 GHz 3dB-MEG Phantom® ¾ NMO, White Radome
TRA24003	2.4 – 2.5 GHz 3 dB-MEG Phantom® ¾ NMO, White Radome
TRA58003	4.9- 6.0 GHz 3 dB-MEG Phantom® ¾ NMO, White Radome
TRADCAGP	G- Drop ceiling antenna adaptor for P-mount Phantom w/ 6"x6"x0.016" ground plane
Sealtube3	Heat shrink tubing 3″x1″DIA install (use for jaw protector on installation wrench)

Add "B" to model number for black radome. Example: TRAB8063 Add "P" to model number for Permanent Mount. Example: TRA8063P

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antennas category:

Click to view products by Laird Connectivity manufacturer:

Other Similar products are found below:

CCT FM1 ABFT AD-NM-SMAF 001-0021 CTC110 MAF94149 EXE902SF MMCX-SMA-100 PDQ24496-91NF GAN30084EU 930-033-R A08-HABUF-P5I AAF95035 DG-ANT-20DP-BG-B APAMPGJ-141 1513563-1 OF86315-FNF OP24516DS-91NM A09-HASM-7 EXE902MD EXE902SM SPDA17806/2170LAR APAMPG-117 GPS1575SP26-004 GPS15MGSMA CMD69273P-30NF CMQ69273-30NF RD2458-5-OTDR-NM RD2458-5-RSMA TRAB24/49003 W4120ER5000 W6102B0100 YE572113-30RSMM 108-00014-50 SPDA17RP918 OP24516SX-91NM OP24516SX-91RSMM CMQ69273P-30NF CMS69273-30NF CMS69273P-30NF TRAB24003N TRAB24003NP TRAB8213NP TRAB8903 A09-Y8NF A09-Y11NF A09-HSM-7 A09-F8NF-M A09-F5NF-M