TRA(B)T1500



Phantom Antenna Frequency Tunable 150-168 MHz (field tunable starting at 150 MHz)



Our patented Phantom® is a rugged antenna for outdoor or indoor applications. The Phantom® revolutionary design features field diversity with both vertical and horizontal polarization components. This gives the antenna diversity, frequency agility, low visibility, wide bandwidth and a low angle radiation pattern that is superior to traditional gain antennas in most applications.

The industry standard NMO mounting socket mates with all Antenex® magnetic, trunk lid, and hole mounts. The Phantom® patented technology is beneficial when high performance is desired and ruggedness and low profile is required.

FEATURES AND BENEFITS

- Easy installation with optional NMO mounts
- UV-treated radome resists sun damage

APPLICATIONS

- FirstNet/Public Safety
- Transportation
- Industrial and commercial communications

| Model Name | TRA(B)T1500 |
|-------------------------------|---|
| Operating Frequency (MHz) | 150-168 MHz (field tunable starting at 150 MHz) |
| Frequency Bandwidth (MHz) | 2.0 |
| /SWR (dBi) | <2:1 |
| Return Loss (dB) – minimum | -10 |
| Gain (dBi) | Unity |
| Elevation = 45° | -5 |
| Elevation = 90° | -11 |
| Iominal Impedance (Ohms) | 50 |
| Max Power - Ambient 25°C (W) | 60 |
| Polarization | Vertical |
| Pattern | Omnidirectional |
| /ertical Plane 3 dB Beamwidth | 120° |
| Funing | Tunable coil with tuning key provided |

| MECHANICAL SPECIFICATIONS | | |
|----------------------------------|-------------------------------|--|
| Dimensions – W x H – mm (inches) | xx x xx (3¼ x 3½) | |
| Weight – kg (lbs.) | Xx (0.25) | |
| Cable Type | None | |
| Finish | ABS | |
| Color | White or Black | |
| Mounting | 4' x 4' Metallic Ground Plane | |

| ENVIRONMENTAL SPECIFICATIONS | | |
|---|------------------------------|--|
| Operating Environment (Indoor or Outdoor) | Indoor and Outdoor | |
| Operating Temperature – °C (°F) | -30 to +70°C (-22 to +158°F) | |
| Storage Temperature – °C (°F) | -30 to +70°C (-22 to +158°F) | |
| Lightning Protection | AC Ground | |


CONFIGURATION

| PART NUMBER | COLOR | CONNECTOR |
|-------------|-------|-----------|
| TRAT1500 | White | NMO |
| TRA(B)T1500 | Black | NMO |




RADIATION PATTERNS

Representative Azimuth Field Pattern



Elevation Pattern (Z, Y, or H-plane)





Laird warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations Laird will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the Laird product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.



Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request.

© Copyright 2019 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trademarks or registered trademarks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.

sales@lairdconnect.com support@lairdconnect.com www.lairdconnect.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antennas category:

Click to view products by Laird Connectivity manufacturer:

Other Similar products are found below:

GAN30084EU 930-033-R GW17.07.0250E 1513563-1 EXE902SM APAMPG-117 MAF94383 W3908B0100 W6102B0100 YE572113-30RSMM 108-00014-50 66089-2406 SPDA17RP918 A09-F8NF-M A09-F5NF-M RGFRA1903041A1T W3593B0100 W3921B0100 SIMNA-868 SIMNA-915 SIMNA-433 W1044 W1049B090 A75-001 WTL2449CQ1-FRSMM CPL9C EXB148BN 0600-00060 TRA9020S3PBN-001 Y4503 GD5W-28P-NF MA9-7N GD53-25 GD5W-21P-NF C37 MAF94051 MA9-5N EXD420PL B1322NR QWFTB120 MAF94271 MAF94300 GPSMB301 FG4403 AO-AGSM-OM54 5200232 MIKROE-2349 WCM.01.0111 MIKROE-2393 MIKROE-2352