

50 Series Enterprise Modules Dual-Band 802.11n Wi-Fi + Bluetooth 4.0



FOR THE BEST IN ENTERPRISE WIRELESS, LAIRD HAS YOU COVERED



Powered by the Qualcomm Atheros QCA6004 and the Cambridge Silicon Radio CSR8811, Laird's 50 Series Wi-Fi® + Bluetooth® modules achieve the best possible connectivity in any RF environment. With industry-leading software, Linux and Android support, and a wide range of form factors, Laird's 50 Series is a flexible option for your enterprise wireless needs. The security and robustness inherited from Laird's expertise in its 40 and 45 Series modules means the most reliable wireless in crucial, even life-critical applications, such as medical and industrial.

- New Wireless Capabilities: Advanced 802.11a/b/g/n, 2x2 MIMO, Advanced Power Save, Enhanced BT/Wi-Fi Coexistence, Fast Roam
- New Form Factors: Extremely small 15mm x 15mm SiP module, M.2 module, and more
- Bluetooth 4.0: Enables Classic Bluetooth and Low Energy mode.
- Complete RF Pathway: Onboard baluns, mobile phone coexistence filter, diplexer, power amplifier, low noise amplifier, and reference crystal oscillator.
- Pre-calibrated for performance: Tuned in manufacturing

Features at a Glance



BRING WI-FI + BLUETOOTH TO EVEN MORE DEVICES

50 Series modules are supported on Linux® and Android™.



ALWAYS CONNECTED, EVEN IN THE HARSHEST CONDITIONS

802.11r + CCKM support for rapid roaming and true TX/RX Diversity with 2x2 MIMO.



MULTIPLE FORM FACTORS TO SUIT DIVERSE NEEDS

Available as a SiP, 60-pin SDIO, M.2 (USB or SDIO), and full wireless bridge subsystem.



ROBUST SECURITY FOR ENTERPRISE DEMANDS

Full list of security standards and EAP types, plus WB's added security via Level 2 bridging.



BROAD CERTIFICATION AND INTERNATIONAL APPROVALS

Certifications and approvals for FCC (USA), IC (Canada), ETSI (Europe), KC (Korea), Giteki (Japan), and RCM (AS/NZ).



PERSONAL SUPPORT FROM DESIGN TO MANUFACTURE

Laird's industry-recognized integration and support organization is dedicated to reducing your time to market.

Application Areas



Connected Hospital/ Medical Devices



IoT Bridging/
Cable Replacement



Industrial/AIDC

Contact Sales - Americas: Europe:

+1 262 375 4400 +44 1628 940 ext. 958 Korea: +82 10 2622 3935 Hong Kong: +852 2923 0610

Laird 50 Series Wi-Fi + Bluetooth 4.0 Modules

Product Brief

Configuration Options

SSD50NBT SiP Module



- Featured on each 50 Series variant
- Smallest footprint (15mm x 15mm x 2.5mm)

Small and customizable

M2US50NBT/M2SD50NBT

USB or SDIO Module



- Popular low-profile M.2 form (E-key type)
- Choose from USB or SDIO interface options
- 22mm x 30mm x 3.3mm

Widely adopted form factor, easier integration

MSD50NBT **SDIO** Module



- Features 60-pin Molex connector for SDIO interface
- 32mm x 22mm x 4.7mm

Upgrade path for existing MSD customers

WB50NBT Standalone Wireless Subsystem



- On-board Linux-based MPU
- Layers of physical/logical security
- Operates independent of host
- 47mm x 37mm x 4.9mm

Secure, robust all-in-one solution

Key Specifications

Category	Feature	Specification
Chipset	Main Chip	Wi-Fi: Qualcomm Atheros QCA6004
	•	Bluetooth: Cambridge Silicon Radio Ltd. (CSR) CSR8811 A08
Interfaces	Logical Interfaces	USB and SDIO (Wi-Fi), UART (Bluetooth)
RF Performance	Transmit Power	Wi-Fi: 12 to 18 dBm. Bluetooth: 3 to 6 dBm
	Typical Receiver Sensitivity	Wi-Fi: -72 to -93 dBm. Bluetooth: -76 to -87 dBm.
	Antenna Options	Pin access (SSD50). 2x U.FL (WB50, MSD50, M2US/M2SD)
Environmental	Operating Temp/Humidity	-30°C to 85°C (-22°F to 185°F). 10 to 90% humidity (non-condensing)
Wi-Fi	Operating Frequency	2.4 GHz to 2.495, 5.15 GHz to 5.825 GHz (including DFS)
	Regulatory Domains	ETSI, FCC, MIC, KCC, IC, AS/NZ (pending)
	Wi-Fi Media	DSSS, CCK, OFDM
	Wi-Fi Media Access Protocol	Carrier sense multiple access with collision avoidance (CSMA/CA)
	Wi-Fi Standards	IEEE 802.11a/b/g/n, 802.11d, 802.11e, 802.11h, 802.11i, 802.11r
Bluetooth	Standards	Bluetooth v2.1 with EDR, Bluetooth 4.0 (Bluetooth Low Energy)
Software	Operating Systems Supported	Linux 3.x.x, 4.0.x kernel, Android 4.1.2 (Jellybean) and newer
Security	Standards	WEP, WPA, WPA2
	Encryption	WEP, TKIP, AES
	Supported EAP Types	EAP-FAST, EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-MSCHAPv2, PEAP-TLS, LEA
Certifications	Applicable Certifications	Wi-Fi Alliance (pending) 802.11a, 802.11b, 802.11g, 802.11n WPA Enterprise, WPA2 Enterprise
		Cisco Compatible Extensions (Version 4) (pending)
		Bluetooth SIG Qualification (pending)
Warranty		Three-year Limited Lifetime

For full specifications on 50 Series modules, please see the appropriate Hardware Integration Guide.

Did You Know?

LSR, a Laird Business, is a leader in Wireless Product Development, offering true end-to-end solutions through its array of services and technical expertise.





Design Services

- RF Hardware and Antenna Design Software/Firmware Development
- Mobile App/Cloud Development
- Industrial Design
- Mechanical Engineering

+1 262 375 4400 Korea: +44 1628 940 ext. 958

EMC Testing & Certification

- On-Site FCC/IC/CE/Giteki/RCM **EMC** Certification
- Wireless and Antenna Testina
- **EMC** Emissions Testing
- International Testing Services

To learn more about LSR visit: www.lsr.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for WiFi Modules - 802.11 category:

Click to view products by Laird Connectivity manufacturer:

Other Similar products are found below:

KBPC10/15/2506WP SX-PCEAN2C-SP 849WM520100E WIFI-AT2350 7265.NGWG.SW HDG204-DN-3 FXX-3061-MIX EMIO-1533-00A2 7265.NGWWB.W PPC-WL-KIT02-R11 RC-CC2640-B HLK-7688A WH-NB73-BA NF-02-PA LSD4BT-E92ASTD001 EAR00364 3168.NGWG MY-WF003U AX210.NGWG.NV ESP-15F32Mbit ESP32-S32Mb TG-01M ESP-13 ESP-01F-2M ESP-01E-2M ESP-20 ESP32-SL ESP-12K-PSRAM ESP-12K-PSRAM-IPEX ESP-12H BW18 BW12-16Mb BW14 BW15 BW16 TG-12F SIM7600CE-L1S CB3S(tjrl) CB3S(hvk9) CB3S(qh6) WB2S(csyd) WB3S(ppty) WB3S(h238) WB3S(uvmz) 1005869 1012 QCA4004X-BL3B 32-2006-BU WT51822-S4AT WT8266-S2