

Innovative **Technology** for a **Connected** World

51G EMI Gaskets

Fabric-over-Foam



UL 94V0 RATED NI/CU NYLON RIPSTOP (NRS) FABRIC-OVER-FOAM

Laird Technologies' Fabric-over-Foam (FoF) 51G EMI gaskets provide excellent EMI shielding performance for customers where EMI issues occur. The 51G Series EMI gaskets are composed of electrically conductive fabric wrapped around a soft urethane foam core. They are supplied with either a conductive or non-conductive pressure sensitive adhesive (PSA), and can be equipped with an Extended Release Liner (ERL) on the adhesive. The 51G is a halogen-free, UL 94V0 rated product that can be created with cross-section profiles such as rectangle, D, C, P, T, knife, bell shapes, and others. The 51G EMI gaskets can be further customized to an application by die-cutting, hole punching, notching, etc.

FEATURES ✓ RoHS


- Fabric-over-Foam gaskets are RoHS compliant
- Halogen-free per IEC-61249-2-21 standard
- UI 94V0
- Low surface resistivity of < 0.07 Ω/□ provides excellent conductivity
- Shielding effectiveness of >100 dB across a wide spectrum of frequencies
- Extremely low compression forces allow for use of lighter materials
- Fabric is highly conductive to provide good EMI shielding and grounding
- Abrasion resistant metallized fabrics show virtually no degradation in electrical performance after 1,000,000 cycles
- Laird Technologies' proprietary coating prevents fabric fraying and fingerprinting
- Available with conductive or non-conductive PSA
- Many cross-section profiles available such as rectangle, D, C, P, T, knife, bell and more
- Profile gaskets can be cut to specified lengths, kiss-cut on release liner, or mitered to form frame configurations

MARKETS




- Cabinet applications
- LCD and Plasma TV
- Medical equipment
- Servers
- Printers
- Laptop computers
- Networking equipment
- Desktop computers
- Telecommunications cabinets

FORCE/DISPLACEMENT/RESISTANCE (FDR)



SHIELDING EFFECTIVENESS (dB)



global solutions: local support ™

USA: +1.866.928.8181 Europe: +49.0.8031.2460.0 Asia: +86.755.2714.1166



51G EMI Gaskets


Fabric-over-Foam

Item	Unit	Value	Test Method		
Shielding Effectiveness					
at 100 MHz		109	SAE-ARP-1705(Mod.)		
at 1 GHz	dB	113	(W10 mm x H8 mm)		
Surface Resistivity	Ω/□	< 0.07	ASTM F390		
Compression Set	%	< 20	ASTM D3574		
Operation Temperature	°C	-40 ~ 70	-		
Flame Retardant	UL 94V0 (UL file No.E1703	327)			
Hazardous Substance	Compliant with RoHS (Directive 2011/65/EU)				
	Compliant with SONY ss-00259				
	Halogen-free (based on IEC-61249-2-21)				

12 months at 23°C/ 60% R.H.

COMPOSITION OF PRODUCT

Shelf Life



Antimony-free


PRESSURE SENSITIVE ADHESIVE (PSA TAPE) OPTIONS

Name	Туре	Thickness (mm)	Peel strength on stainless steel (JIS Z 0237)	Z-axis Resistance
LT-301	Conductive PSA	0.09	> 1.3 kgf/25 mm	$<$ 0.05 Ω
LT-350	PSA	0.12	> 2 kgf/25 mm	-

^{*}Other PSA can be provided. Contact Laird Technologies engineering.

ORDERING INFORMATION

PART NUMBER EXAMPLE



EMI-DS-FOF-51G 0712

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for EMI Gaskets, Sheets, Absorbers & Shielding category:

Click to view products by Laird Performance Materials manufacturer:

Other Similar products are found below:

23-76FSC-SN-24 2-1616323-1 4-1616259-0 3013350A 46J8501020.NN00 3013310A 3013325A 3013308A 3020604 55005106 3021302 3031313 67SLH050050025PI00 3021310 0137131400 6-34UT-070-BD-16 303076048 46J5N03020.NN00 30206025 260737 30395641 3030403 3690103020 HNY-LT15CU4241 46X7503020.NN00 46X7501020.NN00 46W5E02520.NN00 46W5E01520.NN00 302095032 30207032 30210005 46J5N02520.NN00 3021213 3020804 3021004 74273711 74273704 33403 3031210 3031008 3031004 3030903 30308055 303076016 303045018 303035015 3029564 3025602 3023502 3022303