

Hardened Mini Gigabit Ethernet Media Converter 10/100/1000Base-T to 1000Base-SX/LX

The M/GE-ISW Series is an hardened Gigabit Ethernet Mini media converter that provides cost effective media conversion between 10/100/1000Base-T ports and 1000Base-SX/LX ports for hardened or outdoor environments. With its supported operating temperature range of -40°C to +75°C, the Mini offers a space saving alternative for converting copper to fiber in extreme environments.



M/GE-ISW-SFP-01

Key Features

- Unit and Port LEDs allow for quick status information
- Auto-Negotiation
- Fixed Full-Duplex on Fiber
- Auto-MDI/MDIX on copper port
- Active Link Pass Through
- Jumbo Frame (up to 10240Bytes)
- Supports DC and AC Input Power via terminal block
 - If the voltage of your power source doesn't match the device input power, external power supplies are available
 - Includes barrel connector pig-tail cable
- Multiple mounting options
 - DIN Rail clip and Velcro included
 - Wall mount bracket sold separately
- Overload Current Protection
- Reverse Polarity Protection

Specifications

Standards	IEEE 802.3 IEEE 802.3u IEEE 802.3ab IEEE 802.3z IEEE 802.3x
Max Frame Size	10240 bytes
Status LEDs	PWR (Power): (below RJ-45) ON = Lit for normal operation FX-Link/Act (Fiber Link/Activity): (Upper Left on RJ-45) On = link; Flashing = Activity TX-Link/Act (Copper Link/Activity): (Upper Right on RJ-45) On = link; Flashing = Activity
Dimensions	Width: 1.8" [46 mm] Depth: 3.3" [85 mm] Height: 0.85" [22 mm]
Power Consumption	1.2 Watts
Power Input	2-pin terminal block Unit accepts 12 - 48 VDC or 24 - 36VAC (External power supplies sold separately)
Ingress Protection	IP20
Environment	Operating: -40°C to +75°C Storage: -40°C to +85°C Humidity: 5% to 95% (non-condensing) Altitude: 0 - 10,000 ft.
Weight	0.40 lbs. [0.18 kg]
MTBF	Greater than 41,680 hours (MIL-HDBK-217F) Greater than 114,580 hours (Bellcore7 V5.0)
Certifications	FCC Class A, CISPR22/EN55022 Class A, EN55034, CE Mark
Warranty	Lifetime

Ordering Information

M/GE-ISW-SX-01
10/100/1000Base-T (RJ-45) to 1000Base-SX, SC, multimode, [62.5/125 um: 220 m/722 ft.] [50/125 um: 550 m/1804 ft.]
Link Budget: 7.5 dB

M/GE-ISW-LC-01
10/100/1000Base-T (RJ-45) to 1000Base-SX, LC, multimode, [62.5/125 um: 220 m/722 ft.] [50/125 um: 550 m/1804 ft.]
Link Budget: 8.0 dB

M/GE-ISW-LX-01
10/100/1000Base-T (RJ-45) to 1000Base-LX, SC, single mode, [10 km/6.2 mi.] Link Budget: 10.5 dB

M/GE-ISW-SFP-01
10/100/1000Base-T (RJ-45) to 100/1000Base-X Open SFP Slot

Optional Accessories (sold separately)

SFP Modules

Power Supplies (sold separately)

SPS-UA12DHT
12 VDC, 18W, External AC/DC Desktop Power Supply

25165
Universal AC/DC Input DIN Rail Mountable +12 VDC Power Supply

Mounting Options (sold separately)

WMBM
Wall Mount Bracket Mini

RMBM
Rack Mount Bracket for Mini Media Converters in the RMS19-SA4-02

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Media Converters](#) category:

Click to view products by [Lantronix](#) manufacturer:

Other Similar products are found below :

[CF-020010-264](#) [RSM3485PCT](#) [CAN-BUS-XL2515](#) [CTM1051KAT](#) [TD322D485H-A](#) [CTM1051KT](#) [TD322DCAN](#) [TD301D485H](#)
[CTM8251KD](#) [CTM8251KAT](#) [RSM3485IDHT](#) [RSM3485CT](#) [CTM8251KT](#) [RSM485IDHT](#) [CTM1051T](#) [TD501D485H-E](#) [RSM485ECHT](#)
[TD501DCANH3](#) [TD501DCAN](#) [CTM8251AT](#) [TD301D485H-A](#) [TD301DCAN](#) [TD522DCAN](#) [TD321D485H-A](#) [RSM485PHT](#) [RSM485PCT](#)
[TD522D485H-A](#) [CTM8251KAD](#) [TD501D485H](#) [RSM3485IQHT](#) [CTM1051AMG](#) [CTM1051MG](#) [RSM485LECHT](#) [SC1510R](#) [CSM300](#)
[CTM8251AT](#) [TD302DCAN](#) [TD301MCAN](#) [CTM1051M](#) [TD301MCANFD](#) [TD301DCAN](#) [CTM1051](#) [CTM1051T](#) [TD322DCAN](#)
[TD301DCANH3](#) [TD522DCAN](#) [CTM1051AT](#) [CTM1051AMG](#) [CTM8251T](#) [CTM1051KT](#)