



Spider Duo

Remote-KVM/IP
with Local Access



COMPACT KVM-OVER-IP PLUS LOCAL ACCESS FOR DISTRIBUTED SERVER MANAGEMENT

The Lantronix® Spider Duo KVM-over-IP is the newest in the popular Spider family of remote KVM solutions. Spider Duo provides secure, remote KVM (keyboard, video and mouse)-over-IP capabilities, as well as transparent local access.



Flexible KVM-over-IP

The Spider Duo is ideal for those who need local access, as well as the flexibility of KVM-over-IP in a single integrated solution. Its palm-sized, “zero-U” design is perfect for space-constrained applications. What’s more, Spider Duo requires no additional software and allows full BIOS level control of the host system.



Secure Remote Management

Spider Duo makes administration a breeze. Using integrated Virtual Media, users can transfer files, perform upgrades, install patches, redirect local drives and perform full system upgrades by ISO file. Coupled with the optional single port PCU (power control unit), authorized users can also initiate system reboots over the network. Spider Duo allows complete local, plus remote management of the host machine anytime, from virtually anywhere. It provides reliable, secure access to servers located in data centers, kiosks, regional offices, campuses, ATMs, point of sale (POS), training centers, or test and development labs.

Spider Duo Highlights

- Reduce costs and decrease downtime by remotely managing PCs and servers, down to the BIOS level, while still allowing transparent local access
- Transfer files, install patches, perform upgrades remotely with Virtual Media
- Remotely manage power with the optional power control unit
- Easy configuration and installation with color coded connectors—local and remote management are up and running in minutes

Features and Specifications

Security

- In-Band (Ethernet) - Dual Ethernet ports
- Hardware based encryption of keyboard, mouse and video data
- IP Source Address Filtering
- Remote Authentication: LDAP, RADIUS, Active Directory
- User/Group management with permissions control
- Configurable port numbers (HTTP, HTTPS, Telnet, SSH)
- Selective disable of Telnet/SSH

Access

- Local access and up to 8 simultaneous remote users

Target Server Requirements

- Supports Multiple Operating Systems: Windows® 2000/2003/2008/XP/Vista/7, Linux, or MAC OS X® 10
- Keyboard/mouse: 1 USB, 1 PS/2
- keyboard, and 1 PS/2 mouse connector
- Video Interface: HD15 VGA video output (up to 1600x1200@60Hz)

Client System Requirements

- Internet Explorer® 6.0+, Netscape 5.0+, Firefox® 3.0+, Safari® 2.0+
- PIII Processor equivalent or better (recommended)
- Sun Java 2 Runtime Environment
- Telnet/SSH client for command line (CLI) access

Interfaces

- Network: 10/100Base-T Ethernet Port with activity indicators (RJ45)
- Serial: RS-232, up to 115,200 bps for serial device pass-through, unit configuration or PCU controller
- USB
- Local KVM connector
- Computer input connector

Cables

- Includes local KVM and computer input USB or USB and PS/2, 21.6" VGA cables

Environmental

- Operating: 0° to 45° C (32° to 115° F)
- Storage: -20° to 70° C (-4° to 158° F)
- Humidity: 0 to 95% RH (non-condensing)
- Heat Dissipation: 4-8 Watts (14-28 BTU/hr)

Power Requirements

- Input: 5 VDC @ 1.6A max.

Certifications

- UL/CUL (CSA-22.2 No. 60950-1-03 / UL-60950-1)
- CE - IEC 60950-1
- C-Tick
- FCC Part 15, Equipment Class A
- VCCI V-3/2006.04 Class A
- AS/NZS CISPR 22: 2006 Class A
- EN55022:1998 +A1:2000
- +A2:2003 Class A
- EN61000-3-2: 2000 +A2: 2005 Class A
- EN61000-3-3: 1995 +A1: 2001
- EN55024: 1998 +A1:2001 +A2:2003
- RoHS Compliant

Warranty

- 2-year limited warranty

Form Factor

- Dimensions: (H x W x D) 13.2 x 5.8 x 3.6 cm (5.2 x 2.3 x 1.4 in)
- Weight: USB: 269g (9.50 oz), PS/2: 278g (9.80 oz)

Ordering Information

Part Number	Description
SLSLP400USB-01	1 Port Local plus Remote KVM-over-IP with USB Connectors; 21.6" VGA cables
SLSLP400PS2-01	1 Port Local + Remote KVM-over-IP with PS/2 and USB Connectors; 21.6" VGA cables

Accessories

Part Number	Description
PCU100-01	Single port power control unit, 100-240VAC, 50/60Hz, 10A (Includes IEC320/C13 to NEMA inlet and IEC320/C14 to IEC320/C13 outlet power cables)
500-199-R	Extended length cable (computer input) USB connector; 59" VGA cable
500-200-R	Extended length cable (computer input) PS/2 and USB connectors; 59" VGA cable
520-156-R	Replacement DC Power Supply with International Adapters (100-240VAC, 50-60 Hz; 5 VDC @ 2A)

Contact Information

Americas

Call: 800.422.7055
sales@lantronix.com
http://www.lantronix.com
NASDAQ: LTRX

Asia/Pacific/Japan

Call: +852 3428.2338
asiapacific_sales@lantronix.com

China: +86.21.6237.8868
Shanghai@lantronix.com

India: +91 994-551-2488
sales_india@lantronix.com

Indonesia: +91 994-551-2488
sales_indonesia@lantronix.com

Japan: +81.3.3273.8850
Sales_Japan@lantronix.com

Europe

Call: +31 (0) 76.52.3.6.74 4
EMEA@lantronix.com



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Interface Modules](#) category:

Click to view products by [Lantronix](#) manufacturer:

Other Similar products are found below :

[8500-003](#) [IFD8520](#) [cPCI-3544](#) [422CON](#) [ATX6022/14GP7](#) [ATX6022/8](#) [AX93221-24/48](#) [FC6A-EXM2](#) [OPT8AP-AE](#) [60006-016](#)
[96RMKVM-19V1C-A](#) [60016-011](#) [60016-014](#) [60006-008](#) [60016-015](#) [60011-075](#) [HPCI-14S12U](#) [cBP-3208](#) [cBP-3062A](#) [FAB205-6P5](#)
[ATX6022/6](#) [60016-012](#) [96RMKVM-17V1C-A](#) [PCE-DP10-00A1E](#) [MOS-1120Y-0201E](#) [96RMLCD-17V1-A](#) [96RMKVM-17V8C-A](#) [60004-](#)
[005](#) [60016-017](#) [60006-019](#) [60006-009](#) [60016-035](#) [60016-034](#) [60016-031](#) [60016-030](#) [60016-026](#) [60016-025](#) [60016-024](#) [60016-021](#) [60016-](#)
[018](#) [60016-007](#) [60016-006](#) [60016-005](#) [60016-004](#) [60007-002](#) [60006-018](#) [60006-010](#) [AXX10GBTWLHW3](#) [382-BBEH](#) [555-BDCL](#)