

## ÖLFLEX® 140\*

H05VV5-F (EN 50525-2-51)

ÖLFLEX® 140 - H05VV5-F harmonised PVC control cable, oil-resistant, flexible and numbered for various applications, U<sub>0</sub>/U: 300/500 V

### Info

Oil-resistant according to EN 50363-4-1: TM5

Harmonised (HAR): H05VV5-F

CPR: Article number choice under [www.lappkabel.com/cpr](http://www.lappkabel.com/cpr)



Good chemical resistance



Oil-resistant

### Benefits

High acceptance in Europe due to Harmonisation

### Application range

Plant engineering

Industrial machinery

Heating and air-conditioning systems

Machine tools

Mainly used in dry, damp and wet interiors (including water-oil mixtures), but not for outdoor use

For fixed installation under medium mechanical load conditions, and applications with occasional flexing at free, non-continuously recurring movement without tensile load or compulsory guidance

### Product features

Flame-retardant according IEC 60332-1-2

Oil-resistant according to EN 50363-4-1: TM5

Last Update (18.02.2021)

©2021 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## ÖLFLEX® 140\*

### Norm references / Approvals

EN 50525-2-51

### Product Make-up

Fine-wire strand made of bare copper wires

PVC core insulation

Cores twisted in layers

PVC outer sheath, high oil-resistance, grey (similar to RAL 7001)

### Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000104 ETIM 5.0 Class-Description: Control cable
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000104 ETIM 6.0 Class-Description: Control cable
Core identification code:	Black with white numbers acc. to VDE 0293-334
Conductor stranding:	Fine wire according to VDE 0295, class 5/IEC 60228 class 5
Minimum bending radius:	Occasional flexing: 12.5 x outer diameter Fixed installation: 4 x outer diameter
Nominal voltage:	U0/U: 300/500 V
Test voltage:	2000 V
Protective conductor:	G = with GN-YE protective conductor X = without protective conductor
Temperature range:	Occasional flexing: -5°C to +70°C Fixed installation: -40°C to +70°C

### Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths)

Packaging size: coil  $\leq$  30 kg or  $\leq$  250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

\* Trade product, no Lapp product

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter [mm]	Copper index (kg/km)
ÖLFLEX® 140 H05VV5-F			
0011000	3 G 0.5	5.5 - 7	14.4
0011104	4 G 0.5	6.2 - 7.9	19.2
0011001	5 G 0.5	6.8 - 8.6	24
0011002	7 G 0.5	8.3 - 10.4	33.6
0011003	12 G 0.5	10.4 - 12.9	58
0011004	18 G 0.5	12.3 - 15.3	86.4
0011005	25 G 0.5	14.8 - 18.3	120
0011006	34 G 0.5	17.2 - 21.2	163.2
0011009	3 G 0.75	6 - 7.6	21.6
0011204	4 G 0.75	6.6 - 8.3	28.8
0011010	5 G 0.75	7.4 - 9.3	36
0011011	7 G 0.75	9 - 11.3	50
0011012	12 G 0.75	11 - 13.7	86
0011013	18 G 0.75	13.2 - 16.4	130
0011014	25 G 0.75	15.8 - 19.5	180
0011015	34 G 0.75	18.4 - 22.6	245
0011241	41 G 0.75	20.1 - 24.7	296
0011018	3 G 1.0	6.3 - 8	28.8
0011304	4 G 1.0	6.9 - 8.7	38.4
0011019	5 G 1.0	7.8 - 9.8	48
0011020	7 G 1.0	9.5 - 11.8	67
0011021	12 G 1.0	11.8 - 14.6	115
0011022	18 G 1.0	14 - 17.2	173
0011023	25 G 1.0	16.8 - 20.7	240
0011024	34 G 1.0	19.6 - 24	326
0011341	41 G 1.0	21.4 - 26.2	394
0011027	3 G 1.5	7.4 - 9.4	43
0011404	4 G 1.5	8.2 - 10.2	58
0011028	5 G 1.5	9.1 - 11.4	72
0011029	7 G 1.5	11.3 - 14.1	101
0011030	12 G 1.5	13.8 - 17	173
0011031	18 G 1.5	16.5 - 20.3	259
0011032	25 G 1.5	19.8 - 24.3	360

Last Update (18.02.2021)  
 ©2021 Lapp Group - Technical changes reserved  
 Product Management www.lappkabel.de  
 You can find the current technical data in the corresponding data sheet:  
 PN 0456 / 02\_03\_16

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter [mm]	Copper index (kg/km)
0011033	34 G 1.5	23.1 - 28.2	490
0011036	3 G 2.5	9 - 11.2	72
0011504	4 G 2.5	10.1 - 12.5	96
0011037	5 G 2.5	11 - 13.7	120
0011038	7 G 2.5	13.6 - 16.8	168
0011039	12 G 2.5	16.8 - 20.6	288
0011045	14 G 2.5	18.3 - 22.7	336
0011040	18 G 2.5	20.2 - 24.8	432
0011041	25 G 2.5	24.2 - 29.6	600

Last Update (18.02.2021)

©2021 Lapp Group - Technical changes reserved  
Product Management [www.lappkabel.de](http://www.lappkabel.de)  
You can find the current technical data in the corresponding data sheet.  
PN 0456 / 02\_03\_16

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Ribbon Cables / IDC Cables](#) category:*

*Click to view products by [Lapp Kabel](#) manufacturer:*

Other Similar products are found below :

[FSK-12A](#) [AWG28-10G](#) [EHJ3C](#) [EHJ4C](#) [FSP-25A](#) [cab-LVDV-DAT-34-15](#) [49635-C62-S2](#) [1-3636-600-5204](#) [92315-1408](#) [426171120-3](#) [2-1589735-3](#) [JSM015PP2DCC23N](#) [92301-0283](#) [ACL-eSSI-2](#) [92301-0718](#) [MMSDT-06-20-S-05.5-D-K-LDX](#) [IDD-04-G](#) [NM-2J2-051-PS1-JJAB](#) [1700/26SF \(100FT\)](#) [1700/34SF \(100FT\)](#) [3801/09 \(100FT\)](#) [DS1058-08M28-30.5](#) [DS1058-30M28-30.5](#) [0015712](#) [0015905](#) [S30109](#)  
[11203](#) [11223](#) [11243](#) [11262](#) [0037147](#) [0022512](#) [0022412](#) [0022416](#) [0022421](#) [0022632](#) [0022602](#) [0022502](#) [0022603](#) [0022403](#) [0022604](#)  
[0022404](#) [0022605](#) [0022505](#) [0022405](#) [0022607](#) [0022608](#) [0022508](#) [0022408](#) [0011022](#)